

# Documented Code For tracklang v1.6.3

Nicola L.C. Talbot

Dickimaw Books

<http://www.dickimaw-books.com/>

2025-01-22

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Main Package Code</b>	<b>2</b>
<b>3</b>	<b>L<sup>A</sup>T<sub>E</sub>X Code (tracklang.sty)</b>	<b>2</b>
<b>4</b>	<b>Generic Code (tracklang.tex)</b>	<b>7</b>
4.1	Internal Lists . . . . .	21
4.2	Known Languages . . . . .	24
4.3	Mappings . . . . .	27
4.4	Tracking Languages and Dialects . . . . .	37
4.5	Predefined Root Languages . . . . .	55
4.6	Predefined Dialects . . . . .	69
4.7	Dialect Option Synonyms . . . . .	79
4.8	Conditionals and Loops . . . . .	84
4.9	Resources . . . . .	124
<b>5</b>	<b>Regions Generic Code (tracklang-region-codes.tex)</b>	<b>135</b>
<b>6</b>	<b>ISO 15924 Scripts L<sup>A</sup>T<sub>E</sub>X Package (tracklang-scripts.sty)</b>	<b>143</b>
<b>7</b>	<b>ISO 15924 Scripts Generic Code (tracklang-scripts.tex)</b>	<b>143</b>

## 1 Introduction

This is the documented code for the tracklang package. See tracklang-manual.pdf for the main user guide.

## 2 Main Package Code

### 3 L<sup>A</sup>T<sub>E</sub>X Code (tracklang.sty)

To ensure maximum portability this file only uses L<sup>A</sup>T<sub>E</sub>X kernel commands, rather than using more convenient commands provided by packages such as etoolbox.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{tracklang}[2025/01/22 v1.6.3 (NLCT) Track Languages]
```

```
\@tracklang@declareoption Set up package options.
```

```
\providecommand*{\@tracklang@declareoption}[1]{%
  \DeclareOption{#1}{\TrackPredefinedDialect{#1}}%
}
```

Load generic code:

```
\input{tracklang}
```

There are no other options as this package will typically be loaded using `\RequirePackage` by a package. Explicitly adding an option at that point might create a package option clash. The declared package options are all the possible language names that might be passed as a document class option. (Also, adding any non-language options here will interfere with `\@tracklang@declaredoptions`.)

```
\let\@tracklang@declaredoptions\@declaredoptions
```

Version 1.6.3: however, it's useful to pick up `verbose` passed in the document class and this shouldn't conflict with any language label.

```
\DeclareOption{verbose}{\TrackLangShowVerbosetrue}
\DeclareOption{noverbose}{\TrackLangShowVerbosefalse}
\ProcessOptions
```

Unset `\@tracklang@declareoption`:

```
\let\@tracklang@declareoption\@gobble
```

In the event that the language hasn't been supplied through the package options (or through the class options, which the package options should process provided the document class has used the standard option declarations) we need to check if any of the known language packages have been loaded. This is a bit risky as it relies on the packages not changing their internal language macros. It would be easier if all the language packages could provide a reliable user interface to determine which languages (and variants) have been loaded.

```
\@tracklang@prelangpkgcheck@hook In the event that any of the language packages choose to load this package
and use tracklang.tex's commands to identify the tracked languages and re-
gions, then they can first define \@tracklang@prelangpkgcheck@hook to do
\endinput which will skip the checks.
```

```
\csname @tracklang@prelangpkgcheck@hook\endcsname
```

```
\ifx\@tracklang@languages\@empty
```

First try babel. If babel has been loaded, the languages are stored in `\bbl@loaded`, so check if this command has been defined, and if it has add those languages.

```
\@ifundefined{bbl@loaded}%  
{%
```

If translator has been loaded, the languages are stored in `\trans@languages`

```
\@ifundefined{trans@languages}  
{%
```

Has ngerman been loaded?

```
\@ifpackageloaded{ngerman}%  
{%  
  \@tracklang@add@ngerman  
}%  
{%
```

Has german been loaded?

```
\@ifpackageloaded{german}%  
{%  
  \@tracklang@add@german  
}%  
{%
```

Has polyglossia been loaded?

```
\@ifpackageloaded{polyglossia}  
{%
```

polyglossia now provides `\xpg@bcp@loaded`, which contains a comma-separated list of language tags, so use that if it exists.

```
\@ifundefined{xpg@bcp@loaded}%  
{%
```

Older versions: polyglossia sets `\langle lang \rangle@loaded` for each loaded language, so check this for all known languages. I don't know how to consistently check for variants. (Conditionals such as `\if@british@locale` are set immediately with `\setotherlanguage` but are deferred to the start of the document with `\setmainlanguage`, which is too late for tracklang.) Script names seem to be stored in `\xpg:scripttag@⟨language⟩` but again this doesn't seem to be set for the main language until the start of the document. New versions of polyglossia store the list of loaded languages in `\xpg@loaded`, so check if this is defined.

```
\@ifundefined{xpg@loaded}%  
{%
```

`\xpg@loaded` isn't defined, so iterate over known options and check if the language has been loaded.

```
\PackageInfo{tracklang}{polyglossia loaded but  
\string\xpg@loaded\space not defined. Will attempt  
to track known languages.}%  
\@for\this@language:=\@tracklang@declaredoptions\do{%
```

```

\@ifundefined{\this@language @loaded}%
{%
  {\@nameuse{@tracklang@add@\this@language}}%
}%
}%
{%
\@for\this@language:=\xpg@loaded\do{%
  \@ifundefined{@tracklang@add@\this@language}%
  {%
    \PackageWarning{tracklang}%
      {Adding unknown polyglossia language ‘\this@language’}%

    \AddTrackedLanguage{\this@language}%
  }%
  {\@nameuse{@tracklang@add@\this@language}}%
}%
}%
}%
{%
\@for\this@language:=\xpg@bcp@loaded\do{%

```

These are language tags, which is more convenient.

```

\expandafter\TrackLanguageTag{\this@language}%
}%
}%

```

The `\xpg@bcp@loaded` list doesn't seem to include the main language until the start of the document environment but `\mainbabelname` is defined after `\setmainlanguage`. I'm not sure if `\mainbabelname` was provided in the same version of polyglossia as `\xpg@bcp@loaded` or a different one, so have a separate conditional.

```

\@ifundefined{mainbabelname}{}%
{%
  \let\@org@tracklang@add@latex\@tracklang@add@latex
  \def\@tracklang@add@latex{%
    \PackageWarning{tracklang}%
      {Can't detect polyglossia main language. It may
       not have been set yet}%
  }%
  \@ifundefined{@tracklang@add@\mainbabelname}%
  {%
    \PackageWarning{tracklang}%
      {Adding unknown polyglossia main babel name ‘\mainbabelname’}%
    \expandafter\AddTrackedLanguage{\mainbabelname}%
  }%
  {%
    \@nameuse{@tracklang@add@\mainbabelname}%
  }%
  \let\@tracklang@add@latex\@org@tracklang@add@latex
}%

```

```
}%
{%
```

None of the known packages have been loaded, so do nothing in case another package wants to load this one before setting up the language options. However, if at this point babel has been loaded, then it's an older version that hasn't defined `\bbl@loaded` so check for this.

```
\@ifpackageloaded{babel}
{%
  \PackageInfo{tracklang}{babel loaded but
  \string\bbl@loaded\space not defined. Will attempt
  to track known languages.}%
  \@for\this@language:=\@tracklang@declaredoptions\do{%
    \ifundefined{captions\this@language}%
    {%
      {\@nameuse{\@tracklang@add\this@language}}%
    }%
  }%
}%
}%
{%
```

Add from translator. If translator has been loaded, the language names are stored in `\trans@languages` but these are labels used by translator, so some mapping is required.

```
\let\@tracklang@add@Acadian\@tracklang@add@acadian
\let\@tracklang@add@French\@tracklang@add@french
\let\@tracklang@add@Afrikaans\@tracklang@add@afrikaans
\let\@tracklang@add@Dutch\@tracklang@add@dutch
\let\@tracklang@add@AmericanEnglish\@tracklang@add@american
\let\@tracklang@add@Austrian\@tracklang@add@austrian
\@namedef{\@tracklang@add@Austrian1997}{\@tracklang@add@naustrian}
\let\@tracklang@add@Bahasa\@tracklang@add@bahasa
\let\@tracklang@add@Basque\@tracklang@add@basque
\let\@tracklang@add@Brazilian\@tracklang@add@brazil
\let\@tracklang@add@Portuguese\@tracklang@add@portuguese
\let\@tracklang@add@Breton\@tracklang@add@breton
\let\@tracklang@add@BritishEnglish\@tracklang@add@british
\let\@tracklang@add@Bulgarian\@tracklang@add@bulgarian
\let\@tracklang@add@Canadian\@tracklang@add@canadian
\let\@tracklang@add@Canadien\@tracklang@add@canadien
\let\@tracklang@add@Catalan\@tracklang@add@catalan
\let\@tracklang@add@Croatian\@tracklang@add@croatian
\let\@tracklang@add@Czech\@tracklang@add@czech
\let\@tracklang@add@Danish\@tracklang@add@danish
\let\@tracklang@add@Dutch\@tracklang@add@dutch
\let\@tracklang@add@English\@tracklang@add@english
```

```

\let\@tracklang@add@Esperanto\@tracklang@add@esperanto
\let\@tracklang@add@Estonian\@tracklang@add@estonian
\let\@tracklang@add@Finnish\@tracklang@add@finnish
\let\@tracklang@add@French\@tracklang@add@french
\let\@tracklang@add@Galician\@tracklang@add@galician
\let\@tracklang@add@German\@tracklang@add@german
\@namedef{@tracklang@add@German1997}{\@tracklang@add@ngerman}
\let\@tracklang@add@Greek\@tracklang@add@greek
\let\@tracklang@add@Polutoniko\@tracklang@add@polutoniko
\let\@tracklang@add@Hebrew\@tracklang@add@hebrew
\let\@tracklang@add@Hungarian\@tracklang@add@hungarian
\let\@tracklang@add@Icelandic\@tracklang@add@icelandic
\let\@tracklang@add@Irish\@tracklang@add@irish
\let\@tracklang@add@Italian\@tracklang@add@italian
\let\@tracklang@add@Latin\@tracklang@add@latin
\let\@tracklang@add@LowerSorbian\@tracklang@add@lowersorbian
\let\@tracklang@add@Magyar\@tracklang@add@magyar
\let\@tracklang@add@Nynorsk\@tracklang@add@nynorsk
\let\@tracklang@add@Norsk\@tracklang@add@norsk
\let\@tracklang@add@Polish\@tracklang@add@polish
\let\@tracklang@add@Portuguese\@tracklang@add@portuguese
\let\@tracklang@add@Romanian\@tracklang@add@romanian
\let\@tracklang@add@Russian\@tracklang@add@russian
\let\@tracklang@add@Scottish\@tracklang@add@scottish
\let\@tracklang@add@Serbian\@tracklang@add@serbian
\let\@tracklang@add@Slovak\@tracklang@add@slovak
\let\@tracklang@add@Slovene\@tracklang@add@slovene
\let\@tracklang@add@Spanish\@tracklang@add@spanish
\let\@tracklang@add@Swedish\@tracklang@add@swedish
\let\@tracklang@add@Turkish\@tracklang@add@turkish
\let\@tracklang@add@Ukrainian\@tracklang@add@ukrainian
\let\@tracklang@add@UpperSorbian\@tracklang@add@uppersorbian
\let\@tracklang@add@Welsh\@tracklang@add@welsh

```

Now iterate through the declared languages:

```

\@for\this@language:=\trans@languages\do{%
  \ifundefined{@tracklang@add@\this@language}{}%
  {\@nameuse{@tracklang@add@\this@language}}%
}%
}%
}%
{%

```

Add from babel

```

\@for\this@language:=\bbl@loaded\do{%
  \ifundefined{@tracklang@add@\this@language}%
  {%
    \PackageWarning{tracklang}%
      {Adding unknown babel language ‘\this@language’}%
    \AddTrackedLanguage{\this@language}%
  }
}

```

```

    }%
    {\@nameuse{@tracklang@add@this@language}}%
  }%

```

If babel has been loaded with serbian, then the script needs to be set to Latn.  
(The Cyrillic script is provided with serbianc.)

```

    \ifx\captionsserbian\undefined
    \else
      \SetTrackedDialectScript{serbian}{Latn}%
    \fi
  }

```

End of check for language packages

```
\fi
```

## 4 Generic Code (tracklang.tex)

Does the category code of @ need changing?

```
\@tracklang@restore@at
```

```

\ifnum\catcode'\@=11\relax
  \def\@tracklang@restore@at{}%
\else
  \expandafter\edef\csname @tracklang@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@ \relax
  }%
  \catcode'\@=11\relax
\fi

```

First check if this file has already been loaded:

```

\ifx\@tracklang@languages\undefined
\else
  \@tracklang@restore@at
  \expandafter\endinput
\fi

```

Version info.

```

\expandafter\def\csname ver@tracklang.tex\endcsname{%
  2025/01/22 v1.6.3 (NLCT) Track Languages Generic Code}

```

Define a long command for determining the existence of a control sequence by its name. (`\relax` is considered undefined.)

```
\@tracklang@ifundef
```

```

\long\def\@tracklang@ifundef#1#2#3{%
  \ifcsname#1\endcsname
    \expandafter\ifx\csname #1\endcsname\relax
      #2%
    \else
      #3%

```

```

    \fi
  \else
    \expandafter\ifx\csname #1\endcsname\relax
      #2%
    \else
      #3%
    \fi
  \fi
}
\ifcsname is an eTeX primitive. Need to check if it's defined.
\ifx\ifcsname\undefined
Not using eTeX.

```

```

  \long\def\@tracklang@ifundef#1#2#3{%
    \expandafter\ifx\csname #1\endcsname\relax
      #2%
    \else
      #3%
    \fi
  }

```

Can't have an else part here as TeX won't recognise `\ifcsname` and we'll have an unmatched end brace.

```
\fi
```

The shell escape stuff needs the Plain TeX version of `\input`. This is `\@@input` if we're using L<sup>A</sup>T<sub>E</sub>X.

```

\@tracklang@input
\ifx\@@input\undefined
  \let\@tracklang@input\input
  \def\@tracklang@inputfile#1{\input #1\relax}
\else
  \let\@tracklang@input\@@input
  \def\@tracklang@inputfile#1{\input{#1}}
\fi

```

Provide some commands in case the L<sup>A</sup>T<sub>E</sub>X kernel hasn't been loaded.

```

\@tracklang@nnil
\ifx\@nnil\undefined
  \def\@tracklang@nnil{\@nil}
\else
  \let\@tracklang@nnil\@nnil
\fi

```

```

\@tracklang@for
\ifx\@for\undefined
  \long\def\@tracklang@for#1:=#2\do#3{%
    \expandafter\def\expandafter\@fortmp\expandafter{#2}%

```



```

\ifx\@fortmp\empty
\else
\expandafter
\@tracklang@forloop #2,\@nil,\@nil\@@ #1{#3}%
\fi
}
\long\def\@tracklang@forloop#1,#2,#3\@@ #4#5{%
\def #4{#1}%
\ifx#4\@tracklang@nnil
\else
#5%
\def #4{#2}%
\ifx#4\@tracklang@nnil
\else
#5%
\@tracklang@iforloop #3\@@ #4{#5}%
\fi
\fi
}
\long\def\@tracklang@iforloop#1,#2\@@ #3#4{%
\def#3{#1}%
\ifx#3\@tracklang@nnil
\expandafter
\@tracklang@fornoop
\else
#4\relax
\expandafter\@tracklang@iforloop
\fi
#2\@@ #3{#4}%
}
\long\def\@tracklang@fornoop#1\@@ #2#3{}
\else
\let\@tracklang@for\@for
\fi

```

\@tracklang@namedef

```

\ifx\@namedef\undefined
\def\@tracklang@namedef#1{\expandafter\def\csname#1\endcsname}
\else
\let\@tracklang@namedef\@namedef
\fi

```

\@tracklang@enamedef

```

\def\@tracklang@enamedef#1{\expandafter\edef\csname#1\endcsname}

```

\@tracklang@nameuse

```

\def\@tracklang@nameuse#1{%
\@tracklang@ifundef{#1}{-}{\csname#1\endcsname}%
}

```

```
\@tracklang@ifcseqcsname{<cs>}{<csname>}{<true>}{<false>}
```

`\@tracklang@ifcseqcsname`

Compares two commands, the first is reference as a control sequence the second is referenced as a control sequence name. Condition is false if the second isn't defined (no check for the existence of the first).

```
\def\@tracklang@ifcseqcsname#1#2#3#4{%
  \@tracklang@ifundef{#2}{#4}%
  {%
    \expandafter\ifx\expandafter#1\csname#2\endcsname
    #3%
  }
  \else
  #4%
  \fi
}%
}
```

`\@tracklang@sanitize`

```
\ifx\@onelevel@sanitize\undefined
  \def\@tracklang@sanitize#1{%
    \edef#1{\expandafter\@tracklang@strip@prefix\meaning#1}%
  }
  \def\@tracklang@strip@prefix#1>{}
\else
  \let\@tracklang@sanitize\@onelevel@sanitize
\fi
```

`\@tracklang@firstoftwo`

```
\long\def\@tracklang@firstoftwo#1#2{#1}
```

`\@tracklang@secondoftwo`

```
\long\def\@tracklang@secondoftwo#1#2{#2}
```

`\@tracklang@err`

```
\ifx\PackageError\undefined
  \def\@tracklang@err#1#2{%
    \errhelp{#2}%
    \errmessage{tracklang: #1}}
\else
  \def\@tracklang@err#1#2{\PackageError{tracklang}{#1}{#2}}
\fi
```

`\ifTrackLangShowWarnings` Allow user to switch warnings on or off.

```
\newif\ifTrackLangShowWarnings
\TrackLangShowWarningstrue
```

`\@tracklang@pkgwarn` Provided for related packages such as texosquery.

```
\ifx\PackageWarning\undefined
  \def\@tracklang@pkgwarn#1#2{%
```

```

        \ifTrackLangShowWarnings
        {%
            \newlinechar='\^^J
            \def\MessageBreak{^^J}%
            \message{^^J#1 Warning: #2 on line \the\inputlineno.^^J}%
        }%
    \fi
}
\else
\def\@tracklang@pkgwarn#1#2{%
    \ifTrackLangShowWarnings
    \PackageWarning{#1}{#2}%
    \fi
}
\fi

```

\@tracklang@warn

```

\def\@tracklang@warn#1{\@tracklang@pkgwarn{tracklang}{#1}}%

```

\ifTrackLangShowInfo Allow user to switch information messages on or off.

```

\newif\ifTrackLangShowInfo
\TrackLangShowInfotrue

```

\@tracklang@info

```

\ifx\PackageInfo\undefined
\def\@tracklang@info#1{%
    \ifTrackLangShowInfo
    {%
        \newlinechar='\^^J
        \def\MessageBreak{^^J}%
        \message{^^Jtracklang Info: #1 on line \the\inputlineno.^^J}%
    }%
    \fi
}%
\else
\def\@tracklang@info#1{%
    \ifTrackLangShowInfo
    \PackageInfo{tracklang}{#1}%
    \fi
}%
\fi

```

\ifTrackLangShowVerbose Allow user to switch verbose (debugging) information messages on or off. Note that verbose information will be off regardless of this switch if the info switch is off.

```

\newif\ifTrackLangShowVerbose
\TrackLangShowVerbosefalse

```

\@tracklang@verbose

```

\def\@tracklang@verbose#1{%
  \ifTrackLangShowVerbose
    \@tracklang@info{#1}%
  \fi
}%

```

\@tracklang@ifFileExists

```

\ifx\IfFileExists\undefined
\long\def\@tracklang@ifFileExists#1#2#3{%
  \openin0=#1 %
  \ifeof0\relax
    \def\@tracklang@tmp{#3}%
  \else
    \closein0\relax
    \edef\@filef@und{#1 }%
    \def\@tracklang@tmp{#2}%
  \fi
  \@tracklang@tmp
}

\else
  \let\@tracklang@ifFileExists\IfFileExists
\fi

```

\TrackLangEncodingName Provide a default encoding name to avoid repeated tests to determine whether or not \inputencodingname has been defined.

```

\ifx\inputencodingname\undefined
\def\TrackLangEncodingName{utf8}
\else
\def\TrackLangEncodingName{\inputencodingname}
\fi

```

Provide a way to query the environment variables LC\_ALL or LANG to determine the region and language. The result is stored in \TrackLangEnv if it can be obtained. If it can't be obtained, \TrackLangEnv is set to empty. Also define \TrackLangQueryOtherEnv{<name>} to query LC\_ALL, <name>, LANG. For example

```

%\TrackLangQueryOtherEnv{LC\_MONETARY}
%

```

Note that there's not much that can be done from within T<sub>E</sub>X for the C or POSIX locale or a locale starting with a slash, so provide a check for them.

\@tracklang@checklocale

```

\def\@tracklang@checklocale{%
  \ifx\TrackLangEnv\empty
  \else
    \ifx\TrackLangEnv\@tracklang@locale@posix
      \def\TrackLangEnv{}%
    \fi
  \fi
}

```

```

\else
\ifx\TrackLangEnv\@tracklang@locale@c
\def\TrackLangEnv{}%
\else
\expandafter\@tracklang@checklocale
\TrackLangEnv\empty\relax
\fi
\fi
\fi
}

```

\@tracklang@checklocale Check for leading slash.

```

\def\@tracklang@checklocale#1#2\relax{%
\ifx#1/\relax
\def\TrackLangEnv{}%
\fi
}

```

\@tracklang@locale@posix

```

\def\@tracklang@locale@posix{POSIX}

```

\@tracklang@locale@c

```

\def\@tracklang@locale@c{C}

```

```

\ifx\directlua\undefined

```

We can't use Lua, so we'll have to use the shell escape if it's enabled. First determine if the shell escape is available.

\@tracklang@tryshellescape No shell escape.

```

\def\@tracklang@tryshellescape#1{%
\def\TrackLangQueryEnv{%
\@tracklang@warn{\string\TrackLangQueryEnv\space
non-operational as shell escape has been disabled}%
\def\TrackLangEnv{}%
}%
\def\TrackLangQueryOtherEnv##1{%
\@tracklang@warn{\string\TrackLangQueryOtherEnv{##1}\space
non-operational as shell escape has been disabled}%
\def\TrackLangEnv{}%
}%
}%

```

```

\ifx\pdfshellescape\undefined

```

```

\ifx\shellescape\undefined

```

Can't determine if the shell escape has been enabled.

```

\def\@tracklang@tryshellescape#1{%
\def\TrackLangQueryEnv{%
\@tracklang@warn{\string\TrackLangQueryEnv\space

```

```

        non-operational as can't determine if the
        shell escape has been enabled. (Consider using
        eTeX or pdfTeX.)}%
        \def\TrackLangEnv{}}%
    }%
    \def\TrackLangQueryOtherEnv##1{%
        \@tracklang@warn{\string\TrackLangQueryOtherEnv{##1}\space
        non-operational as can't determine if the
        shell escape has been enabled. (Consider using
        eTeX or pdfTeX.)}%
        \def\TrackLangEnv{}}%
    }%
}
\else
\shellescape is defined. Check no one's been messing around with it and set
it to \relax.
    \ifx\shellescape\relax
    \else
        \ifnum\shellescape=0\relax
        \else
            \def\@tracklang@tryshellescape#1{#1}%
        \fi
    \fi
\fi
\else
\pdfshellescape is defined. Check no one's been messing around with it and
set it to \relax. (Default no-op already set.)
    \ifx\pdfshellescape\relax
\pdfshellescape has been set to \relax. Is it possible that \shellescape is
available?
    \ifx\shellescape\undefined
    \else
        \ifx\shellescape\relax
        \else
\shellescape is available.
        \ifnum\shellescape=0\relax
        \else
            \def\@tracklang@tryshellescape#1{#1}%
        \fi
    \fi
\fi
\else
\ifnum\pdfshellescape=0\relax
\else
    \def\@tracklang@tryshellescape#1{#1}%
\fi
\fi

```

```
\fi
```

Try the shell escape:

```
\@tracklang@tryshellescape  
{%
```

```
\TrackLangQueryEnv
```

```
\def\TrackLangQueryEnv{%  
  \begingroup\endlinechar=-1\relax  
  \everyeof{\noexpand}%  
  \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%  
    \@tracklang@input|"kpsewhich --var-value LC_ALL" }}\@tracklang@x  
  \@tracklang@checklocale  
  \ifx\TrackLangEnv\empty  
    \begingroup\endlinechar=-1\relax  
    \everyeof{\noexpand}%  
    \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%  
      \@tracklang@input|"kpsewhich --var-value LANG" }}\@tracklang@x
```

Not sure if a path is likely to occur with kpsewhich but check for it just in case.

```
\@tracklang@checklocale  
\ifx\TrackLangEnv\empty
```

Try texosquery if available.

```
\ifx\TeXOSQueryLocale\undefined  
  \@tracklang@warn{Locale environment variables  
    unavailable (tried LC\string_ALL and LANG)}%  
\else  
  \@tracklang@info{Using texosquery to find locale}%  
  \TeXOSQueryLocale\TrackLangEnv  
  \ifx\TrackLangEnv\empty  
    \@tracklang@warn{Locale can't be found  
      (tried querying LC\string_ALL and LANG variables and  
      tried using texosquery)}%  
  \fi  
\fi  
\fi  
\fi  
}%
```

```
\TrackLangQueryOtherEnv
```

```
\def\TrackLangQueryOtherEnv#1{%  
  \begingroup\endlinechar=-1\relax  
  \everyeof{\noexpand}%  
  \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%  
    \@tracklang@input|"kpsewhich --var-value LC_ALL" }}\@tracklang@x  
  \@tracklang@checklocale  
  \ifx\TrackLangEnv\empty  
    \begingroup\endlinechar=-1\relax  
    \everyeof{\noexpand}%
```

```

\edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
  \@tracklang@input|"kpsewhich --var-value #1" }}\@tracklang@x
\@tracklang@checklocale
\ifx\TrackLangEnv\empty
  \begingroup\endlinechar=-1\relax
  \everyeof{\noexpand}%
  \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
    \@tracklang@input|"kpsewhich --var-value LANG" }}\@tracklang@x
  \@tracklang@checklocale
\ifx\TrackLangEnv\empty

```

Try texosquery if available.

```

\ifx\TeXOSQueryLocale\undefined
\@tracklang@warn{Locale environment variables unavailable
  (tried LC\string_ALL, #1 and LANG)}%
\else
  \@tracklang@info{Using texosquery to find locale}%
  \TeXOSQueryLocale\TrackLangEnv
  \ifx\TrackLangEnv\empty
    \@tracklang@warn{Locale can't be found
      (tried querying LC\string_ALL, #1 and LANG variables and
        tried using texosquery)}%
  \fi
\fi
\fi
\fi
\fi
\fi
}%
\else

```

\directlua is defined, so we can query it through Lua:

\TrackLangQueryEnv

```

\def\TrackLangQueryEnv{%
\edef\TrackLangEnv{\directlua{
  l = os.getenv("LC_ALL")
  if l == nil or l == "" or l == "C" or l == "POSIX"
    or string.find(l, "~/") then
    l = os.getenv("LANG")
    if l == nil or l == "" or l == "C" or l == "POSIX"
      or string.find(l, "~/") then
      l=os.setlocale(nil)
      if l == nil or l == "C" or l == "POSIX"
        or string.find(l, "~/") then
        l = ""
      end
    end
  end
end
end
tex.print(l)}}%

```





```

        (tried querying LC\string_ALL, #1 and LANG variables and
        os.setlocale(nil) and tried using texosquery)}%
    \fi
  \fi
\fi
}
\fi

```

Allowed formats for the localisation environment variables are

```

<iso-lang>[_<iso-territory>][.<encoding>][@<modifier>]

```

(where the square brackets above indicate an optional component not that there are literal square brackets.) This is a bit fiddly, so it needs to be broken up into manageable chunks.

`\TrackLangParseFromEnv` Parse `\TrackLangEnv`, if it has been set, and set `\TrackLangEnvLang`, `\TrackLangEnvTerritory` and `\TrackLangEnvCodeSet`. If the information is unavailable, the relevant commands will be set to empty. Use `\TrackLangFromEnv` to query, parse and set.

```

\def\TrackLangParseFromEnv{%
  \ifx\TrackLangEnv\undefined
    \@tracklang@warn{\string\TrackLangParseFromEnv\space
      non-operational as \string\TrackLangEnv\space hasn't been
      defined}%
    \def\TrackLangEnvLang{}%
    \def\TrackLangEnvTerritory{}%
    \def\TrackLangEnvCodeSet{}%
    \def\TrackLangEnvModifier{}%
  \else
    \ifx\TrackLangEnv\empty
      \@tracklang@warn{\string\TrackLangParseFromEnv\space
        non-operational as \string\TrackLangEnv\space is empty}%
      \def\TrackLangEnvLang{}%
      \def\TrackLangEnvTerritory{}%
      \def\TrackLangEnvCodeSet{}%
      \def\TrackLangEnvModifier{}%
    \else
      \@tracklang@parse@locale{\TrackLangEnv}%
      \let\TrackLangEnvLang\@TrackLangEnvLang
      \let\TrackLangEnvTerritory\@TrackLangEnvTerritory
      \let\TrackLangEnvCodeSet\@TrackLangEnvCodeSet
      \let\TrackLangEnvModifier\@TrackLangEnvModifier
    \fi
  \fi
}

```

`\@tracklang@parse@locale` Parse localisation format.

```

\def\@tracklang@parse@locale#1{%

```

Initialise.

```
\def\@TrackLangEnvLang{}%
\def\@TrackLangEnvSubLang{}%
\def\@TrackLangEnvFirstSubLang{}%
\def\@TrackLangEnvTerritory{}%
\def\@TrackLangEnvCodeSet{}%
\def\@TrackLangEnvVariant{}%
\def\@TrackLangEnvModifier{}%
\def\@TrackLangEnvScript{}%
\def\@TrackLangEnvAdditional{}%
```

Just in case argument is empty or \relax.

```
\expandafter\ifx\expandafter\relax#1\relax
\else
```

Parse codeset and modifier first.

```
\expandafter\@tracklang@parseenv
#1..\relax\@tracklang@end@parseenv\@tracklang@result
```

Parse language and territory.

```
\ifx\@tracklang@result\empty
\else
\expandafter\@tracklang@split@underscoreorhyphen\expandafter
{\@tracklang@result}%
\let\@TrackLangEnvLang\@tracklang@split@pre
\let\@TrackLangEnvTerritory\@tracklang@split@post
\fi
\fi
}
```

`\@tracklang@split@underscoreorhyphen` Split on either an underscore or a hyphen and store the results in `\@tracklang@split@pre` and `\@tracklang@split@post`

```
\def\@tracklang@split@underscoreorhyphen#1{%
```

First try to split on an underscore.

```
\@tracklang@split@underscore{#1}%
```

If the post part was empty, try to split on hyphen instead.

```
\ifx\@tracklang@split@post\empty
\@tracklang@split@hyphen{#1}%
```

If the post part was empty, maybe the underscore has had its category code changed to 12.

```
\ifx\@tracklang@split@post\empty
\@tracklang@split@otherunderscore{#1}%
\fi
\fi
}
```

`\@tracklang@split@underscore` Split on an underscore and store the results in `\@tracklang@split@pre` and `\@tracklang@split@post`. First make sure that the underscore has its normal subscript category code.

```

{
\catcode'\_8\relax
\gdef\@tracklang@split@underscore#1{%
\@@tracklang@split@underscore#1__\relax\@tracklang@end@split@underscore
}
\gdef\@@tracklang@split@underscore#1_#2_#3\@tracklang@end@split@underscore{%
\def\@tracklang@split@pre{#1}%
\ifx\relax#3\relax
\def\@tracklang@split@post{#2}%
\else
\@tracklang@split@underscore@remainder#2_#3%
\fi
}
\gdef\@tracklang@split@underscore@remainder#1__\relax{%
\def\@tracklang@split@post{#1}%
}
}

```

\@tracklang@split@otherunderscore As above but where underscore has catcode 12.

```

{
\catcode'\_12\relax
\gdef\@tracklang@split@otherunderscore#1{%
\@@tracklang@split@otherunderscore#1__\relax\@tracklang@end@split@underscore
}
\gdef\@@tracklang@split@otherunderscore#1_#2_#3\@tracklang@end@split@underscore{%
\def\@tracklang@split@pre{#1}%
\ifx\relax#3\relax
\def\@tracklang@split@post{#2}%
\else
\@tracklang@split@otherunderscore@remainder#2_#3%
\fi
}
\gdef\@tracklang@split@otherunderscore@remainder#1__\relax{%
\def\@tracklang@split@post{#1}%
}
}

```

\@tracklang@split@hyphen Split on a hyphen and store the results in \@tracklang@split@pre and \@tracklang@split@post

```

{
\catcode'\-12\relax
\gdef\@tracklang@split@hyphen#1{%
\@@tracklang@split@hyphen#1--\relax\@tracklang@end@split@hyphen
}
\gdef\@@tracklang@split@hyphen#1-#2-#3\@tracklang@end@split@hyphen{%
\def\@tracklang@split@pre{#1}%
\ifx\relax#3\relax
\def\@tracklang@split@post{#2}%
\else
\@tracklang@split@hyphen@remainder#2-#3%

```

```

    \fi
  }
  \gdef\@tracklang@split@hyphen@remainder#1--\relax{%
    \def\@tracklang@split@post{#1}%
  }
}

```

`\@tracklang@parseenv` Parse for the codeset. The first argument will be the language and (optionally) the territory. So the final argument is the control sequence to use to store the first argument, which can then be split.

```

\gdef\@tracklang@parseenv#1.#2.#3\@tracklang@end@parseenv#4{%
  \def\@TrackLangEnvCodeSet{#2}%
  \def#4{#1}%
  \ifx\@TrackLangEnvCodeSet\empty
    \tracklangparsemod#4%
  \else
    \tracklangparsemod\@TrackLangEnvCodeSet
  \fi
}

```

`\tracklangparsemod` Extract the modifier from the code set. The @ is rather awkward as we need to change its category code as it's likely to be set to 12 within `\TrackLangEnv`. So change the category code of @ to 12, but this means we can't use it in the command name, so although these are private internal commands they don't look like internal commands.)

```

{\catcode'\@=12\relax
  \gdef\tracklangparsemod#1{
    \expandafter\tracklangparseenvatmod#1@\relax\tracklangendparseenvatmod
    \let#1\tracklangtmp
  }%
  \gdef\tracklangparseenvatmod#1@#2@#3\tracklangendparseenvatmod{%
    \def\tracklangtmp{#1}%

```

Need to use `\csname` here as can't use internal commands.

```

  \expandafter\def\csname @TrackLangEnvModifier\endcsname{#2}%

```

Sanitize in case it contains any special characters.

```

  \csname @tracklang@sanitize\expandafter\endcsname
  \csname @TrackLangEnvModifier\endcsname
}
}

```

## 4.1 Internal Lists

`\@tracklang@languages` Provide a list to keep track of all the languages.

```

\def\@tracklang@languages{}

```

`\@tracklang@dialects` Provide a list to keep track of all the dialects. Here the “dialect” isn't necessarily an actual dialect but may be a root language or a synonym. It will usually correspond to the language name as specified by the user in the package option.

```
\def\@tracklang@dialects{}
```

\@tracklang@regions Provide a list to keep track of all the regions.

```
\def\@tracklang@regions{}
```

```
\@tracklang@ifinlist{<item>}{<list>}{<true part>}{<false part>}
```

\@tracklang@ifinlist

Checks if  $\langle item \rangle$  is in  $\langle list \rangle$ . (Performs a one-level expansion on  $\langle list \rangle$  but no expansion on  $\langle item \rangle$ .)

```
\def\@tracklang@ifinlist#1#2#3#4{%
  \def\@tracklang@doifinlist##1,#1,##2\end@tracklang@doifinlist{%
    \def\@before{##1}%
    \def\@after{##2}%
  }%
  \expandafter\@tracklang@doifinlist\expandafter,#2,#1,\@nil
  \end@tracklang@doifinlist
  \ifx\@after\@tracklang@mnil
not found
    #4%
  \else
found
    #3%
  \fi
}
```

```
\@tracklang@add{<item>}{<list cs>}
```

\@tracklang@add

Adds an item to the list given by  $\langle list cs \rangle$ . Does nothing if  $\langle item \rangle$  is empty or is already in the list. The  $\langle item \rangle$  is fully expanded before being added.

```
\def\@tracklang@add#1#2{%
```

First find out if the item is empty.

```
\edef\@tracklang@element{#1}%
\ifx\@tracklang@element\empty
```

Item is empty, so do nothing.

```
\else
  \expandafter\@tracklang@ifinlist\expandafter{\@tracklang@element}#2%
  {%
```

Already in list, so do nothing.

```
}%
{%
```

Not in list, so add.

```
\ifx\empty#2\relax
  \let#2\@tracklang@element
\else
  \edef#2{#2,\@tracklang@element}%
\fi
}%
\fi
}
```

```
\AddTrackedDialect{<dialect name>}{<language name>}
```

\AddTrackedDialect

Add a dialect. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.)

```
\def\AddTrackedDialect#1#2{%
  \@tracklang@add{#1}{\@tracklang@dialects}%
  \@tracklang@add{#2}{\@tracklang@languages}%
}
```

Add region to list if available.

```
\@tracklang@enamedef{\@tracklang@fromdialect@#1}{#2}%
\@tracklang@ifundef{\@tracklang@todialect@#2}%
{\@tracklang@enamedef{\@tracklang@todialect@#2}{#1}}%
{%
  \def\@tracklang@lang{#1}%
  \expandafter\@tracklang@add\expandafter\@tracklang@lang
  \csname \@tracklang@todialect@#2\endcsname
}%
```

Provide a convenient way of referencing the last dialect to be tracked.

```
\edef\TrackLangLastTrackedDialect{#1}%
}
```

```
\AddTrackedLanguage{<language name>}
```

\AddTrackedLanguage

Add a dialect.

```
\def\AddTrackedLanguage#1{%
  \AddTrackedDialect{#1}{#1}%
}
```

```
\AddTrackedRegion{<country code>}{<dialect>}
```

\AddTrackedRegion

Add to tracked region list.

```
\def\AddTrackedRegion#1#2{%
  \AddTrackedIsoLanguage{3166-1}{#1}{#2}%
  \@tracklang@add{#1}{\@tracklang@regions}%
}
```

## 4.2 Known Languages

`\@tracklang@known@langs` List of known (root) languages (that may or may not be tracked).

```
\def\@tracklang@known@langs{}
```

```
\TrackLangNewLanguage{<language name>}{<639-1
code>}{<639-2 (T)>}{<639-2 (B)>}{<639-3>}{<3166-1>}{<default
script>}
```

`\TrackLangNewLanguage`

Identifies a new language that may be tracked. The code arguments may be empty if not available. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.) Most root languages don't have an associated country code as they're spoken in multiple regions. The *<default script>* is the default script identified with the ISO 15924 alpha script code. To reduce overheads, only define 639-3 if there's no 639-1 or 639-2 code.

```
\def\TrackLangNewLanguage#1#2#3#4#5#6#7{%
\@tracklang@add{#1}{\@tracklang@known@langs}%
\edef\@tracklang@tmp{#2}%
\ifx\@tracklang@tmp\empty
\else
\@tracklang@enamedef{\@tracklang@knownisolang@#2}{#1}%
\@tracklang@enamedef{\@tracklang@knowniso@639@1@#1}{#2}%
\fi
\edef\@tracklang@tmp{#3}%
\ifx\@tracklang@tmp\empty
\else
\@tracklang@enamedef{\@tracklang@knownisolang@#3}{#1}%
\@tracklang@enamedef{\@tracklang@knowniso@639@2@#1}{#3}%
\fi
\edef\@tracklang@tmp{#4}%
\ifx\@tracklang@tmp\empty
\else
\@tracklang@enamedef{\@tracklang@knowniso@639@2B@#1}{#4}%
\fi
\edef\@tracklang@tmp{#5}%
\ifx\@tracklang@tmp\empty
\else
\@tracklang@enamedef{\@tracklang@knownisolang@#5}{#1}%
\@tracklang@enamedef{\@tracklang@knowniso@639@3@#1}{#5}%
\fi
\edef\@tracklang@tmp{#6}%
\ifx\@tracklang@tmp\empty
\else
\@tracklang@enamedef{\@tracklang@knowniso@3166@#1}{#6}%
\fi
\edef\@tracklang@tmp{#7}%
\ifx\@tracklang@tmp\empty
\else
```



```

\@tracklang@enamedef{@tracklang@knowniso@script@#1}{#7}%
\fi
}

```

```
\TrackLangIfKnownLang{<language>}{<true>}{<false>}
```

\TrackLangIfKnownLang

Tests if *<language>* is known (but not necessarily tracked).

```

\def\TrackLangIfKnownLang#1#2#3{%
\expandafter\@tracklang@ifinlist\expandafter{#1}{\@tracklang@known@langs}%
{#2}%
{#3}%
}

```

```
\TrackLangIfKnownIsoTwoLetterLang{<language>}{<true>}
{<false>}
```

\TrackLangIfKnownIsoTwoLetterLang

Checks if the given language has an ISO 639-1 language code (but is not necessarily tracked).

```

\def\TrackLangIfKnownIsoTwoLetterLang#1#2#3{%
\@tracklang@ifundef{@tracklang@knowniso@639@1@#1}%
{#3}%
{#2}%
}

```

```
\TrackLangGetKnownIsoTwoLetterLang{<language>}
```

\TrackLangGetKnownIsoTwoLetterLang

Gets the ISO 639-1 language code for the given language.

```

\def\TrackLangGetKnownIsoTwoLetterLang#1{%
\@tracklang@nameuse{@tracklang@knowniso@639@1@#1}%
}

```

```
\TrackLangIfKnownIsoThreeLetterLang{<language>}{<true>}
{<false>}
```

\TrackLangIfKnownIsoThreeLetterLang

Checks if the given language has an ISO 639-2 language code (but is not necessarily tracked).

```

\def\TrackLangIfKnownIsoThreeLetterLang#1#2#3{%
\@tracklang@ifundef{@tracklang@knowniso@639@2@#1}%
{#3}%
{#2}%
}

```

\TrackLangGetKnownIsoThreeLetterLang

`\TrackLangGetKnownIsoThreeLetterLang{<language>}`

Gets the ISO 639-2 language code.

```
\def\TrackLangGetKnownIsoThreeLetterLang#1{%
  \@tracklang@nameuse{@tracklang@knowniso@639@2@#1}%
}
```

\TrackLangIfKnownIsoThreeLetterLangB

`\TrackLangIfKnownIsoThreeLetterLangB{<language>}{<true>}{<false>}`

Checks if the given language has an ISO 639-2 (B) language code (but is not necessarily tracked).

```
\def\TrackLangIfKnownIsoThreeLetterLangB#1#2#3{%
  \@tracklang@ifundef{@tracklang@knowniso@639@2B@#1}%
  {#3}%
  {#2}%
}
```

\TrackLangGetKnownIsoThreeLetterLangB

`\TrackLangGetKnownIsoThreeLetterLangB{<language>}`

Gets the ISO 639-2 (B) language code.

```
\def\TrackLangGetKnownIsoThreeLetterLangB#1{%
  \@tracklang@nameuse{@tracklang@knowniso@639@2B@#1}%
}
```

\TrackLangIfKnownLangFromIso

`\TrackLangIfKnownLangFromIso{<ISO code>}{<true>}{<false>}`

Checks if the given ISO language code (639-1 or 639-2 or 639-3) is recognised (but not necessarily tracked).

```
\def\TrackLangIfKnownLangFromIso#1#2#3{%
  \@tracklang@ifundef{@tracklang@knownisolang@#1}%
  {#3}%
  {#2}%
}
```

\TrackLangGetKnownLangFromIso

`\TrackLangGetKnownLangFromIso{<ISO code>}`

Gets the root language label from the given ISO code (639-1 or 639-2).

```
\def\TrackLangGetKnownLangFromIso#1{%
  \@tracklang@nameuse{@tracklang@knownisolang@#1}%
}
```

`\TrackLangIfHasKnownCountry`

```
\TrackLangIfHasKnownCountry{<language>}{<true>}{<false>}
```

Checks if the given language has an ISO 3166-1 country code (but is not necessarily tracked).

```
\def\TrackLangIfHasKnownCountry#1#2#3{%
  \@tracklang@ifundef{@tracklang@knowniso@3166@#1}%
  {#3}%
  {#2}%
}
```

`\TrackLangGetKnownCountry`

```
\TrackLangGetKnownCountry{<language>}
```

Fetches the ISO 3166-1 country code for the given language.

```
\def\TrackLangGetKnownCountry#1{%
  \@tracklang@nameuse{@tracklang@knowniso@3166@#1}%
}
```

`\TrackLangGetDefaultScript`

```
\TrackLangGetDefaultScript{<language>}
```

Gets the default script for the given root language label.

```
\def\TrackLangGetDefaultScript#1{%
  \@tracklang@nameuse{@tracklang@knowniso@script@#1}%
}
```

`\TrackLangIfHasDefaultScript`

```
\TrackLangIfHasDefaultScript{<language>}{<true>}{<false>}
```

If there's a default script for *<language>*, do *<true>* otherwise do *<false>*.

```
\def\TrackLangIfHasDefaultScript#1#2#3{%
  \@tracklang@ifundef{@tracklang@knowniso@script@#1}{#3}{#2}%
}
```

### 4.3 Mappings

`\AddTrackedIsoLanguage`

```
\AddTrackedIsoLanguage{<code type>}{<code>}{<language>}
```

Adds a mapping between the given ISO code and language name. There may be multiple mappings from an ISO code to a language name, but only one mapping from a language name to an ISO code. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.)

```
\def\AddTrackedIsoLanguage#1#2#3{%
  \@tracklang@namedef{@tracklang@#1@isofromlang@#3}{#2}%
  \@tracklang@ifundef{@tracklang@#1@isotolang@#2}%
}
```

```

{\@tracklang@enamedef{@tracklang@#1@isotolang@#2}{#3}}%
{%
  \def\@tracklang@lang{#3}%
  \expandafter\@tracklang@add\expandafter\@tracklang@lang
  \csname \@tracklang@#1@isotolang@#2\endcsname
}%
}

```

```
\TrackedLanguageFromIsoCode{<code type>}{<code>}
```

\TrackedLanguageFromIsoCode

Fetches the language label (or labels) associated with the given code.

```

\def\TrackedLanguageFromIsoCode#1#2{%
  \@tracklang@nameuse{@tracklang@#1@isotolang@#2}%
}

```

```
\TrackedIsoCodeFromLanguage{<code type>}{<language>}
```

\TrackedIsoCodeFromLanguage

Fetches the code associated with the given language or dialect.

```

\def\TrackedIsoCodeFromLanguage#1#2{%
  \@tracklang@nameuse{@tracklang@#1@isofromlang@#2}%
}

```

```
\TrackedLanguageFromDialect{<dialect>}
```

\TrackedLanguageFromDialect

Fetches the language name from the given dialect.

```

\def\TrackedLanguageFromDialect#1{%
  \@tracklang@nameuse{@tracklang@fromdialect@#1}%
}

```

```
\TrackedDialectsFromLanguage{<root language label>}
```

\TrackedDialectsFromLanguage

Fetches the tracked dialects whose language is given by *<root language label>*.

```

\def\TrackedDialectsFromLanguage#1{%
  \@tracklang@nameuse{@tracklang@todialect@#1}%
}

```

\TwoLetterIsoCountryCode

```
\def\TwoLetterIsoCountryCode{3166-1}
```

\TwoLetterIsoLanguageCode

```
\def\TwoLetterIsoLanguageCode{639-1}
```

\ThreeLetterIsoLanguageCode

```
\def\ThreeLetterIsoLanguageCode{639-2}
```

ThreeLetterExtIsoLanguageCode

```
\def\ThreeLetterExtIsoLanguageCode{639-3}
```

```
\SetTrackedDialectModifier{<dialect>}{<value>}
```

\SetTrackedDialectModifier

Set the modifier for *<dialect>*. (For example, old or new.) Arguments are expanded.

```
\def\SetTrackedDialectModifier#1#2{%
  \@tracklang@namedef{@tracklang@modifier@#1}{#2}%
}
```

```
\GetTrackedDialectModifier{<dialect>}
```

\GetTrackedDialectModifier

Get the modifier for *<dialect>*.

```
\def\GetTrackedDialectModifier#1{%
  \@tracklang@nameuse{@tracklang@modifier@#1}%
}
```

```
\IfHasTrackedDialectModifier{<dialect>}{<true>}{<false>}
```

\IfHasTrackedDialectModifier

If there's a modifier for *<dialect>*, do *<true>* otherwise do *<false>*.

```
\def\IfHasTrackedDialectModifier#1#2#3{%
  \@tracklang@ifundef{@tracklang@modifier@#1}{#3}{#2}%
}
```

```
\SetTrackedDialectScript{<dialect>}{<value>}
```

\SetTrackedDialectScript

Set the script for *<dialect>*. (For example, Latn or Cyril.) Arguments are expanded.

```
\def\SetTrackedDialectScript#1#2{%
  \@tracklang@namedef{@tracklang@script@#1}{#2}%
}
```

```
\GetTrackedDialectScript{<dialect>}
```

\GetTrackedDialectScript

Get the script for *<dialect>*.

```
\def\GetTrackedDialectScript#1{%
  \@tracklang@nameuse{@tracklang@script@#1}%
}
```

```
\IfHasTrackedDialectScript{<dialect>}{<true>}{<false>}
```

\IfHasTrackedDialectScript

If there's a script for <dialect>, do <true> otherwise do <false>.

```
\def\IfHasTrackedDialectScript#1#2#3{%
  \@tracklang@ifundef{@tracklang@script@#1}{#3}{#2}%
}
```

```
\IfTrackedDialectIsScriptCs{<dialect>}{<cs>}{<true>}
{<false>}
```

\IfTrackedDialectIsScriptCs

If the given tracked dialect has an associated script and that script code matches the replacement text for the control sequence <cs> then do <true> otherwise to <false>. If the tracked dialect doesn't have an associated script then the default script for the root language is tested. The use of a control sequence allows \ifx for the test, which means that this command can expand. The supplementary package tracklang-script provides control sequences for known ISO 15924 codes.

```
\def\IfTrackedDialectIsScriptCs#1#2#3#4{%
  \IfHasTrackedDialectScript{#1}%
  {%
    \expandafter\ifx\expandafter#2\csname @tracklang@script@#1\endcsname
    #3%
    \else
    #4%
    \fi
  }%
  {%
    \TrackLangIfHasDefaultScript{\TrackedLanguageFromDialect{#1}}%
    {%
      \expandafter\ifx\expandafter
      #2\csname @tracklang@knowniso@script@\TrackedLanguageFromDialect{#1}\endcsname
      #3%
      \else
      #4%
      \fi
    }%
    {#4}%
  }%
}
```

```
\SetTrackedDialectVariant{<dialect>}{<value>}
```

\SetTrackedDialectVariant

Set the modifier for <dialect>. (For example, old or new.) Arguments are expanded.

```
\def\SetTrackedDialectVariant#1#2{%
  \@tracklang@enamedef{@tracklang@variant@#1}{#2}%
}
```

```
}
```

```
\GetTrackedDialectVariant{<dialect>}
```

```
\GetTrackedDialectVariant
```

Get the modifier for *<dialect>*.

```
\def\GetTrackedDialectVariant#1{%  
  \@tracklang@nameuse{@tracklang@variant@#1}%  
}
```

```
\IfHasTrackedDialectVariant{<dialect>}{<true>}{<false>}
```

```
\IfHasTrackedDialectVariant
```

If there's a modifier for *<dialect>*, do *<true>* otherwise do *<false>*.

```
\def\IfHasTrackedDialectVariant#1#2#3{%  
  \@tracklang@ifundef{@tracklang@variant@#1}{#3}{#2}%  
}
```

```
\SetTrackedDialectSubLang{<dialect>}{<value>}
```

```
\SetTrackedDialectSubLang
```

Set the sublang for *<dialect>*. Arguments are expanded.

```
\def\SetTrackedDialectSubLang#1#2{%  
  \@tracklang@namedef{@tracklang@sublang@#1}{#2}%  
}
```

```
\GetTrackedDialectSubLang{<dialect>}
```

```
\GetTrackedDialectSubLang
```

Get the sublang for *<dialect>*.

```
\def\GetTrackedDialectSubLang#1{%  
  \@tracklang@nameuse{@tracklang@sublang@#1}%  
}
```

```
\IfHasTrackedDialectSubLang{<dialect>}{<true>}{<false>}
```

```
\IfHasTrackedDialectSubLang
```

If there's a sublang for *<dialect>*, do *<true>* otherwise do *<false>*.

```
\def\IfHasTrackedDialectSubLang#1#2#3{%  
  \@tracklang@ifundef{@tracklang@sublang@#1}{#3}{#2}%  
}
```

```
\SetTrackedDialectAdditional{<dialect>}{<value>}
```

```
\SetTrackedDialectAdditional
```

Set the extra for *<dialect>*. Arguments are expanded.

```
\def\SetTrackedDialectAdditional#1#2{%  
  \@tracklang@enamedef{@tracklang@extra@#1}{#2}%  
}
```

`\GetTrackedDialectAdditional{<dialect>}`

`\GetTrackedDialectAdditional`

Get the extra for *<dialect>*.

```
\def\GetTrackedDialectAdditional#1{%  
  \@tracklang@nameuse{@tracklang@extra@#1}%  
}
```

`\IfHasTrackedDialectAdditional{<dialect>}{<true>}{<false>}`

`\HasTrackedDialectAdditional`

If there's extra info for *<dialect>*, do *<true>* otherwise do *<false>*.

```
\def\IfHasTrackedDialectAdditional#1#2#3{%  
  \@tracklang@ifundef{@tracklang@extra@#1}{#3}{#2}%  
}
```

`\GetTrackedLanguageTag{<dialect>}`

`\GetTrackedLanguageTag`

Get the language tag for *<dialect>*.

```
\def\GetTrackedLanguageTag#1{%  
  \IfTrackedLanguageHasIsoCode{639-1}{\TrackedLanguageFromDialect{#1}}%  
  {\TrackedIsoCodeFromLanguage{639-1}{\TrackedLanguageFromDialect{#1}}}%  
  {%  
    \IfTrackedLanguageHasIsoCode{639-2}{\TrackedLanguageFromDialect{#1}}%  
    {\TrackedIsoCodeFromLanguage{639-2}{\TrackedLanguageFromDialect{#1}}}%  
    {%  
      \IfTrackedLanguageHasIsoCode{639-3}{\TrackedLanguageFromDialect{#1}}%  
      {\TrackedIsoCodeFromLanguage{639-3}{\TrackedLanguageFromDialect{#1}}}%  
      {und}% undefined  
    }%  
  }%  
  \@tracklang@ifundef{@tracklang@sublang@#1}%  
  {}%  
  {-\csname @tracklang@sublang@#1\endcsname}%  
  \@tracklang@ifundef{@tracklang@script@#1}%  
  {}%  
  {-\csname @tracklang@script@#1\endcsname}%  
  \IfTrackedLanguageHasIsoCode{3166-1}{#1}%  
  {-\TrackedIsoCodeFromLanguage{3166-1}{#1}}%  
  {}%  
  \@tracklang@ifundef{@tracklang@variant@#1}%  
}
```



```

{}%
{-\csname @tracklang@variant@#1\endcsname}%
\@tracklang@ifundef{\@tracklang@extra@#1}%
{}%
{-\csname @tracklang@extra@#1\endcsname}%
}

```

\SetCurrentTrackedDialect{*dialect*}

\SetCurrentTrackedDialect

Provided for use by language hooks to establish the current tracked dialect. This command doesn't change \language or hyphenation patterns etc. It just provides convenient commands that can be accessed. The argument may be a tracklang dialect label or the language hook label from which a tracklang dialect label can be obtained or the root language label.

```

\def\SetCurrentTrackedDialect#1{%
  \edef\CurrentTrackedDialect{#1}%
  \@tracklang@verbose{Setting current tracked dialect '\CurrentTrackedDialect'}%
  \IfTrackedDialect{\CurrentTrackedDialect}%
  {}%
  {%
    \@tracklang@verbose{Not a recognised tracklang label}%

```

Has a mapping from this dialect to a tracklang dialect been supplied?

```

\IfHookHasMappingFromTrackedDialect{\CurrentTrackedDialect}%
{%
  \IfTrackedDialect{\GetTrackedDialectFromMapping\CurrentTrackedDialect}%
  {%
    \edef\CurrentTrackedDialect{\GetTrackedDialectFromMapping
      {\CurrentTrackedDialect}}%
    \@tracklang@verbose{Mapping found to tracklang label '\CurrentTrackedDialect'}%
  }%
  {}%

```

Has the root language name been supplied?

```

\IfTrackedLanguage{#1}%
{%
  \@tracklang@verbose{Supplied label is a root language.
    Finding last tracked dialect for language '#1'}%

```

Get the last dialect to be tracked with this language.

```

\edef\@tracklang@dialects{\TrackedDialectsFromLanguage{#1}}%
\@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%
  \let\CurrentTrackedDialect\@tracklang@dialect
}%
}%
{%
  \@tracklang@verbose{No tracklang dialect found for label '#1'}%
}%
}%

```

```

}%
{%
  \@tracklang@verbose{No mapping found}%
Has the root language name been supplied?
  \IfTrackedLanguage{#1}%
  {%
    \@tracklang@verbose{Supplied label is a root language.
      Finding last tracked dialect for language ‘#1’}%
Get the last dialect to be tracked with this language.
    \edef\@tracklang@dialects{\TrackedDialectsFromLanguage{#1}}%
    \@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%
      \let\CurrentTrackedDialect\@tracklang@dialect
    }%
  }%
  {%
    \@tracklang@verbose{No tracklang dialect found for label ‘#1’}%
  }%
}%
\IfTrackedDialect{\CurrentTrackedDialect}%
{%
  \edef\CurrentTrackedLanguage{%
    \TrackedLanguageFromDialect{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedDialectModifier{%
    \GetTrackedDialectModifier{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedDialectVariant{%
    \GetTrackedDialectVariant{\CurrentTrackedDialect}}%
Get the default script if not set.
  \IfHasTrackedDialectScript{\CurrentTrackedDialect}%
  {%
    \edef\CurrentTrackedDialectScript{%
      \GetTrackedDialectScript{\CurrentTrackedDialect}}%
  }%
  {%
    \edef\CurrentTrackedDialectScript{%
      \TrackLangGetDefaultScript\CurrentTrackedLanguage}%
  }%
  \edef\CurrentTrackedDialectSubLang{%
    \GetTrackedDialectSubLang{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedDialectAdditional{%
    \GetTrackedDialectAdditional{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedLanguageTag{%
    \GetTrackedLanguageTag{\CurrentTrackedDialect}}%
Region code.
  \IfTrackedLanguageHasIsoCode{3166-1}{\CurrentTrackedDialect}%
  {%
    \edef\CurrentTrackedRegion{%

```

```

    \TrackedIsoCodeFromLanguage{3166-1}{\CurrentTrackedDialect}}%
}%
{\def\CurrentTrackedRegion{}}%

```

Language code.

```

\IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
{%
  \edef\CurrentTrackedIsoCode{%
    \TrackedIsoCodeFromLanguage{639-1}{\CurrentTrackedLanguage}}%
}%
{%
  \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
  {%
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage{639-2}{\CurrentTrackedLanguage}}%
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
    {%
      \edef\CurrentTrackedIsoCode{%
        \TrackedIsoCodeFromLanguage{639-3}{\CurrentTrackedLanguage}}%
    }%
    {%
      \def\CurrentTrackedIsoCode{}%
    }%
  }%
}%
}%
\@tracklang@verbose{Current tracked dialect: '\CurrentTrackedDialect'.\MessageBreak
Language: '\CurrentTrackedLanguage'.\MessageBreak
ISO code: '\CurrentTrackedIsoCode'.\MessageBreak
Sub-lang: '\CurrentTrackedDialectSubLang'.\MessageBreak
Modifier: '\CurrentTrackedDialectModifier'.\MessageBreak
Variant: '\CurrentTrackedDialectVariant'.\MessageBreak
Script: '\CurrentTrackedDialectScript'.\MessageBreak
Region: '\CurrentTrackedRegion'.\MessageBreak
Additional: '\CurrentTrackedDialectAdditional'.\MessageBreak
Tag: '\CurrentTrackedLanguageTag'.
}%
}%
{%
  \@tracklang@warn{Unknown dialect label '#1' passed to
    \string\SetCurrentTrackedDialect}}%
  \edef\CurrentTrackedLanguage{\language}%
  \def\CurrentTrackedDialectModifier{}%
  \def\CurrentTrackedDialectVariant{}%
  \def\CurrentTrackedDialectScript{}%
  \def\CurrentTrackedDialectSubLang{}%
  \def\CurrentTrackedDialectAdditional{}%
  \def\CurrentTrackedIsoCode{}%
  \def\CurrentTrackedRegion{}%
}

```

```

\def\CurrentTrackedLanguageTag{und}%
}%
}

```

`\AddTrackedLanguageIsoCodes{<language>}`

`\AddTrackedLanguageIsoCodes`

Adds the 639-1, 639-2 and 639-3 ISO codes for the given language, which must have previously been declared using `\TrackLangNewLanguage`.

```

\def\AddTrackedLanguageIsoCodes#1{%
\@tracklang@ifundef{@tracklang@knowniso@639@1@#1}%
{}%
{%
\AddTrackedIsoLanguage\TwoLetterIsoLanguageCode
{\csname @tracklang@knowniso@639@1@#1\endcsname}{#1}%
}%
\@tracklang@ifundef{@tracklang@knowniso@639@2@#1}%
{}%
{%
\AddTrackedIsoLanguage\ThreeLetterIsoLanguageCode
{\csname @tracklang@knowniso@639@2@#1\endcsname}{#1}%

```

Does it have a different 639-2 (B) code?

```

\@tracklang@ifundef{@tracklang@knowniso@639@2B@#1}%
{}%
{%
\AddTrackedIsoLanguage{\ThreeLetterIsoLanguageCode-T}%
{\csname @tracklang@knowniso@639@2@#1\endcsname}{#1}%
\AddTrackedIsoLanguage{\ThreeLetterIsoLanguageCode-B}%
{\csname @tracklang@knowniso@639@2B@#1\endcsname}{#1}%
}%
}%
\@tracklang@ifundef{@tracklang@knowniso@639@3@#1}%
{}%
{%
\AddTrackedIsoLanguage\ThreeLetterExtIsoLanguageCode
{\csname @tracklang@knowniso@639@3@#1\endcsname}{#1}%
}%
}

```

`\AddTrackedCountryIsoCode`

As above but adds the 3166-1 country code if provided. Most root languages don't have an associated country code as they're spoken in multiple regions. Some of those that do have an associated region code may also be spoken as a minority language elsewhere, so this is separate from the previous command. If a regionless setting is required, use `\TrackLocale` instead of `\TrackPredefinedDialect`.

```

\def\AddTrackedCountryIsoCode#1{%
\@tracklang@ifundef{@tracklang@knowniso@3166@#1}%
{}%

```

```

    {%
      \expandafter \expandafter \expandafter
      \AddTrackedRegion
      \expandafter \expandafter \expandafter
      {\csname @tracklang@knowniso@3166@#1\endcsname}{#1}%
    }%
  }
}

```

## 4.4 Tracking Languages and Dialects

The commands here are provided to indicate that a language or dialect is active (tracked) in the document.

```
\TrackPredefinedDialect{<dialect label>}
```

\TrackPredefinedDialect

Track a predefined language or dialect.

```

\def\TrackPredefinedDialect#1{%
  \@tracklang@ifundef{@tracklang@add@#1}%
  {%
    \@tracklang@err{Dialect or language ‘#1’ is not predefined}{}%
  }%
  {\@tracklang@nameuse{@tracklang@add@#1}}%
}

```

\@tracklang@hassecondchar Check if second argument is present (non-empty and not \relax).

```

\def\@tracklang@hassecondchar#1#2\@end@tracklang@hassecondchar#3#4{%
  \ifx\relax#2\relax
    #4%
  \else
    #3%
  \fi
}

```

\@tracklang@hasthirdchar Check if third argument is present (non-empty and not \relax).

```

\def\@tracklang@hasthirdchar#1#2#3\@end@tracklang@hasthirdchar#4#5{%
  \ifx\relax#3\relax
    #5%
  \else
    #4%
  \fi
}

```

\@tracklang@hasfourthchar Check if fourth argument is present (non-empty and not \relax).

```

\def\@tracklang@hasfourthchar#1#2#3#4\@end@tracklang@hasfourthchar#5#6{%
  \ifx\relax#4\relax
    #6%
  \else

```

```

#5%
\fi
}

```

`\@tracklang@hasfifthchar` Check if fifth argument is present (non-empty and not `\relax`).

```

\def\@tracklang@hasfifthchar#1#2#3#4#5\@end@tracklang@hasfifthchar#6#7{%
\ifx\relax#5\relax
#7%
\else
#6%
\fi
}

```

`\@tracklang@hasninthchar` Check if ninth argument is present (non-empty and not `\relax`).

```

\def\@tracklang@hasninthchar#1#2#3#4#5#6#7#8#9\@end@tracklang@hasninthchar{%
\ifx\relax#9\relax
\expandafter\@tracklang@secondoftwo
\else
\expandafter\@tracklang@firstoftwo
\fi
}

```

`\@tracklang@ifalpha` Check if argument `a, ..., z` or `A, ..., Z`.

```

\def\@tracklang@ifalpha#1#2#3{%
\ifx\relax#1\relax
First argument empty or \relax.
#3%
\else
\ifnum\lccode'#1<'a\relax
#3%
\else
\ifnum\lccode'#1>'z\relax
#3%
\else
Is alpha.
#2%
\fi
\fi
\fi
}

```

`\@tracklang@ifdigit` Check if argument is digit (0, ..., 9).

```

\def\@tracklang@ifdigit#1#2#3{%
\ifx\relax#1\relax
First argument empty or \relax.
#3%
\else

```

```

\ifnum'#1<'0\relax
#3%
\else
\ifnum'#1>'9\relax
#3%
\else

```

Is digit.

```

#2%
\fi
\fi
\fi
}

```

`\@tracklang@ifalldigits` Check if the argument only consists of digits (no sign).

```

\def\@tracklang@ifalldigits#1{%
\expandafter\ifx\relax#1\relax
\expandafter\@tracklang@secondoftwo
\else
\expandafter\@tracklang@ifalldigits#1\@tracklang@nnil
\fi
}

```

`\@@tracklang@ifalldigits`

```

\def\@@tracklang@ifalldigits#1{%
\ifx#1\@tracklang@nnil
\def\@tracklang@next{\expandafter\@tracklang@firstoftwo}%
\else
\@tracklang@ifdigit{#1}%
{%
\let\@tracklang@next\@@tracklang@ifalldigits
}%
{%
\def\@tracklang@next##1\@tracklang@nnil{%
\expandafter\@tracklang@secondoftwo}%
}%
\fi
\@tracklang@next
}

```

`\@tracklang@ifalphanumeric` Check if argument is an alphanumeric (0,...,9) or (a,...,z) or (A,...,Z).

```

\def\@tracklang@ifalphanumeric#1#2#3{%
\@tracklang@ifalpha{#1}%
{#2}%
{%
\@tracklang@ifdigit{#1}{#2}{#3}%
}%
}

```

```
\TrackLangIfAlphaNumericChar{<tag>}{<true>}{<false>}
```

\TrackLangIfAlphaNumericChar

Check if the argument is a single alphanumeric character.

```
\def\TrackLangIfAlphaNumericChar#1#2#3{%
  \expandafter\ifx\expandafter\relax#1\relax
  Tag empty or \relax.
  #3%
  \else
  \expandafter\@tracklang@hassecondchar#1\relax\relax
  \end@tracklang@hassecondchar
  {#3}%
  \expandafter\@tracklang@ifalphanumeric#1{#2}{#3}%
  \fi
}
```

```
\TrackLangIfLanguageTag{<tag>}{<true>}{<false>}
```

\TrackLangIfLanguageTag

Check if the argument is a language tag (two or three letter lower case).

```
\def\TrackLangIfLanguageTag#1#2#3{%
  \expandafter\@tracklang@hasthirdchar#1\relax\relax\relax
  \end@tracklang@hasthirdchar
  {%
  Has 3 or more characters.
  \expandafter\@tracklang@hasfourthchar#1\relax\end@tracklang@hasfourthchar
  {#3}%
  {%
  Has 3 characters. Are they all lower case?
  \expandafter\@tracklang@iflanguage@iii@tag#1{#2}{#3}%
  }%
  }%
  {%
  Has less than 3 characters.
  \expandafter\@tracklang@hassecondchar#1\relax\relax
  \end@tracklang@hassecondchar
  {%
  Has two characters. Are they both lower case?
  \expandafter\@tracklang@iflanguage@ii@tag#1{#2}{#3}%
  }%
  {#3}%
  }%
  }
}

\@tracklang@iflanguage@ii@tag
\def\@tracklang@iflanguage@ii@tag#1#2#3#4{%
```



```

\ifnum\lccode'#1=#1\relax
\ifnum\lccode'#2=#2\relax
#3%
\else
#4%
\fi
\else
#4%
\fi
}

```

\tracklang@iflanguage@iii@tag

```

\def\@tracklang@iflanguage@iii@tag#1#2#3#4#5{%
\ifnum\lccode'#1=#1\relax
\ifnum\lccode'#2=#2\relax
\ifnum\lccode'#3=#3\relax
#4%
\else
#5%
\fi
\else
#5%
\fi
\else
#5%
\fi
}

```

`\TrackLangIfRegionTag{<tag>}{<true>}{<false>}`

\TrackLangIfRegionTag

Check if the argument is a region tag (two letter upper case or three digit numeric).

```

\def\TrackLangIfRegionTag#1#2#3{%
\expandafter\@tracklang@hasthirdchar#1\relax\relax\relax
\@end@tracklang@hasthirdchar
{%

```

Has 3 or more characters. Is it a three digit numeric code?

```

\expandafter\@tracklang@hasfourthchar#1\relax\@end@tracklang@hasfourthchar
{%

```

Has 4 or more characters.

```

#3%
}%
{%

```

Has 3 characters. Are they all digits?

```

\@tracklang@ifalldigits{#1}{#2}{#3}%
}%

```

```
}%  
{%
```

Has less than 3 characters.

```
\expandafter\@tracklang@hassecondchar#1\relax\relax  
\@end@tracklang@hassecondchar  
{%
```

Has two characters. Are they both upper case?

```
\expandafter\@tracklang@ifregion@ii@tag#1{#2}{#3}%  
}%  
{#3}%  
}%  
}
```

```
\@tracklang@ifregion@ii@tag
```

```
\def\@tracklang@ifregion@ii@tag#1#2#3#4{%  
\ifnum\uccode'#1='#1\relax  
\ifnum\uccode'#2='#2\relax  
#3%  
\else  
#4%  
\fi  
\else  
#4%  
\fi  
}
```

```
\@tracklang@ifregion@iii@tag
```

```
\def\@tracklang@ifregion@iii@tag#1#2#3#4#5{%  
\ifnum\uccode'#1='#1\relax  
\ifnum\uccode'#2='#2\relax  
\ifnum\uccode'#3='#3\relax  
#4%  
\else  
#5%  
\fi  
\else  
#5%  
\fi  
\else  
#5%  
\fi  
}
```

```
\TrackLangIfScriptTag{<tag>}{<true>}{<false>}
```

\TrackLangIfScriptTag

Check if the argument is a script tag (four letter title case).

```

\def\TrackLangIfScriptTag#1#2#3{%
  \expandafter\@tracklang@hasfifthchar#1\relax\relax\relax\relax\relax
  \@end@tracklang@hasfifthchar
  {#3}%
  {%

```

Has less than 5 characters.

```

  \expandafter\@tracklang@hasfourthchar#1\relax\relax\relax\relax
  \@end@tracklang@hasfourthchar
  {%

```

Has four characters. Are they title case? (First letter upper case, others lower case.)

```

  \expandafter\@tracklang@ifscripttag#1{#2}{#3}%
  }%
  {#3}%
  }%
}

```

\@tracklang@ifscripttag

```

\def\@tracklang@ifscripttag#1#2#3#4#5#6{%
  \ifnum\uccode'#1=#1\relax
  \ifnum\lccode'#2=#2\relax
  \ifnum\lccode'#3=#3\relax
  \ifnum\lccode'#4=#4\relax
  #5%
  \else
  #6%
  \fi
  \else
  #6%
  \fi
  \else
  #6%
  \fi
  \else
  #6%
  \fi
}

```

\TrackLangIfVariantTag{<tag>}{<true>}{<false>}

\TrackLangIfVariantTag

Check if the argument is a variant tag.

```

\def\TrackLangIfVariantTag#1#2#3{%
  \expandafter\@tracklang@hasfifthchar#1\relax\relax\relax\relax\relax
  \@end@tracklang@hasfifthchar
  {%

```

Has at least 5 characters. Does it have a maximum of 8?

```

\expandafter\@tracklang@hasninthchar#1\relax\relax\relax\relax\relax
\relax\relax\relax\relax
\@end@tracklang@hasninthchar
{#3}%
{#2}%
}%
{%

```

Less than 5 characters.

```

\expandafter\@tracklang@hasfourthchar#1\relax\relax\relax\relax
\@end@tracklang@hasfourthchar
{%

```

Has 4 characters.

```

\expandafter\@tracklang@ifvariant@iv@tag#1{#2}{#3}%
}%
{#3}%
}%
}

```

\@tracklang@ifvariant@iv@tag four character variant starting with a digit.

```

\def\@tracklang@ifvariant@iv@tag#1#2#3#4#5#6{%
\@tracklang@ifdigit{#1}%
{#5}
{#6}%
}

```

\@tracklang@parse@extlang \@TrackLangEnvSubLang, \@tracklang@split@pre and \@tracklang@split@post should be initialised before use. This assumes the tag is well formed.

```

\def\@tracklang@parse@extlang{%
\TrackLangIfLanguageTag{\@tracklang@split@pre}
{%
\ifx\@TrackLangEnvSubLang\empty
\let\@TrackLangEnvSubLang\@tracklang@split@pre
\let\@TrackLangEnvFirstSubLang\@TrackLangEnvSubLang
\else
\edef\@TrackLangEnvSubLang{\@TrackLangEnvSubLang-\@tracklang@split@pre}%
\fi
}

```

Split again if there's more.

```

\ifx\@tracklang@split@post\empty
\else
\expandafter\@tracklang@split@underscoreorhyp\expandafter
{\@tracklang@split@post}%
\ifx\@tracklang@split@pre\empty
\else
\@tracklang@parse@extlang
\fi
\fi
}%
{}%

```

```
}
```

`\@tracklang@parse@variant` `\@TrackLangEnvVariant`, `\@tracklang@split@pre` and `\tracklang@split@post` should be initialised before use.

```
\def\@tracklang@parse@variant{%
  \TrackLangIfVariantTag{\@tracklang@split@pre}
  {%
    \ifx\@TrackLangEnvVariant\empty
      \let\@TrackLangEnvVariant\@tracklang@split@pre
    \else
      \edef\@TrackLangEnvVariant{\@TrackLangEnvVariant
        -\@tracklang@split@pre}%
    \fi
```

Split again if there's more.

```
\ifx\@tracklang@split@post\empty
\else
  \expandafter\@tracklang@split@underscoreorhyp\expandafter
    {\@tracklang@split@post}%
  \ifx\@tracklang@split@pre\empty
  \else
    \@tracklang@parse@variant
  \fi
\fi
}%
}%
}
```

```
\TrackLanguageTag{tag}
```

`\TrackLanguageTag`

Parse RFC 5646 language tag (assumes regular and well-formed). See also <https://tools.ietf.org/html/rfc5646>. Ensure `<tag>` is fully-expanded. Warn if argument is empty.

```
\def\TrackLanguageTag#1{%
  \edef\@tracklang@tag{#1}%
  \ifx\@tracklang@tag\empty
    \@tracklang@warn{Empty tag in \string\TrackLanguageTag}%
  \else
    \expandafter\@TrackLanguageTag\expandafter{\@tracklang@tag}%
  \fi
}
```

`\@TrackLanguageTag` Argument must be expanded.

```
\def\@TrackLanguageTag#1{%
First check if it's predefined.
  \@tracklang@ifundef{\@tracklang@add@#1}%
  {%
```

Parse language tag.

```
\@tracklang@parselangtag{#1}%
```

Track this information.

```
\@tracklang@track@locale  
}%  
{%
```

Predefined tag.

```
\@tracklang@nameuse{@tracklang@add@#1}%  
}%  
}
```

```
\TrackIfKnownLanguage{<tag>}{<success code>}{<fail code>}
```

\TrackIfKnownLanguage

Like \TrackLanguageTag but does *<fail code>* if the tag doesn't contain a valid language code. If successful, does *<success code>* after tracking the language.

```
\def\TrackIfKnownLanguage#1#2#3{%  
  \edef\@tracklang@tag{#1}%  
  \ifx\@tracklang@tag\empty  
    #3%  
  \else  
    \expandafter\@TrackIfKnownLanguage\expandafter{\@tracklang@tag}{#2}{#3}%  
  \fi  
}
```

\@TrackIfKnownLanguage Argument must be expanded.

```
\def\@TrackIfKnownLanguage#1#2#3{%
```

First check if it's predefined.

```
\@tracklang@ifundef{@tracklang@add@#1}%  
{%
```

Parse language tag.

```
\@tracklang@parselangtag{#1}%
```

Track this information if \@TrackLangEnvLang is a known ISO language code.

```
\TrackLangIfKnownLangFromIso{\@TrackLangEnvLang}%  
{\@tracklang@track@locale#2}{#3}%  
}%  
{%
```

Predefined tag.

```
\@tracklang@nameuse{@tracklang@add@#1}%  
#2%  
}%  
}
```

\@tracklang@parse@langtag

```
\def\@tracklang@parselangtag#1{%
```

Initialise.

```
\def\@TrackLangEnvLang{}%
\def\@TrackLangEnvSubLang{}%
\def\@TrackLangEnvFirstSubLang{}%
\def\@TrackLangEnvTerritory{}%
\def\@TrackLangEnvCodeSet{}%
\def\@TrackLangEnvVariant{}%
\def\@TrackLangEnvModifier{}%
\def\@TrackLangEnvScript{}%
\def\@TrackLangEnvAdditional{}%
```

First split to determine language code.

```
\@tracklang@split@underscoreorhyps{#1}%
```

Save the result.

```
\let\@TrackLangEnvLang\@tracklang@split@pre
```

Is there anything else?

```
\ifx\@tracklang@split@post\empty
```

That's it.

```
\else
```

Split again.

```
\expandafter\@tracklang@split@underscoreorhyps\expandafter
{\@tracklang@split@post}%
```

Is this an extension to the language tag?

```
\@tracklang@parse@extlang
```

Does this fit the format for a script?

```
\TrackLangIfScriptTag{\@tracklang@split@pre}%
{%
```

Found script.

```
\let\@TrackLangEnvScript\@tracklang@split@pre
```

Split again if there's more.

```
\ifx\@tracklang@split@post\empty
\else
\expandafter\@tracklang@split@underscoreorhyps\expandafter
{\@tracklang@split@post}%
\fi
}%
{}
```

Does this fit the format for a region?

```
\TrackLangIfRegionTag{\@tracklang@split@pre}%
{%
```

Found region. Is it a 2 letter alpha or a 3 digit numeric code?

```
\expandafter\@tracklang@hasthirdchar\@tracklang@split@pre
\relax\relax\relax
\@end@tracklang@hasthirdchar
{%
```

Is three digit numeric code. We need the mappings. Has tracklang-region-codes.tex been loaded?

```

\ifx\TrackLangIfKnownNumericRegion\undefined
  \@tracklang@inputfile{tracklang-region-codes.tex}%
\fi
\TrackLangIfKnownNumericRegion{\@tracklang@split@pre}%
{%
  \edef\@TrackLangEnvTerritory{%
    \TrackLangNumericToAlphaIIRegion{\@tracklang@split@pre}%
  }%
}%
{%
  \let\@TrackLangEnvTerritory\@tracklang@split@pre
  \@tracklang@warn{Unrecognised numeric region code
    '\@tracklang@split@pre'}%
}%
}%
{%

```

Is two letter alpha code.

```

\let\@TrackLangEnvTerritory\@tracklang@split@pre
}%
\expandafter\@tracklang@split@underscoreorhyp\expandafter
{\@tracklang@split@post}%
}%
{}%

```

Parse for variant.

```

\@tracklang@parse@variant

```

Anything left can go in additional.

```

\let\@TrackLangEnvAdditional\@tracklang@split@post
\fi
}%

```

\input@extra@region@filelist

```

\def\@tracklang@extra@region@filelist{}

```

\TrackLangAddExtraRegionFile Add a file name to the list of extra region code files that should be input by tracklang-regions-codes.tex

```

\def\TrackLangAddExtraRegionFile#1{%
  \ifx\TrackLangRegionMap\undefined
  \else

```

tracklang-region-codes.tex has already been loaded so input the file now.

```

  \@tracklang@inputfile{#1}%
  \fi
  \@tracklang@add{#1}{\@tracklang@extra@region@filelist}%
}

```



`ng@input@extra@region@files` Iterate through list of extra region files to allow other packages to define new regions.

```
\def\@tracklang@input@extra@region@files{%
  \@tracklang@for\@tracklang@currfile:=\@tracklang@extra@region@filelist\do
  {%
    \@tracklang@inputfile{\@tracklang@currfile}%
  }%
}
```

`input@extra@script@filelist`

```
\def\@tracklang@extra@script@filelist{}
```

`TrackLangAddExtraScriptFile` Add the given file name to the list of files that should be automatically loaded by tracklang-scripts.tex

```
\def\TrackLangAddExtraScriptFile#1{%
  \ifx\TrackLangScriptMap\undefined
  \else
```

tracklang-scripts.tex has already been loaded so input the file now.

```
    \@tracklang@inputfile{#1}%
  \fi
  \@tracklang@add{#1}{\@tracklang@extra@script@filelist}%
}
```

`ng@input@extra@script@files` Iterate through list of extra script files to allow other packages to define new scripts.

```
\def\@tracklang@input@extra@script@files{%
  \@tracklang@for\@tracklang@currfile:=\@tracklang@extra@script@filelist\do
  {%
    \@tracklang@inputfile{\@tracklang@currfile}%
  }%
}
```

```
\GetTrackedDialectFromLanguageTag{<tag>}{<cs>}
```

`TrackedDialectFromLanguageTag`

Find the tracked dialect that matches the given language tag and stores the dialect label in `<cs>`. If no match found, `<cs>` will be empty. Just tests the root language, script, variant, sub-language and region. Doesn't check the additional information. As from v1.3.6, this sets `\TrackedDialectClosestSubMatch` to the closest sub-match.

```
\def\GetTrackedDialectFromLanguageTag#1#2{%
```

Initialise default values (in case of no match).

```
  \def#2{}%
  \def\TrackedDialectClosestSubMatch{}%
  \@tracklang@parselangtag{#1}%
  \edef\@tracklang@dialect{%
```

```

    \@TrackLangEnvLang
    \@TrackLangEnvSubLang
    \@TrackLangEnvScript
    \@TrackLangEnvTerritory
    \@TrackLangEnvModifier
    \@TrackLangEnvVariant}%

Has this dialect label been tracked?
    \IfTrackedDialect{\@tracklang@dialect}%
    {%

Found it. All done.
        \let#2\@tracklang@dialect
    }%
    {%

Get the root language label.
        \edef\@tracklang@lang{\TrackLangGetKnownLangFromIso\@TrackLangEnvLang}%

Get the default script for this language.
        \edef\@tracklang@defscript{\TrackLangGetDefaultScript\@tracklang@lang}%

Keep track of best match.
        \def\@tracklang@bestmatch{0}%

Get the list of tracked dialects for this language.
        \edef\@tracklang@dialects{\TrackedDialectsFromLanguage\@tracklang@lang}%

For each dialect in this list, check if it matches.
        \@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%

Does the script match? (Initialise to no.)
        \def\@tracklang@currentmatch{0}%
        \edef\@tracklang@tmp{%
            \GetTrackedDialectScript{\@tracklang@dialect}}%
        \ifx\@tracklang@tmp\@TrackLangEnvScript

Script matches.
            \def\@tracklang@currentmatch{1}%
        \else

Script doesn't match. If no script has been provided, does this dialect's script
match the default for this language?
            \ifx\@TrackLangEnvScript\empty
                \ifx\@tracklang@tmp\@tracklang@defscript

Default script matches.
                    \def\@tracklang@currentmatch{1}%
                \fi
            \fi
        \fi
    }%

```

Does the sub-language match?

```
\edef\@tracklang@tmp{%  
  \GetTrackedDialectSubLang{\@tracklang@dialect}}%  
  \ifx\@tracklang@tmp\@TrackLangEnvSubLang
```

Sub-language matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%  
\else
```

Sub-language doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%  
\fi
```

Does the variant match?

```
\edef\@tracklang@tmp{%  
  \GetTrackedDialectVariant{\@tracklang@dialect}}%  
  \ifx\@tracklang@tmp\@TrackLangEnvVariant
```

Variant matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%  
\else
```

Variant doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%  
\fi
```

Does the region match?

```
\edef\@tracklang@tmp{%  
  \TrackedIsoCodeFromLanguage{3166-1}{\@tracklang@dialect}}%  
  \ifx\@tracklang@tmp\@TrackLangEnvTerritory
```

Region matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%  
\else
```

Region doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%  
\fi
```

Do all four match?

```
\ifx\@tracklang@currentmatch\@tracklang@fullmatch
```

Found it.

```
\let#2\@tracklang@dialect  
\else
```

Not a complete match. Is this the best match so far?

```
\ifnum\@tracklang@currentmatch>\@tracklang@bestmatch\relax  
  \let\TrackedDialectClosestSubMatch\@tracklang@dialect  
  \let\@tracklang@bestmatch\@tracklang@currentmatch  
  \fi  
\fi
```

```
}%  
}%  
}
```

`\@tracklang@fullmatch` (Used to identify a full match for script, sub-language, variant and region.)

```
\def\@tracklang@fullmatch{1111}
```

`\TrackLangFromEnv` This command performs the following steps: query environment variable (if `\TrackLangEnv` not already set), parse `\TrackLangEnv` (if it has been set), and add the dialect (if recognised).

Note that this works slightly differently from just using `\TrackLangQueryEnv` followed by `\TrackLangParseFromEnv` and `\TrackPredefinedDialect`.

```
\def\TrackLangFromEnv{%
```

Initialise.

```
\def\TrackLangEnvLang{}%
\def\TrackLangEnvTerritory{}%
\def\TrackLangEnvCodeSet{}%
\def\TrackLangEnvModifier{}%
```

If `\TrackQueryEnv` is empty, assume `\TrackQueryEnv` has already been attempted but failed, so don't bother retrying.

```
\ifx\TrackLangEnv\undefined
  \TrackLangQueryEnv
\fi
\ifx\TrackLangEnv\empty
  \@tracklang@warn{\string\TrackLangFromEnv\space
    non-operational as \string\TrackLangEnv\space is empty}%
\else
```

At this point `\TrackLangEnv` shouldn't be undefined (if `\TrackLangQueryEnv` fails it should define `\TrackLangEnv` to be empty), but check in case something unexpected has happened.

```
\ifx\TrackLangEnv\undefined
  \@tracklang@warn{\string\TrackLangFromEnv\space
    non-operational as \string\TrackLangEnv\space hasn't been
    defined}%
\else
```

Parse and track.

```
\@tracklang@parse@track@locale{\TrackLangEnv}%
\let\TrackLangEnvLang\@TrackLangEnvLang
\let\TrackLangEnvTerritory\@TrackLangEnvTerritory
\let\TrackLangEnvCodeSet\@TrackLangEnvCodeSet
\let\TrackLangEnvModifier\@TrackLangEnvModifier
\fi
\fi
}
```

`\TrackLocale`

```
\TrackLocale{<locale>}
```

Track the dialect identified by the given locale. The argument may either be a predefined language/dialect or in the same format as `\TrackLangEnv`.

```

\def\TrackLocale#1{%
Is the argument a recognised dialect?
  \@tracklang@ifundef{\@tracklang@add@#1}%
  {%
  \@tracklang@parse@track@locale{#1}%
  }%
  {%
  \@tracklang@nameuse{\@tracklang@add@#1}%
  }%
}

```

\@tracklang@parse@track@locale Parse localisation format and track.

```

\def\@tracklang@parse@track@locale#1{%
  \@tracklang@parse@locale{#1}%
  \@tracklang@track@locale
}

```

\@tracklang@track@locale

```

\def\@tracklang@track@locale{%
Is the language code known?
  \TrackLangIfKnownLangFromIso{\@TrackLangEnvLang}
  {%
  \edef\@tracklang@lang{\TrackLangGetKnownLangFromIso\@TrackLangEnvLang}%
  \let\@tracklang@dialect\@TrackLangEnvLang
  \ifx\@TrackLangEnvSubLang\empty
  \else
  \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvSubLang}%
  \fi
  \ifx\@TrackLangEnvScript\empty
  \else
  \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvScript}%
  \fi
  \ifx\@TrackLangEnvTerritory\empty
  \else
  \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvTerritory}%
  \fi
  \ifx\@TrackLangEnvModifier\empty
  \else
  \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvModifier}%
  \fi
  \ifx\@TrackLangEnvVariant\empty
  \else
  \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvVariant}%
  \fi
  Language code is recognised. Is the dialect label recognised?
  \@tracklang@ifundef{\@tracklang@add@\@tracklang@dialect}%
  {%

```

Not a recognised dialect. Form new dialect name (without hyphen).

```
\edef\@tracklang@dialect{%
  \@TrackLangEnvLang
  \@TrackLangEnvSubLang
  \@TrackLangEnvScript
  \@TrackLangEnvTerritory
  \@TrackLangEnvModifier
  \@TrackLangEnvVariant}%
```

Add this new dialect.

```
\AddTrackedDialect{\@tracklang@dialect}{\@tracklang@lang}%
\AddTrackedLanguageIsoCodes{\@tracklang@lang}%
```

Is there a sub-language tag?

```
\ifx\@TrackLangEnvFirstSubLang\empty
\else
  \expandafter\AddTrackedIsoLanguage
  \expandafter\ThreeLetterExtIsoLanguageCode
  \expandafter{\@TrackLangEnvFirstSubLang}%
  {\@tracklang@dialect}%
\fi
}%
{%
```

Dialect is recognised.

```
\csname @tracklang@add@\@tracklang@dialect\endcsname
}%
}%
{%
```

Unknown language code.

```
\@tracklang@warn{Unknown language code '\@TrackLangEnvLang'}%
\edef\@tracklang@dialect{%
  \@TrackLangEnvLang
  \@TrackLangEnvSubLang
  \@TrackLangEnvScript
  \@TrackLangEnvTerritory
  \@TrackLangEnvModifier
  \@TrackLangEnvVariant}%
\AddTrackedDialect{\@tracklang@dialect}{\@TrackLangEnvLang}%
```

Determine if the language code is a two or three letter code.

```
\expandafter\@tracklang@hasthirdchar
  \@TrackLangEnvLang\relax\relax\relax\@end\@tracklang@hasthirdchar
{%
```

639-2 code. Track it.

```
\AddTrackedIsoLanguage{639-2}{\@TrackLangEnvLang}{undetermined}%
}%
{%
```

639-1 code. Track it.

```
        \AddTrackedIsoLanguage{639-1}{\@TrackLangEnvLang}{undetermined}%  
    }%  
}%
```

Add the territory if provided. (The territory may not have been defined by the dialect option.)

```
    \ifx\@TrackLangEnvTerritory\empty  
    \else  
        \expandafter\AddTrackedRegion\expandafter  
        {\@TrackLangEnvTerritory}%  
        {\@tracklang@dialect}%  
    \fi
```

If a modifier was provided, add that.

```
    \ifx\@TrackLangEnvModifier\empty  
    \else  
        \SetTrackedDialectModifier{\@tracklang@dialect}{\@TrackLangEnvModifier}%  
    \fi
```

If a variant was provided, add that.

```
    \ifx\@TrackLangEnvVariant\empty  
    \else  
        \SetTrackedDialectVariant{\@tracklang@dialect}{\@TrackLangEnvVariant}%  
    \fi
```

If a script was provided, add that.

```
    \ifx\@TrackLangEnvScript\empty  
    \else  
        \SetTrackedDialectScript{\@tracklang@dialect}{\@TrackLangEnvScript}%  
    \fi
```

If a language extension was provided, add that.

```
    \ifx\@TrackLangEnvSubLang\empty  
    \else  
        \SetTrackedDialectSubLang{\@tracklang@dialect}{\@TrackLangEnvSubLang}%  
    \fi
```

If additional information was provided, add that.

```
    \ifx\@TrackLangEnvAdditional\empty  
    \else  
        \SetTrackedDialectAdditional{\@tracklang@dialect}{\@TrackLangEnvAdditional}%  
    \fi  
}
```

## 4.5 Predefined Root Languages

The ISO 639-1 and 639-2 codes are used to map the root language name to the ISO language code. The 3166-1 codes are used to map the dialect/variant to the ISO country code. The country code is omitted if ambiguous (for example, the language is spoken in multiple countries). Languages that have a country

code may be spoken as a minority language in another region. In this case, `\TrackLocale` should be used instead to set the country code as appropriate. Some “dialects” are just synonyms for a language name, such as “francais” or “frenchb”. These are defined in §4.6. Some of the languages have two ISO 639-2 codes designated as “B” (bibliographic) or “T” (terminology). In these cases the terminology code is used as the primary 639-2 code. The extra “B” and “T” codes are only provided if they are different.

`\@tracklang@declareoption` Provide a hook to declare a predefined setting as a package option. This is defined by `tracklang.sty` before loading `tracklang.tex` but if this file isn’t loaded through `tracklang.sty` provide a definition that ignores its argument if not already defined.

```
\ifx\@tracklang@declareoption\undefined
  \def\@tracklang@declareoption#1{}
\fi
```

`\TrackLangProvidePredefinedLanguage` Set up a language label for use with `\TrackPredefinedDialect`. Note that this doesn’t check if already defined.

```
\def\TrackLangProvidePredefinedLanguage#1{%
  \@tracklang@namedef{\@tracklang@add@#1}{%
    \AddTrackedLanguage{#1}%
    \AddTrackedLanguageIsoCodes{#1}%
    \AddTrackedCountryIsoCode{#1}%
  }%
}
```

```
\TrackLangDeclareLanguageOption{\language name}{\639-1
code}{\639-2 (T)}{\639-2 (B)}{\639-3}{\3166-1}{\default
script}}
```

`\TrackLangDeclareLanguageOption`

Define a new root language that’s declared as an option. The language name must be expanded before use. The default script is the ISO 15924 alpha script code. (Some languages may be written in multiple scripts. Leave empty if not obvious default.)

```
\def\TrackLangDeclareLanguageOption#1#2#3#4#5#6#7{%
  \@tracklang@ifundef{\@tracklang@add@#1}{%
    {%
      \TrackLangNewLanguage{#1}{#2}{#3}{#4}{#5}{#6}{#7}%
      \TrackLangProvidePredefinedLanguage{#1}%
      \@tracklang@declareoption{#1}%
    }%
    {%
      \@tracklang@err{language option ‘#1’ has already been defined}{}%
    }%
  }%
}
```



```

\@tracklang@add@abkhaz
\TrackLangDeclareLanguageOption{abkhaz}{ab}{abk}{}{}{Cyr1}

\@tracklang@add@afar
\TrackLangDeclareLanguageOption{afar}{aa}{aar}{}{}{Latn}

\@tracklang@add@afrikaans
\TrackLangDeclareLanguageOption{afrikaans}{af}{afr}{}{}{Latn}

\@tracklang@add@akan
\TrackLangDeclareLanguageOption{akan}{ak}{aka}{}{}{Latn}

\@tracklang@add@albanian
\TrackLangDeclareLanguageOption{albanian}{sq}{sqi}{alb}{}{}{Latn}

\@tracklang@add@amharic
\TrackLangDeclareLanguageOption{amharic}{am}{amh}{}{}{ET}{Ethi}

\@tracklang@add@anglosaxon
\TrackLangDeclareLanguageOption{anglosaxon}{}{ang}{}{}{Runr}

\@tracklang@add@apache
\TrackLangDeclareLanguageOption{apache}{}{apa}{}{}{Latn}

\@tracklang@add@arabic
\TrackLangDeclareLanguageOption{arabic}{ar}{ara}{}{}{Arab}

\@tracklang@add@aragones
\TrackLangDeclareLanguageOption{aragones}{an}{arg}{}{}{ES}{Latn}

\@tracklang@add@armenian
\TrackLangDeclareLanguageOption{armenian}{hy}{hye}{arm}{}{}{Armn}

\@tracklang@add@assamese
\TrackLangDeclareLanguageOption{assamese}{as}{asm}{}{}{Beng}

\@tracklang@add@asturian
\TrackLangDeclareLanguageOption{asturian}{}{ast}{}{}{Latn}

\@tracklang@add@avaric
\TrackLangDeclareLanguageOption{avaric}{av}{ava}{}{}{Cyr1}

\@tracklang@add@avestan
\TrackLangDeclareLanguageOption{avestan}{ae}{ave}{}{}{Avst}

\@tracklang@add@aymara
\TrackLangDeclareLanguageOption{aymara}{ay}{aym}{}{}{Latn}

```

`\@tracklang@add@azerbaijani` The default script is dependent on the region, but this is a regionless definition so using Latin as the default here as Azerbaijani alphabet is a Latin alphabet. Other countries may be using a different script, such as Cyrillic in Russia.  
`\TrackLangDeclareLanguageOption{azerbaijani}{az}{aze}{}{}{Latn}`

`\@tracklang@add@bahasai`  
`\TrackLangDeclareLanguageOption{bahasai}{id}{ind}{}{}{IN}{Latn}`

`\@tracklang@add@bahasam`  
`\TrackLangDeclareLanguageOption{bahasam}{ms}{msa}{may}{}{}{MY}{Latn}`

`\@tracklang@add@bambara`  
`\TrackLangDeclareLanguageOption{bambara}{bm}{bam}{}{}{ML}{Latn}`

`\@tracklang@add@bashkir`  
`\TrackLangDeclareLanguageOption{bashkir}{ba}{bak}{}{}{Cyr1}`

`\@tracklang@add@basque`  
`\TrackLangDeclareLanguageOption{basque}{eu}{eus}{baq}{}{}{Latn}`

`\@tracklang@add@belarusian`  
`\TrackLangDeclareLanguageOption{belarusian}{be}{bel}{}{}{Cyr1}`

`\@tracklang@add@bengali`  
`\TrackLangDeclareLanguageOption{bengali}{bn}{ben}{}{}{Beng}`

`\@tracklang@add@berber` No default. Could be Tifinagh, Latin or Arabic.  
`\TrackLangDeclareLanguageOption{berber}{}{ber}{}{}{}`

`\@tracklang@add@bihari` No clear default.  
`\TrackLangDeclareLanguageOption{bihari}{bh}{bih}{}{}{}`

`\@tracklang@add@bislama`  
`\TrackLangDeclareLanguageOption{bislama}{bi}{bis}{}{}{VU}{Latn}`

`\@tracklang@add@bokmal`  
`\TrackLangDeclareLanguageOption{bokmal}{nb}{nob}{}{}{NO}{Latn}`

`\@tracklang@add@bosnian`  
`\TrackLangDeclareLanguageOption{bosnian}{bs}{bos}{}{}{Latn}`

`\@tracklang@add@breton`  
`\TrackLangDeclareLanguageOption{breton}{br}{bre}{}{}{FR}{Latn}`

`\@tracklang@add@bulgarian`  
`\TrackLangDeclareLanguageOption{bulgarian}{bg}{bul}{}{}{Cyr1}`

```

\@tracklang@add@burmese
\TrackLangDeclareLanguageOption{burmese}{my}{mya}{bur}{}{}{Mymr}

\@tracklang@add@catalan
\TrackLangDeclareLanguageOption{catalan}{ca}{cat}{}{}{}{Latn}

\@tracklang@add@chamorro
\TrackLangDeclareLanguageOption{chamorro}{ch}{cha}{}{}{}{Latn}

\@tracklang@add@chechen
\TrackLangDeclareLanguageOption{chechen}{ce}{che}{}{}{}{Cyr1}

\@tracklang@add@chichewa
\TrackLangDeclareLanguageOption{chichewa}{ny}{nya}{}{}{}{Latn}

\@tracklang@add@chinese
\TrackLangDeclareLanguageOption{chinese}{zh}{zho}{chi}{}{}{Hans}

\@tracklang@add@churchslavonic
\TrackLangDeclareLanguageOption{churchslavonic}{cu}{chu}{}{}{}{Glag}

\@tracklang@add@chuvash
\TrackLangDeclareLanguageOption{chuvash}{cv}{chv}{}{}{}{RU}{Cyr1}

\@tracklang@add@coptic
\TrackLangDeclareLanguageOption{coptic}{}{cop}{}{}{}{Copt}

\@tracklang@add@cornish
\TrackLangDeclareLanguageOption{cornish}{kw}{cor}{}{}{}{GB}{Latn}

\@tracklang@add@corsican
\TrackLangDeclareLanguageOption{corsican}{co}{cos}{}{}{}{Latn}

\@tracklang@add@cree
\TrackLangDeclareLanguageOption{cree}{cr}{cre}{}{}{}{Cans}

\@tracklang@add@croatian
\TrackLangDeclareLanguageOption{croatian}{hr}{hrv}{}{}{}{Latn}

\@tracklang@add@czech
\TrackLangDeclareLanguageOption{czech}{cs}{ces}{cze}{}{}{Latn}

\@tracklang@add@danish
\TrackLangDeclareLanguageOption{danish}{da}{dan}{}{}{}{Latn}

\@tracklang@add@divehi
\TrackLangDeclareLanguageOption{divehi}{dv}{div}{}{}{}{MV}{Thaa}

```

```

\@tracklang@add@dutch
\TrackLangDeclareLanguageOption{dutch}{nl}{nld}{dut}{}{}{Latn}

\@tracklang@add@dzongkha
\TrackLangDeclareLanguageOption{dzongkha}{dz}{dzo}{}{}{BT}{Tibt}

\@tracklang@add@easternpunjabi
\TrackLangDeclareLanguageOption{easternpunjabi}{pa}{pan}{}{}{IN}{Guru}

\@tracklang@add@english
\TrackLangDeclareLanguageOption{english}{en}{eng}{}{}{}{Latn}

\@tracklang@add@esperanto
\TrackLangDeclareLanguageOption{esperanto}{eo}{epo}{}{}{}{Latn}

\@tracklang@add@estonian
\TrackLangDeclareLanguageOption{estonian}{et}{est}{}{}{}{Latn}

\@tracklang@add@ewe
\TrackLangDeclareLanguageOption{ewe}{ee}{ewe}{}{}{}{Latn}

\@tracklang@add@faroese
\TrackLangDeclareLanguageOption{faroese}{fo}{fao}{}{}{}{Latn}

\@tracklang@add@farsi
\TrackLangDeclareLanguageOption{farsi}{fa}{fas}{per}{}{}{Arab}

\@tracklang@add@fijian
\TrackLangDeclareLanguageOption{fijian}{fj}{fij}{}{}{FJ}{Latn}

\@tracklang@add@finnish
\TrackLangDeclareLanguageOption{finnish}{fi}{fin}{}{}{}{Latn}

\@tracklang@add@french
\TrackLangDeclareLanguageOption{french}{fr}{fra}{fre}{}{}{Latn}

\@tracklang@add@friulan
\TrackLangDeclareLanguageOption{friulan}{}{fur}{}{}{IT}{Latn}

\@tracklang@add@fula No default. Could be Latin or Arabic.
\TrackLangDeclareLanguageOption{fula}{ff}{ful}{}{}{}{}

\@tracklang@add@galician
\TrackLangDeclareLanguageOption{galician}{gl}{glg}{}{}{}{Latn}

\@tracklang@add@ganda
\TrackLangDeclareLanguageOption{ganda}{lg}{lug}{}{}{UG}{Latn}

```

```

\@tracklang@add@georgian
\TrackLangDeclareLanguageOption{georgian}{ka}{kat}{geo}{}{}{Geor}

\@tracklang@add@german
\TrackLangDeclareLanguageOption{german}{de}{deu}{ger}{}{}{Latn}

\@tracklang@add@greek
\TrackLangDeclareLanguageOption{greek}{el}{ell}{gre}{}{}{Grek}

\@tracklang@add@guarani
\TrackLangDeclareLanguageOption{guarani}{gn}{grn}{}{}{}{Latn}

\@tracklang@add@gujarati
\TrackLangDeclareLanguageOption{gujarati}{gu}{guj}{}{}{}{Gujr}

\@tracklang@add@haitian
\TrackLangDeclareLanguageOption{haitian}{ht}{hat}{}{}{}{HT}{Latn}

\@tracklang@add@hausa
\TrackLangDeclareLanguageOption{hausa}{ha}{hau}{}{}{}{Latn}

\@tracklang@add@hebrew
\TrackLangDeclareLanguageOption{hebrew}{he}{heb}{}{}{}{Hebr}

\@tracklang@add@herero
\TrackLangDeclareLanguageOption{herero}{hz}{her}{}{}{}{Latn}

\@tracklang@add@hindi
\TrackLangDeclareLanguageOption{hindi}{hi}{hin}{}{}{}{Deva}

\@tracklang@add@hirimotu
\TrackLangDeclareLanguageOption{hirimotu}{ho}{hmo}{}{}{}{PG}{Latn}

\@tracklang@add@icelandic
\TrackLangDeclareLanguageOption{icelandic}{is}{isl}{ice}{}{}{IS}{Latn}

\@tracklang@add@ido
\TrackLangDeclareLanguageOption{ido}{io}{ido}{}{}{}{Latn}

\@tracklang@add@igbo
\TrackLangDeclareLanguageOption{igbo}{ig}{ibo}{}{}{}{Latn}

\@tracklang@add@interlingua
\TrackLangDeclareLanguageOption{interlingua}{ia}{ina}{}{}{}{Latn}

\@tracklang@add@interlingue
\TrackLangDeclareLanguageOption{interlingue}{ie}{ile}{}{}{}{Latn}

```

\@tracklang@add@inuktitut  
\TrackLangDeclareLanguageOption{inuktitut}{iu}{iku}{}{}{Cans}

\@tracklang@add@inupiaq  
\TrackLangDeclareLanguageOption{inupiaq}{ik}{ipk}{}{}{Latn}

\@tracklang@add@irish  
\TrackLangDeclareLanguageOption{irish}{ga}{gle}{}{}{Latn}

\@tracklang@add@italian  
\TrackLangDeclareLanguageOption{italian}{it}{ita}{}{}{Latn}

\@tracklang@add@japanese  
\TrackLangDeclareLanguageOption{japanese}{ja}{jpn}{}{}{Hani}

\@tracklang@add@javanese  
\TrackLangDeclareLanguageOption{javanese}{jv}{jav}{}{}{Latn}

\@tracklang@add@kalaallisut  
\TrackLangDeclareLanguageOption{kalaallisut}{kl}{kal}{}{}{Latn}

\@tracklang@add@kannada  
\TrackLangDeclareLanguageOption{kannada}{kn}{kan}{}{}{IN}{Knda}

\@tracklang@add@kanuri  
\TrackLangDeclareLanguageOption{kanuri}{kr}{kau}{}{}{Latn}

\@tracklang@add@kashmiri No default script. Could be Arabic or Devanagari.  
\TrackLangDeclareLanguageOption{kashmiri}{ks}{kas}{}{}{IN}{}

\@tracklang@add@kazakh Default script varies according to region.  
\TrackLangDeclareLanguageOption{kazakh}{kk}{kaz}{}{}{}

\@tracklang@add@khmer  
\TrackLangDeclareLanguageOption{khmer}{km}{khm}{}{}{Khmr}

\@tracklang@add@kikuyu  
\TrackLangDeclareLanguageOption{kikuyu}{ki}{kik}{}{}{Latn}

\@tracklang@add@kinyarwanda  
\TrackLangDeclareLanguageOption{kinyarwanda}{rw}{kin}{}{}{Latn}

\@tracklang@add@kirundi  
\TrackLangDeclareLanguageOption{kirundi}{rn}{run}{}{}{Latn}

\@tracklang@add@komi  
\TrackLangDeclareLanguageOption{komi}{kv}{kom}{}{}{RU}{Cyr1}

```

\@tracklang@add@kongo
\TrackLangDeclareLanguageOption{kongo}{kg}{kon}{}{}{Latn}

\@tracklang@add@korean
\TrackLangDeclareLanguageOption{korean}{ko}{kor}{}{}{Hang}

\@tracklang@add@kurdish Script varies according to region.
\TrackLangDeclareLanguageOption{kurdish}{ku}{kur}{}{}{}

\@tracklang@add@kwanyama
\TrackLangDeclareLanguageOption{kwanyama}{kj}{kua}{}{}{Latn}

\@tracklang@add@kyrgyz
\TrackLangDeclareLanguageOption{kyrgyz}{ky}{kir}{}{}{Cyr1}

\@tracklang@add@lao
\TrackLangDeclareLanguageOption{lao}{lo}{lao}{}{}{Lao}

\@tracklang@add@latin
\TrackLangDeclareLanguageOption{latin}{la}{lat}{}{}{Latn}

\@tracklang@add@latvian
\TrackLangDeclareLanguageOption{latvian}{lv}{lav}{}{}{Latn}

\@tracklang@add@limburgish
\TrackLangDeclareLanguageOption{limburgish}{li}{lim}{}{}{Latn}

\@tracklang@add@lingala
\TrackLangDeclareLanguageOption{lingala}{ln}{lin}{}{}{Latn}

\@tracklang@add@lithuanian
\TrackLangDeclareLanguageOption{lithuanian}{lt}{lit}{}{}{Latn}

\@tracklang@add@lsorbian
\TrackLangDeclareLanguageOption{lsorbian}{}{dsb}{}{}{DE}{Latn}

\@tracklang@add@lubakatanga
\TrackLangDeclareLanguageOption{lubakatanga}{lu}{lub}{}{}{CD}{Latn}

\@tracklang@add@luxembourgish
\TrackLangDeclareLanguageOption{luxembourgish}{lb}{ltz}{}{}{Latn}

\@tracklang@add@macedonian
\TrackLangDeclareLanguageOption{macedonian}{mk}{mkd}{mac}{}{}{Cyr1}

\@tracklang@add@magyar
\TrackLangDeclareLanguageOption{magyar}{hu}{hun}{}{}{Latn}

```

```

\@tracklang@add@malagasy
    \TrackLangDeclareLanguageOption{malagasy}{mg}{mlg}{-}{-}{-}{Latn}

\@tracklang@add@malayalam
    \TrackLangDeclareLanguageOption{malayalam}{ml}{mal}{-}{-}{IN}{Mlym}

\@tracklang@add@maltese
    \TrackLangDeclareLanguageOption{maltese}{mt}{mlt}{-}{-}{-}{Latn}

\@tracklang@add@manx
    \TrackLangDeclareLanguageOption{manx}{gv}{glv}{-}{-}{IM}{Latn}

\@tracklang@add@maori
    \TrackLangDeclareLanguageOption{maori}{mi}{mri}{mao}{-}{NZ}{Latn}

\@tracklang@add@marathi
    \TrackLangDeclareLanguageOption{marathi}{mr}{mar}{-}{-}{IN}{Deva}

\@tracklang@add@marshallese
    \TrackLangDeclareLanguageOption{marshallese}{mh}{mah}{-}{-}{MH}{Latn}

\@tracklang@add@mongolian
    \TrackLangDeclareLanguageOption{mongolian}{mn}{mon}{-}{-}{-}{Mong}

\@tracklang@add@nauruan
    \TrackLangDeclareLanguageOption{nauruan}{na}{nau}{-}{-}{NR}{Latn}

\@tracklang@add@navajo
    \TrackLangDeclareLanguageOption{navajo}{nv}{nav}{-}{-}{US}{Latn}

\@tracklang@add@ndonga
    \TrackLangDeclareLanguageOption{ndonga}{ng}{ndo}{-}{-}{-}{Latn}

\@tracklang@add@nepali
    \TrackLangDeclareLanguageOption{nepali}{ne}{nep}{-}{-}{-}{Deva}

\@tracklang@add@nko
    \TrackLangDeclareLanguageOption{nko}{-}{nqo}{-}{-}{-}{Nkoo}

\@tracklang@add@northernndebele
    \TrackLangDeclareLanguageOption{northernndebele}{nd}{nde}{-}{-}{-}{Latn}

\@tracklang@add@nynorsk
    \TrackLangDeclareLanguageOption{nynorsk}{nn}{nno}{-}{-}{NO}{Latn}

\@tracklang@add@norsk
    \TrackLangDeclareLanguageOption{norsk}{no}{nor}{-}{-}{-}{Latn}

```



```

\@tracklang@add@northernsotho
\TrackLangDeclareLanguageOption{northernsotho}{nso}{}{}{Latn}

\@tracklang@add@nuosu
\TrackLangDeclareLanguageOption{nuosu}{ii}{iii}{}{}{CN}{Yiii}

\@tracklang@add@occitan
\TrackLangDeclareLanguageOption{occitan}{oc}{oci}{}{}{Latn}

\@tracklang@add@ojibwe
\TrackLangDeclareLanguageOption{ojibwe}{oj}{oji}{}{}{Latn}

\@tracklang@add@oromo
\TrackLangDeclareLanguageOption{oromo}{om}{orm}{}{}{Latn}

\@tracklang@add@oriya
\TrackLangDeclareLanguageOption{oriya}{or}{ori}{}{}{Orya}

\@tracklang@add@ossetian
\TrackLangDeclareLanguageOption{ossetian}{os}{oss}{}{}{Cyr1}

\@tracklang@add@pali
\TrackLangDeclareLanguageOption{pali}{pi}{pli}{}{}{Brah}

\@tracklang@add@pashto
\TrackLangDeclareLanguageOption{pashto}{ps}{pus}{}{}{Arab}

\@tracklang@add@piedmontese
\TrackLangDeclareLanguageOption{piedmontese}{}{}{pms}{IT}{Latn}

\@tracklang@add@polish
\TrackLangDeclareLanguageOption{polish}{pl}{pol}{}{}{Latn}

\@tracklang@add@portuges
\TrackLangDeclareLanguageOption{portuges}{pt}{por}{}{}{Latn}

\@tracklang@add@quechua
\TrackLangDeclareLanguageOption{quechua}{qu}{que}{}{}{Latn}

\@tracklang@add@romanian
\TrackLangDeclareLanguageOption{romanian}{ro}{ron}{rum}{}{}{Latn}

\@tracklang@add@romansh
\TrackLangDeclareLanguageOption{romansh}{rm}{roh}{}{}{CH}{Latn}

\@tracklang@add@russian
\TrackLangDeclareLanguageOption{russian}{ru}{rus}{}{}{Cyr1}

```

\@tracklang@add@samin  
\TrackLangDeclareLanguageOption{samin}{se}{sme}{}{}{}{Latn}

\@tracklang@add@sanskrit  
\TrackLangDeclareLanguageOption{sanskrit}{sa}{san}{}{}{}{}

\@tracklang@add@samoan  
\TrackLangDeclareLanguageOption{samoan}{sm}{smo}{}{}{}{Latn}

\@tracklang@add@sango  
\TrackLangDeclareLanguageOption{sango}{sg}{sag}{}{}{}{Latn}

\@tracklang@add@sardinian  
\TrackLangDeclareLanguageOption{sardinian}{sc}{srd}{}{}{}{IT}{Latn}

\@tracklang@add@scots Scots. Also spoken in Northern Ireland, so no region. There's no ISO 639-1 language code for this language.  
\TrackLangDeclareLanguageOption{scots}{}{sco}{}{}{}{Latn}

\@tracklang@add@scottish Scottish Gaelic. Also spoken in Canada, so no region.  
\TrackLangDeclareLanguageOption{scottish}{gd}{gla}{}{}{}{Latn}

\@tracklang@add@serbian  
\TrackLangDeclareLanguageOption{serbian}{sr}{srp}{}{}{}{Cyr1}

\@tracklang@add@shona  
\TrackLangDeclareLanguageOption{shona}{sn}{sna}{}{}{}{Latn}

\@tracklang@add@sindhi  
\TrackLangDeclareLanguageOption{sindhi}{sd}{snd}{}{}{}{Sind}

\@tracklang@add@sinhalese  
\TrackLangDeclareLanguageOption{sinhalese}{si}{sin}{}{}{}{LK}{Sinh}

\@tracklang@add@slovak  
\TrackLangDeclareLanguageOption{slovak}{sk}{slk}{slo}{}{}{Latn}

\@tracklang@add@slovene  
\TrackLangDeclareLanguageOption{slovene}{sl}{slv}{}{}{}{Latn}

\@tracklang@add@somali  
\TrackLangDeclareLanguageOption{somali}{so}{som}{}{}{}{Latn}

\@tracklang@add@southernndebele  
\TrackLangDeclareLanguageOption{southernndebele}{nr}{nbl}{}{}{}{ZA}{Latn}

\@tracklang@add@southernsotho  
\TrackLangDeclareLanguageOption{southernsotho}{st}{sot}{}{}{}{Latn}

```

\@tracklang@add@spanish
    \TrackLangDeclareLanguageOption{spanish}{es}{spa}{}{}{Latn}
\@tracklang@add@sudanese
    \TrackLangDeclareLanguageOption{sudanese}{su}{sun}{}{}{Sund}
\@tracklang@add@swahili
    \TrackLangDeclareLanguageOption{swahili}{sw}{swa}{}{}{}
    \@tracklang@add@swati
    \TrackLangDeclareLanguageOption{swati}{ss}{ssw}{}{}{Latn}
\@tracklang@add@swedish
    \TrackLangDeclareLanguageOption{swedish}{sv}{swe}{}{}{Latn}
\@tracklang@add@syriac
    \TrackLangDeclareLanguageOption{syriac}{}{syr}{}{}{Syrn}
\@tracklang@add@tagalog
    \TrackLangDeclareLanguageOption{tagalog}{tl}{tgl}{}{}{PH}{Latn}
\@tracklang@add@tahitian
    \TrackLangDeclareLanguageOption{tahitian}{ty}{tah}{}{}{PF}{Latn}
    \@tracklang@add@tai
    \TrackLangDeclareLanguageOption{tai}{}{tai}{}{}{}
\@tracklang@add@tajik
    \TrackLangDeclareLanguageOption{tajik}{tg}{tgk}{}{}{Cyr1}
\@tracklang@add@tamil
    \TrackLangDeclareLanguageOption{tamil}{ta}{tam}{}{}{Taml}
\@tracklang@add@tatar
    \TrackLangDeclareLanguageOption{tatar}{tt}{tat}{}{}{Cyr1}
\@tracklang@add@telugu
    \TrackLangDeclareLanguageOption{telugu}{te}{tel}{}{}{IN}{Telu}
    \@tracklang@add@thai
    \TrackLangDeclareLanguageOption{thai}{th}{tha}{}{}{TH}{Thai}
\@tracklang@add@tibetan
    \TrackLangDeclareLanguageOption{tibetan}{bo}{bod}{tib}{}{}{Tibt}
\@tracklang@add@tigrinya
    \TrackLangDeclareLanguageOption{tigrinya}{ti}{tir}{}{}{Ethi}

```

```

\@tracklang@add@tonga
\TrackLangDeclareLanguageOption{tonga}{to}{ton}{}{}{T0}{Latn}

\@tracklang@add@tsonga
\TrackLangDeclareLanguageOption{tsonga}{ts}{tso}{}{}{Latn}

\@tracklang@add@tswana
\TrackLangDeclareLanguageOption{tswana}{tn}{tsn}{}{}{Latn}

\@tracklang@add@turkish
\TrackLangDeclareLanguageOption{turkish}{tr}{tur}{}{}{Latn}

\@tracklang@add@turkmen
\TrackLangDeclareLanguageOption{turkmen}{tk}{tuk}{}{}{Latn}

\@tracklang@add@twi
\TrackLangDeclareLanguageOption{twi}{tw}{twi}{}{}{GH}{Latn}

\@tracklang@add@ukrainian
\TrackLangDeclareLanguageOption{ukrainian}{uk}{ukr}{}{}{UA}{Cyr1}

\@tracklang@add@undetermined Undetermined language (ISO 636-2 code 'und') for unknown languages. There's
no ISO 639-1 language code for this language.
\TrackLangDeclareLanguageOption{undetermined}{}{und}{}{}{Latn}

\@tracklang@add@urdu
\TrackLangDeclareLanguageOption{urdu}{ur}{urd}{}{}{Arab}

\@tracklang@add@usorbian
\TrackLangDeclareLanguageOption{usorbian}{}{hsb}{}{}{DE}{Latn}

\@tracklang@add@uyghur
\TrackLangDeclareLanguageOption{uyghur}{ug}{uig}{}{}{CN}{Arab}

\@tracklang@add@uzbek
\TrackLangDeclareLanguageOption{uzbek}{uz}{uzb}{}{}{Latn}

\@tracklang@add@venda
\TrackLangDeclareLanguageOption{venda}{ve}{ven}{}{}{ZA}{Latn}

\@tracklang@add@vietnamese
\TrackLangDeclareLanguageOption{vietnamese}{vi}{vie}{}{}{Latn}

\@tracklang@add@volapuk
\TrackLangDeclareLanguageOption{volapuk}{vo}{vol}{}{}{Latn}

```

`\@tracklang@add@walloon` No country code as Walloon is spoken in multiple regions (Wallonia in Belgium, some villages in Northern France and north-east of Wisconsin.) Not the same as Belgian French.

```
\TrackLangDeclareLanguageOption{walloon}{wa}{wln}{}{}{Latn}
```

`\@tracklang@add@welsh` Also spoken in Argentina, so no region.

```
\TrackLangDeclareLanguageOption{welsh}{cy}{cym}{wel}{}{}{Latn}
```

`\@tracklang@add@westernfrisian`

```
\TrackLangDeclareLanguageOption{westernfrisian}{fy}{fry}{}{}{NL}{Latn}
```

`\@tracklang@add@wolof`

```
\TrackLangDeclareLanguageOption{wolof}{wo}{wol}{}{}{Latn}
```

`\@tracklang@add@xhosa`

```
\TrackLangDeclareLanguageOption{xhosa}{xh}{xho}{}{}{Latn}
```

`\@tracklang@add@yiddish`

```
\TrackLangDeclareLanguageOption{yiddish}{yi}{yid}{}{}{Hebr}
```

`\@tracklang@add@yoruba`

```
\TrackLangDeclareLanguageOption{yoruba}{yo}{yor}{}{}{Latn}
```

`\@tracklang@add@zhuang`

```
\TrackLangDeclareLanguageOption{zhuang}{za}{zha}{}{}{CN}{Hani}
```

`\@tracklang@add@zulu`

```
\TrackLangDeclareLanguageOption{zulu}{zu}{zul}{}{}{Latn}
```

## 4.6 Predefined Dialects

Provide some predefined dialects.

```
\TrackLangProvidePredefinedDialect{<dialect>}{<root
language>}{<3166-1
code>}{<modifier>}{<variant>}{<map>}{<script>}
```

`\TrackLangProvidePredefinedDialect`

This defines a predefined dialect label that can be used by `\TrackPredefinedDialect`. The arguments must be expanded before use. The final argument `<map>` is the mapping from `<dialect>` to the closest babel dialect label.

```
\def\TrackLangProvidePredefinedDialect#1#2#3#4#5#6#7{
\ifx\relax#3\relax
```

No region.

```
\ifx\relax#4\relax
```

No modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%
```

Make it easier for the parser to pick up the dialect label. Note that this should be the same as `\TrackLangLastTrackedDialect` but the parser references `\@tracklang@dialect`.

```
\def\@tracklang@dialect{#1}%  
}%  
\else
```

Has variant but no modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\else
```

Has modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant and modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\fi  
\else
```

Has a region.

```
\ifx\relax#4\relax
```

No modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant no modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\else
```

Has modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant and modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\fi  
\fi
```

Add the mapping if provided.

```
\ifx\relax#6\relax  
\else
```

```

\expandafter
\let\expandafter\@tracklang@tmp\csname @tracklang@add@#1\endcsname
\expandafter\def\csname @tracklang@add@#1\expandafter\endcsname

\expandafter{\@tracklang@tmp\SetTrackedDialectLabelMap{#1}{#6}}%
\fi

```

Add the script if provided.

```

\ifx\relax#7\relax
\else
\expandafter
\let\expandafter\@tracklang@tmp\csname @tracklang@add@#1\endcsname
\expandafter\def\csname @tracklang@add@#1\expandafter\endcsname
\expandafter{\@tracklang@tmp\SetTrackedDialectScript{#1}{#7}}%
\fi
}

```

```

\TrackLangDeclareDialectOption{<dialect>}{<root
language>}{<3166-1
code>}{<modifier>}{<variant>}{<map>}{<script>}

```

`\TrackLangDeclareDialectOption`

The option name is the same as the dialect name. The arguments must be expanded before use. The final argument `<map>` is the mapping from `<dialect>` to the closest babel dialect label. May be empty if no relevant mapping.

```

\def\TrackLangDeclareDialectOption#1#2#3#4#5#6#7{%
\@tracklang@ifundef{\@tracklang@add@#1}%
{%
\TrackLangProvidePredefinedDialect{#1}{#2}{#3}{#4}{#5}{#6}{#7}%
\@tracklang@declareoption{#1}%
}%
{%
\@tracklang@err{dialect option ‘#1’ has already been defined}{}%
}%
}

```

`\@tracklang@add@acadian`

```
\TrackLangDeclareDialectOption{acadian}{french}{}{}{}{}{}
```

`\@tracklang@add@american`

```
\TrackLangDeclareDialectOption{american}{english}{US}{}{}{}{}
```

`\@tracklang@add@australian`

```
\TrackLangDeclareDialectOption{australian}{english}{AU}{}{}{}{}
```

`\@tracklang@add@austrian`

```
\TrackLangDeclareDialectOption{austrian}{german}{AT}{}{}{}{}
```



```

\@tracklang@add@naustrian
    \TrackLangDeclareDialectOption{naustrian}{german}{AT}{new}{1996}{}{}

\@tracklang@add@bahasa
    \TrackLangDeclareDialectOption{bahasa}{bahasai}{IN}{}{}{}

\@tracklang@add@brazil
    \TrackLangDeclareDialectOption{brazil}{portuges}{BR}{}{}{}

\@tracklang@add@brazilian
    \TrackLangDeclareDialectOption{brazilian}{portuges}{BR}{}{}{}

\@tracklang@add@british
    \TrackLangDeclareDialectOption{british}{english}{GB}{}{}{}

\@tracklang@add@canadian
    \TrackLangDeclareDialectOption{canadian}{english}{CA}{}{}{}

\@tracklang@add@canadien
    \TrackLangDeclareDialectOption{canadien}{french}{CA}{}{}{}

\@tracklang@add@croatia
    \TrackLangDeclareDialectOption{croatia}{croatian}{HR}{}{}{}

ng@add@istriacountycroatian
    \TrackLangDeclareDialectOption{istriacountycroatian}{croatian}{HR}{}{}{}

ang@add@istriacountyitalian
    \TrackLangDeclareDialectOption{istriacountyitalian}{italian}{HR}{}{}{}

\@tracklang@add@netherlands
    \TrackLangDeclareDialectOption{netherlands}{dutch}{NL}{}{}{}

\@tracklang@add@persian
    \TrackLangDeclareDialectOption{persian}{farsi}{}{}{}

\@tracklang@add@flemish
    \TrackLangDeclareDialectOption{flemish}{dutch}{BE}{}{}{}

\@tracklang@add@français
    \TrackLangDeclareDialectOption{français}{french}{}{}{}

\@tracklang@add@frenchb
    \TrackLangDeclareDialectOption{frenchb}{french}{}{}{}

\@tracklang@add@france
    \TrackLangDeclareDialectOption{france}{french}{FR}{}{}{}

```

```

\@tracklang@add@belgique
\TrackLangDeclareDialectOption{belgique}{french}{BE}{}{}{}

\@tracklang@add@belgiangerman
\TrackLangDeclareDialectOption{belgiangerman}{german}{BE}{}{}{}

\@tracklang@add@nbelgiangerman
\TrackLangDeclareDialectOption{nbelgiangerman}{german}{BE}{new}{1996}{ngerman}{}

\@tracklang@add@friulian
\TrackLangDeclareDialectOption{friulian}{friulan}{IT}{}{}{}

\@tracklang@add@friulano
\TrackLangDeclareDialectOption{friulano}{friulan}{IT}{}{}{}

\@tracklang@add@furlan Added since it's a babel alias for friulan.
\TrackLangDeclareDialectOption{furlan}{friulan}{IT}{}{}{}

\@tracklang@add@kurmanji Added since it's a babel label.
\TrackLangDeclareDialectOption{kurmanji}{kurdish}{}{}{}{}

\@tracklang@add@galicien
\TrackLangDeclareDialectOption{galicien}{galician}{}{}{}{}

\@tracklang@add@deutsch
\TrackLangDeclareDialectOption{deutsch}{german}{}{}{}{}

\@tracklang@add@ngerman
\TrackLangDeclareDialectOption{ngerman}{german}{}{new}{1996}{}{}

\@tracklang@add@ngermanb
\TrackLangDeclareDialectOption{ngermanb}{german}{}{new}{1996}{ngerman}{}

\@tracklang@add@germanb
\TrackLangDeclareDialectOption{germanb}{german}{}{}{}{}

\@tracklang@add@ngermanDE
\TrackLangDeclareDialectOption{ngermanDE}{german}{DE}{new}{1996}{ngerman}{}

\@tracklang@add@germanDE
\TrackLangDeclareDialectOption{germanDE}{german}{DE}{}{}{}{}

\@tracklang@add@hungarian
\TrackLangDeclareDialectOption{hungarian}{magyar}{HU}{}{}{}{}

\@tracklang@add@indon
\TrackLangDeclareDialectOption{indon}{bahasai}{IN}{}{}{}{}

```

```

\@tracklang@add@indonesian
    \TrackLangDeclareDialectOption{indonesian}{bahasai}{IN}{}{}{}{}

\@tracklang@add@gaeilge
    \TrackLangDeclareDialectOption{gaeilge}{irish}{}{}{}{}{}

\@tracklang@add@IEirish Irish spoken in Republic of Ireland
    \TrackLangDeclareDialectOption{IEirish}{irish}{IE}{}{}{}{}

\@tracklang@add@GBirish Irish spoken in the United Kingdom of Great Britain and Northern Ireland
    \TrackLangDeclareDialectOption{GBirish}{irish}{GB}{}{}{}{}

\@tracklang@add@IEenglish English spoken in the Republic of Ireland.
    \TrackLangDeclareDialectOption{IEenglish}{english}{IE}{}{}{british}{}

    \@tracklang@add@italy
    \TrackLangDeclareDialectOption{italy}{italian}{IT}{}{}{}{}

    \@tracklang@add@vatican
    \TrackLangDeclareDialectOption{vatican}{italian}{VA}{}{}{}{}

\@tracklang@add@sanmarino
    \TrackLangDeclareDialectOption{sanmarino}{italian}{SM}{}{}{}{}

ng@add@sloveneistriaitalian
    \TrackLangDeclareDialectOption{sloveneistriaitalian}{italian}{SI}{}{}{}{}

tracklang@add@jerseyenglish Allow it to hook to pick up \captionsbritish as well as \captionseenglish
since the date format closely matches british.
    \TrackLangDeclareDialectOption{jerseyenglish}{english}{JE}{}{}{british}{}

\@tracklang@add@jerseyfrench
    \TrackLangDeclareDialectOption{jerseyfrench}{french}{JE}{}{}{}{}

tracklang@add@guernseyenglish Allow it to hook to pick up \captionsbritish as well as \captionseenglish
since the date format closely matches british.
    \TrackLangDeclareDialectOption{guernseyenglish}{english}{GG}{}{}{british}{}

tracklang@add@guernseyfrench
    \TrackLangDeclareDialectOption{guernseyfrench}{french}{GG}{}{}{}{}

    \@tracklang@add@latein
    \TrackLangDeclareDialectOption{latein}{latin}{}{}{}{}{}

\@tracklang@add@lowersorbian
    \TrackLangDeclareDialectOption{lowersorbian}{lsorbian}{DE}{}{}{}{}

```

```

\@tracklang@add@malay
\TrackLangDeclareDialectOption{malay}{bahasam}{MY}{}{}{}

\@tracklang@add@meyalu
\TrackLangDeclareDialectOption{meyalu}{bahasam}{MY}{}{}{}

\@tracklang@add@maltamaltese
\TrackLangDeclareDialectOption{maltamaltese}{maltese}{MT}{}{}{}

\@tracklang@add@maltaenglish Allow it to hook to pick up \captionsbritish as well as \captionsenglish
since the date format closely matches british.
\TrackLangDeclareDialectOption{maltaenglish}{english}{MT}{}{}{british}{}

\@tracklang@add@newzealand
\TrackLangDeclareDialectOption{newzealand}{english}{NZ}{}{}{}

\@tracklang@add@isleofmanenglish Allow it to hook to pick up \captionsbritish as well as \captionsenglish
since the date format closely matches british.
\TrackLangDeclareDialectOption{isleofmanenglish}{english}{IM}{}{}{british}{}

\@tracklang@add@norwegian
\TrackLangDeclareDialectOption{norwegian}{norsk}{NO}{}{}{}

\@tracklang@add@piemonteis
\TrackLangDeclareDialectOption{piemonteis}{piedmontese}{IT}{}{}{}

\@tracklang@add@polutonikogreek
\TrackLangDeclareDialectOption{polutonikogreek}{greek}{}{polyton}{}{}{}

\@tracklang@add@polutoniko
\TrackLangDeclareDialectOption{polutoniko}{greek}{}{polyton}{}{}{}

\@tracklang@add@portuguese
\TrackLangDeclareDialectOption{portuguese}{portuges}{}{}{}{}

\@tracklang@add@portugal
\TrackLangDeclareDialectOption{portugal}{portuges}{PT}{}{}{}

\@tracklang@add@romansch
\TrackLangDeclareDialectOption{romansch}{romansh}{}{}{}{}

\@tracklang@add@rumantsch
\TrackLangDeclareDialectOption{rumantsch}{romansh}{}{}{}{}

\@tracklang@add@romanche
\TrackLangDeclareDialectOption{romanche}{romansh}{}{}{}{}

```

```

\@tracklang@add@russianb
    \TrackLangDeclareDialectOption{russianb}{russian}{}{}{}{}
\@tracklang@add@gaelic Scottish Gaelic. Note that this is not the same as Scots.
    \TrackLangDeclareDialectOption{gaelic}{scottish}{}{}{}{}
\@tracklang@add@GBscottish
    \TrackLangDeclareDialectOption{GBscottish}{scottish}{GB}{}{}{}{}
\@tracklang@add@serbianc
    \TrackLangDeclareDialectOption{serbianc}{serbian}{}{}{}{}{Cyril}
\@tracklang@add@serbianl
    \TrackLangDeclareDialectOption{serbianl}{serbian}{}{}{}{}{}{Latn}
\@tracklang@add@slovenian
    \TrackLangDeclareDialectOption{slovenian}{slovene}{}{}{}{}{}{}
\@tracklang@add@slovenia
    \TrackLangDeclareDialectOption{slovenia}{slovene}{SI}{}{}{}{}{slovenian}{}
\@tracklang@add@sloveneistriasslovenian
    \TrackLangDeclareDialectOption{sloveneistriasslovenian}{slovene}{SI}{}{}{}{}{slovenian}{}
\@tracklang@add@spainspanish
    \TrackLangDeclareDialectOption{spainspanish}{spanish}{ES}{}{}{}{}{}
\@tracklang@add@argentinespanish
    \TrackLangDeclareDialectOption{argentinespanish}{spanish}{AR}{}{}{}{}{}
\@tracklang@add@bolivianspanish
    \TrackLangDeclareDialectOption{bolivianspanish}{spanish}{BO}{}{}{}{}{}
\@tracklang@add@chilianspanish
    \TrackLangDeclareDialectOption{chilianspanish}{spanish}{CL}{}{}{}{}{}
\@tracklang@add@columbianspanish
    \TrackLangDeclareDialectOption{columbianspanish}{spanish}{CO}{}{}{}{}{}
\@tracklang@add@costaricanspanish
    \TrackLangDeclareDialectOption{costaricanspanish}{spanish}{CR}{}{}{}{}{}
\@tracklang@add@cubanspanish
    \TrackLangDeclareDialectOption{cubanspanish}{spanish}{CU}{}{}{}{}{}
\@tracklang@add@dominicanspanish
    \TrackLangDeclareDialectOption{dominicanspanish}{spanish}{DO}{}{}{}{}{}

```

\tracklang@add@ecudorianspanish  
 \TrackLangDeclareDialectOption{ecudorianspanish}{spanish}{EC}{}{}{}

\tracklang@add@elsalvadorspanish  
 \TrackLangDeclareDialectOption{elsalvadorspanish}{spanish}{SV}{}{}{}

\tracklang@add@guatemalanspanish  
 \TrackLangDeclareDialectOption{guatemalanspanish}{spanish}{GT}{}{}{}

\tracklang@add@honduranspanish  
 \TrackLangDeclareDialectOption{honduranspanish}{spanish}{HN}{}{}{}

\tracklang@add@mexicanspanish  
 \TrackLangDeclareDialectOption{mexicanspanish}{spanish}{MX}{}{}{}

\tracklang@add@nicaraguanspanish  
 \TrackLangDeclareDialectOption{nicaraguanspanish}{spanish}{NI}{}{}{}

\tracklang@add@panamaspanish  
 \TrackLangDeclareDialectOption{panamaspanish}{spanish}{PA}{}{}{}

\tracklang@add@paraguayspanish  
 \TrackLangDeclareDialectOption{paraguayspanish}{spanish}{PY}{}{}{}

\tracklang@add@peruvianspanish  
 \TrackLangDeclareDialectOption{peruvianspanish}{spanish}{PE}{}{}{}

\tracklang@add@puertoricospansish  
 \TrackLangDeclareDialectOption{puertoricospansish}{spanish}{PR}{}{}{}

\tracklang@add@uruguayspanish  
 \TrackLangDeclareDialectOption{uruguayspanish}{spanish}{UY}{}{}{}

\tracklang@add@venezuelanspanish  
 \TrackLangDeclareDialectOption{venezuelanspanish}{spanish}{VE}{}{}{}

\@tracklang@add@swissgerman  
 \TrackLangDeclareDialectOption{swissgerman}{german}{CH}{}{}{}

\@tracklang@add@nswissgerman  
 \TrackLangDeclareDialectOption{nswissgerman}{german}{CH}{new}{1996}{ngerman}{}

\@tracklang@add@swissfrench  
 \TrackLangDeclareDialectOption{swissfrench}{french}{CH}{}{}{}

\@tracklang@add@swissitalian  
 \TrackLangDeclareDialectOption{swissitalian}{italian}{CH}{}{}{}

```

@tracklang@add@swissromansh
    \TrackLangDeclareDialectOption{swissromansh}{romansh}{CH}{}{}{}
\@tracklang@add@UKenglish
    \TrackLangDeclareDialectOption{UKenglish}{english}{GB}{}{}{}
\@tracklang@add@ukraineb
    \TrackLangDeclareDialectOption{ukraineb}{ukrainian}{UA}{}{}{}
\@tracklang@add@ukraine
    \TrackLangDeclareDialectOption{ukraine}{ukrainian}{UA}{}{}{}
@tracklang@add@uppersorbian
    \TrackLangDeclareDialectOption{uppersorbian}{usorbian}{DE}{}{}{}
\@tracklang@add@USenglish
    \TrackLangDeclareDialectOption{USenglish}{english}{US}{}{}{}
\@tracklang@add@valencian
    \TrackLangDeclareDialectOption{valencian}{catalan}{}{}{}{}
\@tracklang@add@valencien
    \TrackLangDeclareDialectOption{valencien}{catalan}{}{}{}{}
\@tracklang@add@cymraeg
    \TrackLangDeclareDialectOption{cymraeg}{welsh}{}{}{}{}
\@tracklang@add@GBwelsh
    \TrackLangDeclareDialectOption{GBwelsh}{welsh}{GB}{}{}{}
\@tracklang@add@nil Add babel's nil as a dialect of undetermined language.
    \TrackLangDeclareDialectOption{nil}{undetermined}{}{}{}{}

```

## 4.7 Dialect Option Synonyms

Add some dialect synonyms:

```

\LetTrackLangSynonym
    \def\LetTrackLangSynonym#1#2{%
        \expandafter\let\csname @tracklang@add@#1\expandafter\endcsname
            \csname @tracklang@add@#2\endcsname
    }

\LetTrackLangOption
    \def\LetTrackLangOption#1#2{%
        \LetTrackLangSynonym{#1}{#2}%
        \@tracklang@declareoption{#1}%
    }

```

\@tracklang@add@en-US  
\LetTrackLangOption{en-US}{american}

\@tracklang@add@en-GB  
\LetTrackLangOption{en-GB}{british}

\@tracklang@add@en-AU  
\LetTrackLangOption{en-AU}{australian}

\@tracklang@add@en-NZ  
\LetTrackLangOption{en-NZ}{newzealand}

\@tracklang@add@en-CA  
\LetTrackLangOption{en-CA}{canadian}

\@tracklang@add@fr-CA  
\LetTrackLangOption{fr-CA}{canadien}

\@tracklang@add@fr-BE  
\LetTrackLangOption{fr-BE}{belgique}

\@tracklang@add@pt-BR  
\LetTrackLangOption{pt-BR}{brazilian}

\@tracklang@add@it-HR  
\LetTrackLangOption{it-HR}{istriacountyitalian}

\@tracklang@add@nl-BE  
\LetTrackLangOption{nl-BE}{flemish}

\@tracklang@add@fr-FR  
\LetTrackLangOption{fr-FR}{france}

\@tracklang@add@de-DE  
\LetTrackLangOption{de-DE}{germanDE}

\@tracklang@add@de-BE  
\LetTrackLangOption{de-BE}{belgiangerman}

\@tracklang@add@en-GG  
\LetTrackLangOption{en-GG}{guernseyenglish}

\@tracklang@add@fr-GG  
\LetTrackLangOption{fr-GG}{guernseyfrench}

\@tracklang@add@it-IT  
\LetTrackLangOption{it-IT}{italy}



\@tracklang@add@mt-MT  
\LetTrackLangOption{mt-MT}{maltamaltese}

\@tracklang@add@en-MT  
\LetTrackLangOption{en-MT}{maltaenglish}

\@tracklang@add@en-IM  
\LetTrackLangOption{en-IM}{isleofmanenglish}

\@tracklang@add@en-JE  
\LetTrackLangOption{en-JE}{jerseyenglish}

\@tracklang@add@fr-JE  
\LetTrackLangOption{fr-JE}{jerseyfrench}

\@tracklang@add@nl-NL  
\LetTrackLangOption{nl-NL}{netherlands}

\@tracklang@add@pt-PT  
\LetTrackLangOption{pt-PT}{portugal}

\@tracklang@add@it-SM  
\LetTrackLangOption{it-SM}{sanmarino}

\@tracklang@add@sl-SI  
\LetTrackLangOption{sl-SI}{slovenia}

\@tracklang@add@it-SI  
\LetTrackLangOption{it-SI}{sloveneistriaitalian}

\@tracklang@add@es-ES  
\LetTrackLangOption{es-ES}{spainspanish}

\@tracklang@add@es-AR  
\LetTrackLangOption{es-AR}{argentinespanish}

\@tracklang@add@es-BO  
\LetTrackLangOption{es-BO}{bolivianspanish}

\@tracklang@add@es-CL  
\LetTrackLangOption{es-CL}{chilianspanish}

\@tracklang@add@es-CO  
\LetTrackLangOption{es-CO}{columbianspanish}

\@tracklang@add@es-CR  
\LetTrackLangOption{es-CR}{costaricanspanish}

\@tracklang@add@es-CU  
\LetTrackLangOption{es-CU}{cubanspanish}

\@tracklang@add@es-DO  
\LetTrackLangOption{es-DO}{dominicanspanish}

\@tracklang@add@es-EC  
\LetTrackLangOption{es-EC}{ecudorianspanish}

\@tracklang@add@es-SV  
\LetTrackLangOption{es-SV}{elsalvadorspanish}

\@tracklang@add@es-GT  
\LetTrackLangOption{es-GT}{guatemalanspanish}

\@tracklang@add@es-HN  
\LetTrackLangOption{es-HN}{honduranspanish}

\@tracklang@add@es-MX  
\LetTrackLangOption{es-MX}{mexicanspanish}

\@tracklang@add@es-NI  
\LetTrackLangOption{es-NI}{nicaraguanspanish}

\@tracklang@add@es-PA  
\LetTrackLangOption{es-PA}{panamaspanish}

\@tracklang@add@es-PY  
\LetTrackLangOption{es-PY}{paraguayspanish}

\@tracklang@add@es-PE  
\LetTrackLangOption{es-PE}{peruvianspanish}

\@tracklang@add@es-PR  
\LetTrackLangOption{es-PR}{puertoricospanish}

\@tracklang@add@es-UY  
\LetTrackLangOption{es-UY}{uruguayspanish}

\@tracklang@add@es-VE  
\LetTrackLangOption{es-VE}{venezuelanspanish}

\@tracklang@add@de-CH  
\LetTrackLangOption{de-CH}{swissgerman}

\@tracklang@add@fr-CH  
\LetTrackLangOption{fr-CH}{swissfrench}

\@tracklang@add@it-CH  
\LetTrackLangOption{it-CH}{swissitalian}

\@tracklang@add@rm-CH  
\LetTrackLangOption{rm-CH}{swissromansh}

\@tracklang@add@it-VA  
\LetTrackLangOption{it-VA}{vatican}

\@tracklang@add@ga-IE Irish Gaelic in Republic of Ireland.  
\LetTrackLangOption{ga-IE}{IEirish}

\@tracklang@add@ga-GB Irish Gaelic in Northern Ireland.  
\LetTrackLangOption{ga-GB}{GBirish}

\@tracklang@add@en-IE English spoken in Republic of Ireland.  
\LetTrackLangOption{en-IE}{IEenglish}

\@tracklang@add@de-AT-1996  
\LetTrackLangOption{de-AT-1996}{naustrian}

\@tracklang@add@de-AT  
\LetTrackLangOption{de-AT}{austrian}

\@tracklang@add@id-IN  
\LetTrackLangOption{id-IN}{bahasa}

\@tracklang@add@ms-MY  
\LetTrackLangOption{ms-MY}{malay}

\@tracklang@add@hr-HR  
\LetTrackLangOption{hr-HR}{croatia}

\@tracklang@add@de-DE-1996  
\LetTrackLangOption{de-DE-1996}{ngermanDE}

\@tracklang@add@de-CH-1996  
\LetTrackLangOption{de-CH-1996}{nswissgerman}

\@tracklang@add@hu-HU  
\LetTrackLangOption{hu-HU}{hungarian}

\@tracklang@add@gd-GB  
\LetTrackLangOption{gd-GB}{GBscottish}

\@tracklang@add@cy-GB  
\LetTrackLangOption{cy-GB}{GBwelsh}

## 4.8 Conditionals and Loops

```
\IfTrackedLanguage{<language>}{<true part>}{<>false part>}
```

\IfTrackedLanguage

```
\long\def\IfTrackedLanguage#1#2#3{%
First find out if the language name is empty.
  \edef\@tracklang@element{#1}%
  \ifx\@tracklang@element\empty
Language is empty, so do false part.
    #3%
  \else
    \expandafter\@tracklang@ifinlist\expandafter{\@tracklang@element}%
    \@tracklang@languages
    {%
In list, so do true part.
      #2%
    }%
    {%
Not in list, so do false part.
      #3%
    }%
  \fi
}
```

```
\IfTrackedDialect{<dialect>}{<true part>}{<>false part>}
```

\IfTrackedDialect

```
\long\def\IfTrackedDialect#1#2#3{%
  \@tracklang@ifundef{\@tracklang@fromdialect@#1}{#3}{#2}%
}
```

```
\IfTrackedIsoCode{<code type>}{<code>}{<true part>}{<>false part>}
```

\IfTrackedIsoCode

```
\long\def\IfTrackedIsoCode#1#2#3#4{%
  \@tracklang@ifundef{\@tracklang@#1@isotolang@#2}{#4}{#3}%
}
```

```
\IfTrackedLanguageHasIsoCode{<code type>}{<language>}{<true part>}{<>false part>}
```

\IfTrackedLanguageHasIsoCode

```
\long\def\IfTrackedLanguageHasIsoCode#1#2#3#4{%
  \@tracklang@ifundef{\@tracklang@#1@isofromlang@#2}{#4}{#3}%
}
```

```
\ForEachTrackedLanguage{\langle cs \rangle}{\langle body \rangle}
```

\ForEachTrackedLanguage

Iterates through the list of tracked languages. On each iteration  $\langle cs \rangle$  is set to the language tag and  $\langle body \rangle$  is performed.

```
\long\def\ForEachTrackedLanguage#1#2{%
  \@tracklang@for#1:=\@tracklang@languages\do{#2}%
}
```

```
\ForEachTrackedDialect{\langle cs \rangle}{\langle body \rangle}
```

\ForEachTrackedDialect

Iterates through the list of tracked dialects. On each iteration  $\langle cs \rangle$  is set to the dialect tag and  $\langle body \rangle$  is performed.

```
\long\def\ForEachTrackedDialect#1#2{%
  \@tracklang@for#1:=\@tracklang@dialects\do{#2}%
}
```

\AnyTrackedRegions

```
\long\def\AnyTrackedRegions#1#2{%
  \ifx\@tracklang@regions\empty
    #2%
  \else
    #1%
  \fi
}
```

```
\ForEachTrackedRegion{\langle cs \rangle}{\langle body \rangle}
```

\ForEachTrackedRegion

Iterates through the list of tracked regions. On each iteration  $\langle cs \rangle$  is set to the region tag and  $\langle body \rangle$  is performed.

```
\long\def\ForEachTrackedRegion#1#2{%
  \@tracklang@for#1:=\@tracklang@regions\do{#2}%
}
```

\AnyTrackedLanguages

```
\long\def\AnyTrackedLanguages#1#2{%
  \ifx\@tracklang@languages\empty
    #2%
  \else
    #1%
  \fi
}
```

```

\IfTrackedLanguageFileExists{<dialect>}{<prefix>}{<suffix>}
{<true
part>}{<>false part>}

```

`\IfTrackedLanguageFileExists`

Determines if the file `<prefix><tag><suffix>` exists, where `<tag>` is an ISO code or ISO codes or label identifying the language. If `<dialect>` hasn't been identified as a tracked dialect, this just does `<>false part>`, otherwise this tries various different combinations for `<tag>`. If the file `<prefix><tag><suffix>` exists, `\CurrentTrackedTag` is set to `<tag>` and `<>true part>` is performed, otherwise `<>false part>` is performed. The order of priority has changed with version 1.4 and now includes a check for variations that include the script. If the original ordering is specifically required, the old behaviour can be obtained with `\IfTrackedLanguageFileExists@orig`.

```

\long\def\IfTrackedLanguageFileExists#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1'}%

```

Initialise.

```

\def\@@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@dialect
}%
\def\@@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@region
}%
\def\CurrentTrackedTag{}%

```

Select this dialect.

```

\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%

```

Save the three types of language codes to for reference.

```

\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
{639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
{639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
{639-3}{\CurrentTrackedLanguage}}%

```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```

  \@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
  \@tracklang@if@file@exists{#4}{#5}%
}%
{#5}% unknown dialect
}

```

ageFileExistsOmitOnlyRegion

```

\IfTrackedLanguageFileExistsOmitOnlyRegion{<dialect>}
{<prefix>}{<suffix>}{<>true
part>}{<>false part>}

```

As above but skips check for only region.

```

\long\def\IfTrackedLanguageFileExistsOmitOnlyRegion#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1'}%

```

Initialise.

```

\def\@@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@dialect
}%
\def\@@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@notregiononly
}%
\def\CurrentTrackedTag{%

```

Select this dialect.

```

\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%

```

Save the three types of language codes to for reference.

```

\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
{639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
{639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
{639-3}{\CurrentTrackedLanguage}}%

```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```

  \@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
  \@tracklang@if@file@exists{#4}{#5}%
}%
{#5}% unknown dialect
}

```

tDialectLabelOmitOnlyRegion

```

\IfTrackedLanguageFileExistsOmitDialectLabelOnlyRegion
{<dialect>}{<prefix>}{<suffix>}{<>true
part>}{<>false part>}

```

As above but skips check for dialect label and only region. Note that if the dialect label happens to also be the root label, it will still be checked but right at the end instead of near the start.

```

\long\def\IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1'}%

```

Initialise.

```
\def\@@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@skipdialectlabel
}%
\def\@@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@notregiononly
}%
\def\CurrentTrackedTag{}
```

Select this dialect.

```
\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%
```

Save the three types of language codes to for reference.

```
\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
  {639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
  {639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
  {639-3}{\CurrentTrackedLanguage}}%
```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```
\@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
\@tracklang@if@file@exists{#4}{#5}%
}%
{#5}% unknown dialect
}
```

```
\IfTrackedLanguageFileExistsOmitDialectLabel{<dialect>}
{<prefix>}{<suffix>}{<>true
part>}{<>false part>}
```

FileExistsOmitDialectLabel

As above but skips check for dialect label. Note that if the dialect label happens to also be the root label, it will still be checked but right at the end instead of near the start.

```
\long\def\IfTrackedLanguageFileExistsOmitDialectLabel#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1'}%
```

Initialise.

```
\def\@@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@skipdialectlabel
}%
\def\@@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@region
}%
\def\CurrentTrackedTag{}
```



Select this dialect.

```
\SetCurrentTrackedDialect{#1}%  
\IfTrackedDialect{#1}%  
{%
```

Save the three types of language codes to for reference.

```
\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage  
  {639-1}{\CurrentTrackedLanguage}}%  
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage  
  {639-2}{\CurrentTrackedLanguage}}%  
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage  
  {639-3}{\CurrentTrackedLanguage}}%
```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```
\@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%  
\@tracklang@if@file@exists{#4}{#5}%  
}%  
{#5}% unknown dialect  
}
```

```
ng@test@if@file@exists@noop
```

```
\def\@tracklang@test@if@file@exists@noop#1#2#3{}
```

```
test@if@file@exists@for@tag
```

```
\def\@tracklang@test@if@file@exists@for@tag#1#2#3{%  
  \let\CurrentTrackedTag\CurrentTrackedLanguageTag  
  \@tracklang@verbose{Testing tag (exact) ‘\CurrentTrackedTag’}%  
  \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%  
  {%  
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo  
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop  
  }%  
  {%  
    \let\@tracklang@if@file@exists\@tracklang@secondoftwo  
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@dialect  
  }%  
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%  
}
```

Allow dialect label test to be skipped.

```
@if@file@exists@for@dialect
```

```
\def\@tracklang@test@if@file@exists@for@dialect{%  
\@tracklang@test@if@file@exists@for@dialect  
}
```

```
@if@file@exists@for@dialect
```

```
\def\@tracklang@test@if@file@exists@for@dialect#1#2#3{%
```

```

\edef\CurrentTrackedTag{#1}%
\@tracklang@verbose{Testing tag (dialect) '\CurrentTrackedTag'}%
\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscriptregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregion
    }%
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptregion
      }%
      {%
        \let\CurrentTrackedIsoCode\empty
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
      }%
    }%
  }%
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

@exists@for@notdialectlabel Allow dialect label test to be skipped.

```

\def\@tracklang@test@if@file@exists@for@skipdialectlabel#1#2#3{%
  \IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscriptregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregion
    }%
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptregion
      }%
      {%
        \let\CurrentTrackedIsoCode\empty
      }%
    }%
  }%
}

```

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
    }%
  }%
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIscriptregion Test <639-1>-<sublang>-<script>-<region> combination.

```

\def\@tracklang@test@if@file@exists@for@langIscriptregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeI
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \ifx\CurrentTrackedDialectScript\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \fi
  \ifx\CurrentTrackedRegion\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
  \fi
  \@tracklang@verbose{Testing tag (639-1 [sublang] [script] [region]) ‘\CurrentTrackedTag’}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedRegion\empty
      \ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there’s a sub-language code then try again without it.

```

    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langII
    \else
      \let\CurrentTrackedTag\CurrentTrackedIsoCode
      \@tracklang@verbose{Testing tag (639-1 [no script region]) ‘\CurrentTrackedTag’}%
      \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
      {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langII
      }%
    \fi
  \else

```

No region set. If there's a sub-language code then try again without it.

```
\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscript
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-1 script [no region]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscript
  }%
\fi
\fi
\else
  \ifx\CurrentTrackedDialectScript\empty
```

Region is set but no script. If there's a sub-language code then try again without it.

```
\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipregion
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag (639-1 [no script] region) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipregion
  }%
\fi
\fi
\else
```

Region and script set. If there's a sub-language code then try again without it.

```
\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscript
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript
-\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag (639-1 [omit sublang] script region)
'\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
\fi
```

```

        {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscr
        }%
    \fi
\fi
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

ists@for@langIIscriptregion Test <639-2>-<sublang>-<script>-<region> combination.

```

\def\@tracklang@test@if@file@exists@for@langIIscriptregion#1#2#3{%
\let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\ifx\CurrentTrackedDialectScript\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\fi
\ifx\CurrentTrackedRegion\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\fi
\@tracklang@verbose{Testing tag (639-2 [sublang] [script] [region])
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedRegion\empty
\ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
\else
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang] [no script region])
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%

```

```

    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
    }%
  \fi
\else

```

No region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskripscrip
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-2 [omit sublang] script [no region])
    '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskripscrip
  }%
\fi
\fi
\else
  \ifx\CurrentTrackedDialectScript\empty

```

Region is set but no script. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskipregio
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag (639-2 [omit sublang] [no script] region)
    '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskipregio
  }%
\fi
\fi
\else

```

Both region and script are set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskripscrip
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript

```

```

-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] script region)
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskips
}%
\fi
\fi
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

sts@for@langIIscriptregion Test (639-3)-(sublang)-(script)-(region) combination.

```

\def\@tracklang@test@if@file@exists@for@langIIscriptregion#1#2#3{%
\let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\ifx\CurrentTrackedDialectScript\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\fi
\ifx\CurrentTrackedRegion\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\fi
\@tracklang@verbose{Testing tag (639-3 [sublang] [script] [region])
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedRegion\empty
\ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
\else

```

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-3 [omit sublang] [no script region])
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\fi
\else

```

No region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscro
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] script [no region])
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscro
}%
\fi
\fi
\else
\ifx\CurrentTrackedDialectScript\empty

```

Region is set but no script. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipreg
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] [no script] region)
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipreg
}%
\fi

```



```
\else
```

Both region and script are set. If there's a sub-language code then try again without it.

```
\ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskipscrip
\else
  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript
    -\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag (639-3 [omit sublang] script region)
    '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskipscrip
  }%
  \fi
\fi
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

@exists@for@langIiskipscrip No region. Has a script but already tested with 639-1 and script. Just test language code alone.

```
\def\@tracklang@test@if@file@exists@for@langIiskipscrip#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \IfTrackedLanguageHasIsoCode
      {639-2}{\CurrentTrackedLanguage}
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskript
      }%
      {%
        \IfTrackedLanguageHasIsoCode
        {639-3}{\CurrentTrackedLanguage}
      }%
    }%
  }%
}
```

```

    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscript
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
\else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscript
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscript
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
}
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIscript No region but has a script.

```

\def\@tracklang@test@if@file@exists@for@langIIscript#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
}

```

```

{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscript
  \else

```

Try without sub-language.

```

  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-2 [omit sublang] script)
    '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscript
  }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIskipscript No region. Has a script but already checked.

```

\def\@tracklang@test@if@file@exists@for@langIIskipscript#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \IfTrackedLanguageHasIsoCode
        {639-3}{\CurrentTrackedLanguage}
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
      }%
    \else

```

Try without sub-language.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-3}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  }%
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@langIIIscript No region but has a script.

```

\def\@tracklang@test@if@file@exists@for@langIIIscript#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] script) ‘\CurrentTrackedTag’}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscript
    \else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop

```

```

    }%
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
    }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIIscript No region. Has a script but already checked.

```

\def\@tracklang@test@if@file@exists@for@langIIIscript#1#2#3{%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \ifx\CurrentTrackedDialectSubLang\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-3 [sublang]) '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \ifx\CurrentTrackedDialectSubLang\empty
            \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
        \else

```

Try without sub-language.

```

        \let\CurrentTrackedTag\CurrentTrackedIsoCode
        \@tracklang@verbose{Testing tag (639-3 [omit sublang]) '\CurrentTrackedTag'}%
        \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
        {%
            \let\@tracklang@if@file@exists\@tracklang@firstoftwo
            \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
        }%
        {%
            \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
        }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIskipregion No script. Has a region but already tested with 639-1 and script. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIskipregion#1#2#3{%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \ifx\CurrentTrackedDialectSubLang\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
    \fi
}

```

```

\fi
\@tracklang@verbose{Testing tag (639-1 [sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIregion
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
  }%
\else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [omit sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIregion
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
  }%

```

```

    }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIregion No script but has a region.

```

\def\@tracklang@test@if@file@exists@for@langIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
    \else

```

Try without sub-language.

```

    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
    \@tracklang@verbose{Testing tag (639-2 [omit sublang] region)
      '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
    }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIskipregion No script. Has a region but already tested with 639-2 and region. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIIskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%

```

```

\fi
\@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
  \IfTrackedLanguageHasIsoCode
  {639-3}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  }%
  \else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-3}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  }%
  }%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIregion No script but has a region.

```

\def\@tracklang@test@if@file@exists@for@langIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
}

```



```

\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
\@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
  \else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] region)
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIIskipregion No script. Has a region but already tested with 639-3 and region. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIIskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    \else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode

```

```

\@tracklang@verbose{Testing tag (639-2 [omit sublang])
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@langIIIregion No script but has a region.

```

\def\@tracklang@test@if@file@exists@for@langIIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipregion
    \else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] region)
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIIskipregion
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%

```

}

s@for@langIskipscriptregion Already tested script and region. Test without script if the script is the default then without region.

```
\def\@tracklang@test@if@file@exists@for@langIskipscriptregion#1#2#3{%
```

Is the script the default for this dialect?

```
\@tracklang@ifcseqcsname\CurrentTrackedDialectScript
  {\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
  {%
```

Try just language code and region.

```
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-1 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty
```

Try just language code and script.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripkip
\else
```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-1 [omit sublang] region)
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripkip
}%
\fi
}%
}%
{%
```

Script isn't the default.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripkipregion
}%
```

```

\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

Test with script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIscripsskipregion#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-1 [sublang] script) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscriptsk
\else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-1 [omit sublang] script)
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscriptsk
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

Test without script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIskipscriptskregion#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%

```

```

{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
Try other language codes with script and region.
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregi
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
    }%
    {%
No other language codes. Try just the region.
      \let\@tracklang@test@if@file@exists@next\@@tracklang@test@if@file@exists@for@region
    }%
  }%
  \else
Try just language code.
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag (639-1 [omit sublang]) '\CurrentTrackedTag'}%
    \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
Try other language codes with script and region.
      \IfTrackedLanguageHasIsoCode
      {639-2}{\CurrentTrackedLanguage}
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregi
      }%
      {%
        \IfTrackedLanguageHasIsoCode
        {639-3}{\CurrentTrackedLanguage}
        {%
          \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
        }%
        {%

```

No other language codes. Try just the region.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
        }%
    }%
}
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

for@langIIskipscriptregion Already tested script and region. Test without script if the script is the default then without region.

```

\def\@tracklang@test@if@file@exists@for@langIIskipscriptregion#1#2#3{%

```

Is the script the default for this dialect?

```

\@tracklang@ifcseqcsname\CurrentTrackedDialectScript
    {\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
    {%

```

Try just language code and region.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
    \ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code and script.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptskip
\else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] region)
    '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptsk
}%

```

```

    \fi
  }%
}%
{%

```

Script isn't the default.

```

    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptskipregion
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

@for@langIIscriptskipregion Test with script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIscriptskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code.

```

    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscriptsk
  \else

```

Try without sub-language.

```

    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
    \@tracklang@verbose{Testing tag (639-2 [omit sublang] script)
      '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscriptsk
    }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

@langIIskipscriptskipregion Test without script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIskipscriptskipregion#1#2#3{%

```

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\@tracklang@verbose{Testing tag (639-2 [sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
Try other language code with script and region.
  \IfTrackedLanguageHasIsoCode
  {639-3}{\CurrentTrackedLanguage}
  {%
    \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptreg
  }%
  {%
No other language codes. Try just the region.
    \let\@tracklang@test@if@file@exists@next\@@tracklang@test@if@file@exists@for@region
  }%
  \else
Try just language code.
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag (639-2 [omit sublang]) ‘\CurrentTrackedTag’}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
Try other language codes with script and region.
      \IfTrackedLanguageHasIsoCode
      {639-3}{\CurrentTrackedLanguage}
      {%
        \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptreg
      }%
      {%
No other language codes. Try just the region.
        \let\@tracklang@test@if@file@exists@next\@@tracklang@test@if@file@exists@for@region
      }%
    }%
  \fi

```



```

}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

for@langIIIskipscriptregion Already tested script and region. Test without script if the script is the default then without region.

```
\def\@tracklang@test@if@file@exists@for@langIIIskipscriptregion#1#2#3{%
```

Is the script the default for this dialect?

```

\@tracklang@ifcseqcsname\CurrentTrackedDialectScript
  {\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
  {%

```

Try just language code and region.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code and script.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptskip
\else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] region)
'\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptskip
}%
\fi
}%
}%
{%

```

Script isn't the default.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptskipregion
    }%
    \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

for@langIIIscriptskipregion Test with script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIIscriptskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptskipregion
    \else

```

Try without sub-language.

```

        \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
        \@tracklang@verbose{Testing tag (639-3 [omit sublang] script)
          '\CurrentTrackedTag'}%
        \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
        {%
          \let\@tracklang@if@file@exists\@tracklang@firstoftwo
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
        }%
        {%
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptskipregion
        }%
    \fi
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

langIIIscriptskipregion Test without script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIIscriptskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi

```

```

\@tracklang@verbose{Testing tag (639-3 [sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty

```

No other language codes. Try just the region.

```

  \let\@tracklang@test@if@file@exists@next\@@tracklang@test@if@file@exists@for@region
  \else

```

Try just language code.

```

  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag (639-3 [omit sublang])
    ‘\CurrentTrackedTag’}%
  \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%

```

No other language codes. Try just the region.

```

    \let\@tracklang@test@if@file@exists@next\@@tracklang@test@if@file@exists@for@region
  }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

t@if@file@exists@for@langII No region or script.

```

\def\@tracklang@test@if@file@exists@for@langII#1#2#3{%
  \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
  {%
    \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \else
      \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-2 [sublang]) ‘\CurrentTrackedTag’}%
    \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \ifx\CurrentTrackedDialectSubLang\empty
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII

```

```

\else
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag (639-2 [omit sublang])
    '\CurrentTrackedTag'}%
  \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
  }%
\fi
}%
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

\@if@file@exists@for@langIII No region or script.

```

\def\@tracklang@test@if@file@exists@for@langIII#1#2#3{%
  \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
  {%
    \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \else
      \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-3 [sublang]) '\CurrentTrackedTag'}%
    \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \ifx\CurrentTrackedDialectSubLang\empty
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
      \else
        \let\CurrentTrackedTag\CurrentTrackedIsoCode
        \@tracklang@verbose{Testing tag (639-3 [omit sublang])
          '\CurrentTrackedTag'}%
        \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
        {%
          \let\@tracklang@if@file@exists\@tracklang@firstoftwo
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
        }%
      }%
    }%
  }%
}

```

```

        {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
        }%
    \fi
    }%
}%
{%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

Allow region test to be skipped.

t@if@file@exists@for@region

```

\def\@tracklang@test@if@file@exists@for@region{%
\@tracklang@test@if@file@exists@for@region
}

```

t@if@file@exists@for@region Test just the region.

```

\def\@tracklang@test@if@file@exists@for@region#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedRegion
\@tracklang@verbose{Testing tag (region) ‘\CurrentTrackedTag’}%
\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@notregiononly Test just the region.

```

\def\@tracklang@test@if@file@exists@for@notregiononly#1#2#3{%
\@tracklang@test@if@file@exists@for@langvariant{#1}{#2}{#3}%
}

```

file@exists@for@langvariant Test language code and variant

```

\def\@tracklang@test@if@file@exists@for@langvariant#1#2#3{%
\ifx\CurrentTrackedDialectVariant\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
\else
\IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIvariant
}%
{%
\IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
}
}

```

```

    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIvariant
    }%
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIvariant
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
      }%
    }%
  }%
\fi
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIvariant Test 639-1 code and variant

```

\def\@tracklang@test@if@file@exists@for@langIvariant#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeI
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%
  \@tracklang@verbose{Testing tag (639-1 [sublang] variant) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIvariant
    }
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIvariant
      }
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
      }%
    }%
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@langIIvariant Test 639-2 code and variant

```
\def\@tracklang@test@if@file@exists@for@langIIvariant#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] variant) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIvariant
    }
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
    }%
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

e@exists@for@langIIIvariant Test 639-3 code and variant

```
\def\@tracklang@test@if@file@exists@for@langIIIvariant#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] variant) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

if@file@exists@for@rootlang Test the root language label. (Final test.)

```

\def\@tracklang@test@if@file@exists@for@rootlang#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedLanguage
  \@tracklang@verbose{Testing tag (root) '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists#{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  }%
  }%
}%
}

```

ckedLanguageFileExists@orig The new definition of \IfTrackedLanguageFileExists has a different order of priority. If the original behaviour is specifically required, this has the pre version 1.4 definition.

```

\long\def\IfTrackedLanguageFileExists@orig#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1' (pre-v1.4)}%
  \def\CurrentTrackedTag{}%
  \SetCurrentTrackedDialect{#1}%
  \IfTrackedDialect{#1}%
  {%
    \edef\CurrentTrackedTag{#1}%
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@if@file@exists#{#2\CurrentTrackedTag#3}%
    {#4}%
    {%
      \IfTrackedLanguageHasIsoCode
        {639-1}{\CurrentTrackedLanguage}
      {%
        \edef\CurrentTrackedIsoCode{%
          \TrackedIsoCodeFromLanguage
            {639-1}{\CurrentTrackedLanguage}}%
        \ifx\CurrentTrackedRegion\empty
          \let\CurrentTrackedTag\CurrentTrackedIsoCode
          \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
          \@tracklang@if@file@exists#{#2\CurrentTrackedTag#3}%
          {#4}
        {%
          \IfTrackedLanguageHasIsoCode
            {639-2}{\CurrentTrackedLanguage}
          {%
            \edef\CurrentTrackedIsoCode{%
              \TrackedIsoCodeFromLanguage
                {639-2}{\CurrentTrackedLanguage}}%
            \let\CurrentTrackedTag\CurrentTrackedIsoCode
            \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
            \@tracklang@if@file@exists#{#2\CurrentTrackedTag#3}%
            {#4}%
          {%
            \let\CurrentTrackedTag\CurrentTrackedLanguage
            \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
            \@tracklang@if@file@exists#{#2\CurrentTrackedTag#3}{#4}{#5}%
          }%
        }%
      }%
    }%
  }%
}

```



```

    }%
  }%
  {%
    \let\CurrentTrackedTag\CurrentTrackedLanguage
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
  }%
}%
\else
\edef\CurrentTrackedTag{%
  \CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\org@currenttrackedisocode\CurrentTrackedIsoCode
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage
      {639-2}{\CurrentTrackedLanguage}}%
    \edef\CurrentTrackedTag{%
      \CurrentTrackedIsoCode-\CurrentTrackedRegion}%
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
    {%
      \let\CurrentTrackedTag\org@currenttrackedisocode
      \let\org@currenttrackedisocode\CurrentTrackedIsoCode
      \let\CurrentTrackedIsoCode\CurrentTrackedTag
      \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
      \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
      {#4}
      {%
        \let\CurrentTrackedIsoCode\org@currenttrackedisocode
        \let\CurrentTrackedTag\CurrentTrackedIsoCode
        \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
        \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
        {#4}%
        {%
          \let\CurrentTrackedTag\CurrentTrackedRegion
          \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
          \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
          {#4}%
          {%
            \let\CurrentTrackedTag\CurrentTrackedLanguage
            \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
            \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
          }%
        }%
      }%
    }%
  }%
}

```

```

        }%
    }%
} %
{ %
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
    { %
        \let\CurrentTrackedTag\CurrentTrackedRegion
        \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
        \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
        {#4}%
        { %
            \let\CurrentTrackedTag\CurrentTrackedLanguage
            \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
            \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
        }%
    }%
} %
} %
} %
\fi
} %
{ %
    \IfTrackedLanguageHasIsoCode
    {639-2}{\CurrentTrackedLanguage}
    { %
        \edef\CurrentTrackedIsoCode{%
            \TrackedIsoCodeFromLanguage
            {639-2}{\CurrentTrackedLanguage}}%
    }%
    { %
        \IfTrackedLanguageHasIsoCode
        {639-3}{\CurrentTrackedLanguage}
        { %
            \edef\CurrentTrackedIsoCode{%
                \TrackedIsoCodeFromLanguage
                {639-3}{\CurrentTrackedLanguage}}%
        }%
        { %
            \let\CurrentTrackedIsoCode\empty
        }%
    }%
} %
\ifx\CurrentTrackedIsoCode\empty
\ifx\CurrentTrackedRegion\empty
\let\CurrentTrackedTag\CurrentTrackedLanguage
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
\else

```

```

\let\CurrentTrackedTag\CurrentTrackedRegion
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\let\CurrentTrackedTag\CurrentTrackedLanguage
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
}%
\fi
\else
\ifx\CurrentTrackedRegion\empty
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\let\CurrentTrackedTag\CurrentTrackedLanguage
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
}%
\else
\edef\CurrentTrackedTag{%
\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\let\CurrentTrackedTag\CurrentTrackedRegion
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\let\CurrentTrackedTag\CurrentTrackedLanguage
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
}%
}%
}%
\fi
\fi
}%
}%
{#5}% unknown dialect

```

```
}
```

## 4.9 Resources

Provide some commands to make it easier for package authors to integrate the package code with `tracklang`. In the command definition describes below,  $\langle pkgname \rangle$  indicates the initial part of the resource files that follow the naming convention,  $\langle pkgname \rangle - \langle tag \rangle .ldf$ . Typically this will match the base name of the package that uses those resource files, but this isn't compulsory. The argument  $\langle tag \rangle$  is the current tracked tag obtained from `\IfTrackedLanguageFileExists`.

```
\TrackLangProvidesResource{ $\langle tag \rangle$ }[ $\langle version \rangle$ ]
```

```
\TrackLangProvidesResource
```

If `\ProvidesFile` exists, we can use that, otherwise we need to provide a generic version.

```
\ifx\ProvidesFile\undefined
```

Generic code uses simplistic method to grab the version details in the final optional argument. Since we're not using  $\LaTeX$  we don't have commands like `\@ifnextchar` available.

```
\long\def\TrackLangProvidesResource#1#2{%
  \ifx\TrackLangRequireDialectPrefix\undefined
    \@tracklang@err{Resources files using
      \string\TrackLangProvidesResource\space
      must be loaded with \string\TrackLangRequireDialect}%
  \fi
  \ifx#2[\relax
    \def\@tracklang@next{%
      \@tracklang@providesresource{\TrackLangRequireDialectPrefix-#1.ldf}#2%
    }
  \else
    \expandafter\xdef\csname ver@\TrackLangRequireDialectPrefix
      -#1.ldf\endcsname{%
      {%
        \newlinechar='\^^J
        \def\MessageBreak{^^J}%
        \message{^^JFile: \TrackLangRequireDialectPrefix-#1.ldf^^J}%
      }%
      \long\def\@tracklang@next{#2}%
    }%
  \fi
  \@tracklang@next
}
\def\@tracklang@providesresource#1[#2]{%
  \expandafter\xdef\csname ver@#1\endcsname{#2}%
  {%
    \newlinechar='\^^J
```

```

        \def\MessageBreak{^^J}%
        \message{^^JFile: #1 #2^^J}%
    }%
}
\else

```

LaTeX code can simply use `\ProvidesFile`.

```

\def\TrackLangProvidesResource#1{%
  \ifx\TrackLangRequireDialectPrefix\undefined
    \@tracklang@err{Resources files using
      \string\TrackLangProvidesResource\space
      must be loaded with \string\TrackLangRequireDialect}%
  \fi
  \expandafter\ProvidesFile\expandafter
  {\TrackLangRequireDialectPrefix-#1.ldf}%
}
\fi

```

```
\TrackLangAddToHook{<code>}{<type>}
```

`\TrackLangAddToHook`

Within the resource files, a check is required for the language hook, where the hook type is given by `<type>`. For example, if `<type>` is `captions`, the for `babel`, this is `\captions<dialect>` (dialect obtained through `\CurrentTrackedDialect`) and for `polyglossia`, this is `\captions<language>` (language obtained through `\CurrentTrackedLanguage`). This command is not permitted outside resource files.

```
\def\TrackLangAddToHook{\noop@TrackLangAddToHook}
```

`\noop@TrackLangAddToHook`

```

\def\noop@TrackLangAddToHook#1#2{%
  \@tracklang@err{\string\TrackLangAddToHook\space
    only permitted within resource files}
}

```

`\@TrackLangAddToHook`

```
\def\@TrackLangAddToHook#1#2{%
```

babel check first.

```

  \@tracklang@ifundef{#2\CurrentTrackedDialect}%
  {%

```

Does the dialect label have a mapping?

```

  \IfTrackedDialectHasMapping{\CurrentTrackedDialect}%
  {%

```

Try the mapping label next.

```

  \edef\@tracklang@tmp{%
    \csname @tracklang@dialectmap@tohook@\CurrentTrackedDialect\endcsname}%
  \@tracklang@ifundef{#2\@tracklang@tmp}%
  {%

```

No captions hook. Try polyglossia.

```
\@tracklang@ifundef{#2\CurrentTrackedLanguage}%  
{%
```

No captions hook. Do nothing (it's possible no language package has been loaded).

```
\@tracklang@verbose{no hook found for \CurrentTrackedDialect}%  
}%  
{%  
\@tracklang@addtohook{#2}{\CurrentTrackedLanguage}{#1}%  
}%  
}%  
{%  
\@tracklang@addtohook{#2}{\@tracklang@tmp}{#1}%  
}%  
}%  
{%
```

polyglossia check next.

```
\@tracklang@ifundef{#2\CurrentTrackedLanguage}%  
{%
```

No captions hook.

```
\@tracklang@verbose{no hook found for \CurrentTrackedDialect}%  
}%  
{%  
\@tracklang@addtohook{#2}{\CurrentTrackedLanguage}{#1}%  
}%  
}%  
}%  
{%  
\@tracklang@addtohook{#2}{\CurrentTrackedDialect}{#1}%  
}%
```

Do the code now. (This is needed for cases such as the ngerman which defines `\captionsgerman` but calls it immediately rather than at the start of the document.)

```
#1%  
}
```

```
\@tracklang@addtohook{<type>}{<label>}{<code>}
```

`\@tracklang@addtohook`

```
\def\@tracklang@addtohook#1#2#3{%  
\expandafter\let\expandafter\@tracklang@hook\csname #1#2\endcsname  
\expandafter  
\gdef\csname#1#2\expandafter\endcsname\expandafter{\@tracklang@hook#3}%  
}
```

Since the captions hook is the most common, provide a shortcut.

```
\TrackLangAddToCaptions{<code>}
```

\TrackLangAddToCaptions

```
\def\TrackLangAddToCaptions#1{\TrackLangAddToHook{#1}{captions}}
```

```
\TrackLangRedefHook{<code>}{<type>}
```

\TrackLangRedefHook

Similar to \TrackLangAddToHook but redefines the hook rather than appending to it. This command is not permitted outside resource files.

```
\def\TrackLangRedefHook{\noop@TrackLangRedefHook}
```

\noop@TrackLangRedefHook

```
\def\noop@TrackLangRedefHook#1#2{%  
  \@tracklang@err{\string\TrackLangRedefHook\space  
  only permitted within resource files}  
}
```

\@TrackLangRedefHook

```
\def\@TrackLangRedefHook#1#2{%  
  babel check first.  
  \@tracklang@ifundef{#2\CurrentTrackedDialect}%  
  {%  
    Does the dialect label have a mapping?  
    \IfTrackedDialectHasMapping{\CurrentTrackedDialect}%  
    {%  
      Try the mapping label next.  
      \edef\@tracklang@tmp{%  
        \csname @tracklang@dialectmap@tohook@\CurrentTrackedDialect\endcsname}%  
        \@tracklang@ifundef{#2\@tracklang@tmp}%  
        {%  
          No captions hook. Try polyglossia.  
          \@tracklang@ifundef{#2\CurrentTrackedLanguage}%  
          {%  
            No captions hook. Do nothing (it's possible no language package has been  
            loaded).  
            \@tracklang@verbose{no hook found for \CurrentTrackedDialect}%  
            }%  
            {%  
              \@tracklang@redefhook{#2}{\CurrentTrackedLanguage}{#1}%  
            }%  
            }%  
            \@tracklang@redefhook{#2}{\@tracklang@tmp}{#1}%  
          }%  
          }%  
        }%  
      }%  
    }%  
  }%
```

polyglossia check next.

```
\@tracklang@ifundef{#2\CurrentTrackedLanguage}%  
{%
```

No captions hook.

```
\@tracklang@verbose{no hook found for \CurrentTrackedDialect}%  
}%  
{%  
\@tracklang@redefhook{#2}{\CurrentTrackedLanguage}{#1}%  
}%  
}%  
}%  
{%  
\@tracklang@redefhook{#2}{\CurrentTrackedDialect}{#1}%  
}%
```

Do the code now in case the hook has already been used.

```
#1%  
}
```

```
\@tracklang@redefhook{<type>}{<label>}{<code>}
```

\@tracklang@redefhook

```
\def\@tracklang@redefhook#1#2#3{%  
\expandafter\gdef\csname#1#2\endcsname{#3}%  
}
```

```
\SetTrackedDialectLabelMap{<tracklang-label>}{<hook-label>}
```

\SetTrackedDialectLabelMap

Define a mapping between a `tracklang` dialect label and the corresponding label used by the language hook. For example, `ngermanDE` is a recognised `tracklang` dialect label, but the closest `babel` equivalent is `ngerman`, so `ngermanDE` would need to be mapped to `ngerman` for the language hooks. The arguments are `<tracklang-label>` (the `tracklang` dialect label) and `<hook-label>` (the `babel`, `polyglossia` etc label).

```
\def\SetTrackedDialectLabelMap#1#2{%
```

Store the mapping that can obtain the hook label from the `tracklang` label (`tracklang` to hook).

```
\@tracklang@enamedef{@tracklang@dialectmap@tohook@#1}{#2}%
```

Store the mapping that can obtain the `tracklang` label from the hook label.

```
\@tracklang@enamedef{@tracklang@dialectmap@fromhook@#2}{#1}%  
}
```

```
\IfTrackedDialectHasMapping{<tracklang label>}{<true>}  
{<false>}
```

\IfTrackedDialectHasMapping



Test if the tracklang dialect label has been assigned a mapping to a language hook.

```
\def\IfTrackedDialectHasMapping#1#2#3{%
  \@tracklang@ifundef{@tracklang@dialectmap@tohook@#1}{#3}{#2}%
}
```

```
\IfHookHasMappingFromTrackedDialect{<hook label>}{<true>}
{<false>}
```

\HasMappingFromTrackedDialect

Tests if the language hook label has been assigned a mapping from a tracklang dialect label.

```
\def\IfHookHasMappingFromTrackedDialect#1#2#3{%
  \@tracklang@ifundef{@tracklang@dialectmap@fromhook@#1}{#3}{#2}%
}
```

```
\GetTrackedDialectToMapping{<tracklang label>}
```

\GetTrackedDialectToMapping

Gets the mapping for the given tracklang dialect label to a language hook label or the *<label>* itself if no mapping has been defined.

```
\def\GetTrackedDialectToMapping#1{%
  \@tracklang@ifundef{@tracklang@dialectmap@tohook@#1}{#1}%
  {\csname @tracklang@dialectmap@tohook@#1\endcsname}%
}
```

```
\GetTrackedDialectFromMapping{<language hook>}
```

\GetTrackedDialectFromMapping

Gets the reverse mapping from the given language hook to the tracklang label.

```
\def\GetTrackedDialectFromMapping#1{%
  \@tracklang@ifundef{@tracklang@dialectmap@fromhook@#1}{#1}%
  {\csname @tracklang@dialectmap@fromhook@#1\endcsname}%
}
```

```
\TrackLangRequireResource{<tag>}
```

\TrackLangRequireResource

```
\def\TrackLangRequireResource{\noop@TrackLangRequireResource}
```

\noop@TrackLangRequireResource

Default behaviour outside of resource files: generate an error and ignore arguments.

```
\def\noop@TrackLangRequireResource#1{%
  \@tracklang@err{\string\TrackLangRequireResource\space
  only permitted within resource files}
}
```

`\TrackLangRequireResource` Actual behaviour.

```
\def\TrackLangRequireResource#1{%
  \@tracklang@ifundef{ver@\TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@ifFileExists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
    }%
  }%
  {%
    \@tracklang@warn{No ‘\TrackLangRequireDialectPrefix’ support for
      language/region ‘#1’\MessageBreak
      (resource file ‘\TrackLangRequireDialectPrefix-#1.ldf’ not found)}%
  }%
}%
}
```

`\TrackLangRequireResourceOrDo{<tag>}{<resource loaded code>}{<resource already loaded code>}`

`\TrackLangRequireResourceOrDo`

Like `\TrackLangRequireResource` but also does *<resource loaded code>* if the resource file is loaded or *<resource already loaded code>* if the resource file has already been loaded.

```
\def\TrackLangRequireResourceOrDo{%
  \noop@TrackLangRequireResourceOrDo
}
```

`\TrackLangRequireResourceOrDo` Default behaviour outside of resources files: generate an error and ignore arguments.

```
\def\noop@TrackLangRequireResourceOrDo#1#2#3{%
  \@tracklang@err{\string\TrackLangRequireResourceOrDo\space
    only permitted within resource files}
}
```

`\TrackLangRequireResourceOrDo` Actual behaviour.

```
\def\TrackLangRequireResourceOrDo#1#2#3{%
  \@tracklang@ifundef{ver@\TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@ifFileExists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
      #2%
    }%
  }%
  {%
    \@tracklang@warn{No ‘\TrackLangRequireDialectPrefix’ support for
      language/region ‘#1’\MessageBreak
      (resource file ‘\TrackLangRequireDialectPrefix-#1.ldf’ not found)}%
  }%
}
```

```

    }%
  }%
  {#3}%
}

```

```
\TrackLangRequestResource{<tag>}{<not found code>}
```

\TrackLangRequestResource

Like \TrackLangRequireResource but does *<not found code>* if the file doesn't exist.

```
\def\TrackLangRequestResource{\noop@TrackLangRequestResource}
```

\noop@TrackLangRequestResource Default behaviour outside of resources files: generate an error and ignore arguments.

```

\def\noop@TrackLangRequestResource#1#2{%
  \@tracklang@err{\string\TrackLangRequestResource\space
    only permitted within resource files}
}

```

\@TrackLangRequestResource Actual behaviour.

```

\def\@TrackLangRequestResource#1#2{%
  \@tracklang@ifundef{ver@TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@ifFileExists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
    }%
    {#2}%
  }%
  {}%
}

```

```
\TrackLangRequireDialect[<load code>]{<pkgname>}{<dialect>}
```

\TrackLangRequireDialect

```
\def\TrackLangRequireDialect{\@TrackLangRequireDialect}
```

\noop@TrackLangRequireDialect No-op code.

```

\def\noop@TrackLangRequireDialect#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@noop@TrackLangRequireDialect[]}%
  \else
    \def\@tracklang@next{\@noop@TrackLangRequireDialect[] {#1}}%
  \fi
  \@tracklang@next
}
\def\@noop@TrackLangRequireDialect[#1]#2#3{%
  \@tracklang@err{\string\TrackLangRequireDialect...\space

```

```

    only permitted within resource files}
}

```

\TrackLangRequireDialect Actual code.

```

\def\@TrackLangRequireDialect#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialect[]%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialect
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
  \@tracklang@next
}
\def\@TrackLangRequireDialect[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExists{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No ‘#2’ support for dialect ‘#3’
    \ifTrackLangShowWarnings
    \else
      (switch on tracklang’s verbose mode for search attempts)
    \fi
  }%
}
}

```

\@TrackLang@RequireDialect

```

\def\@TrackLang@RequireDialect#1{%

```

Enable \TrackLangRequireResource etc so that they can only be used in resource files.

```

\let\TrackLangRequireResource\@TrackLangRequireResource
\let\TrackLangRequireResourceOrDo\@TrackLangRequireResourceOrDo
\let\TrackLangRequestResource\@TrackLangRequestResource

```

Disable \TrackLangRequireDialect etc so that they can’t be used in resource files.

```

\let\TrackLangRequireDialect\noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabel\noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
  \noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitOnlyRegion\noop@TrackLangRequireDialect

```

Enable \TrackLangAddToHook.

```

\let\TrackLangAddToHook\@TrackLangAddToHook

```

Load resource file using the code provided in the first argument.

```
#1%
```

Disable `\TrackLangRequireResource` etc.

```
\let\TrackLangRequireResource\noop@TrackLangRequireResource
\let\TrackLangRequireResourceOrDo\noop@TrackLangRequireResourceOrDo
\let\TrackLangRequestResource\noop@TrackLangRequestResource
```

Enable `\TrackLangRequireDialect` etc.

```
\let\TrackLangRequireDialect\@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabel
  \@TrackLangRequireDialectOmitDialectLabel
\let\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
  \@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
\let\TrackLangRequireDialectOmitOnlyRegion
  \@TrackLangRequireDialectOmitOnlyRegion
```

Disable `\TrackLangAddToHook`.

```
\let\TrackLangAddToHook\noop@TrackLangAddToHook
}
```

```
\TrackLangRequireDialectOmitDialectLabel[{load code}]
  {{pkgname}}{{dialect}}
```

`\TrackLangRequireDialectOmitDialectLabel`

```
\def\TrackLangRequireDialectOmitDialectLabel{%
  \@TrackLangRequireDialectOmitDialectLabel}
```

`\TrackLangRequireDialectOmitDialectLabel` Actual code.

```
\def\@TrackLangRequireDialectOmitDialectLabel#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitDialectLabel[]%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitDialectLabel
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
    \@tracklang@next
  }
\def\@@TrackLangRequireDialectOmitDialectLabel[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitDialectLabel{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No ‘#2’ support for dialect ‘#3’}
    \ifTrackLangShowWarnings
```

```

        \else
          (switch on tracklang's verbose mode for search attempts)
        \fi
      }%
    }%
  }
}

```

```

\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[⟨load
code⟩]{⟨pkgname⟩}{⟨dialect⟩}

```

lectOmitLabelOmitOnlyRegion

```

\def\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion{%
\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion}

```

tDialectLabelOmitOnlyRegion Actual code.

```

\def\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[]}%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
    \@tracklang@next
  }
\def\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No '#2' support for dialect '#3'}
    \ifTrackLangShowWarnings
      \else
        (switch on tracklang's verbose mode for search attempts)
      \fi
    }%
  }%
}
}

```

```

\TrackLangRequireDialectOmitOnlyRegion[⟨load code⟩]
{⟨pkgname⟩}{⟨dialect⟩}

```

quireDialectOmitOnlyRegion

```

\def\TrackLangRequireDialectOmitOnlyRegion{%
\TrackLangRequireDialectOmitOnlyRegion}

```

requireDialectOmitOnlyRegion Actual code.

```
\def\@TrackLangRequireDialectOmitOnlyRegion#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitOnlyRegion[]}%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitOnlyRegion
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
  \@tracklang@next
}
\def\@@TrackLangRequireDialectOmitOnlyRegion[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitOnlyRegion{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No '#2' support for dialect '#3'
      \ifTrackLangShowWarnings
        \else
          (switch on tracklang's verbose mode for search attempts)
        \fi
    }%
  }%
}
\@tracklang@restore@at
```

Restore category code for @ if necessary.

## 5 Regions Generic Code (tracklang-region-codes.tex)

This is only loaded if a mapping is required between numeric and alphabetic region codes. (It would slow down the package loading to automatically load if not required.) Since this is loaded on the fly, we need to be careful about spurious spaces.

```
\ifnum\catcode'\@=11\relax
  \def\@tracklang@regions@restore@at{%
\else
  \expandafter\edef\csname @tracklang@regions@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@\relax
  }%
  \catcode'\@=11\relax
\fi
```

Check if this file has already been loaded:

```

\ifx\TrackLangRegionMap\undefined
\else
  \@tracklang@regions@restore@at
  \expandafter\endinput
\fi

```

Version info.

```

\expandafter\def\csname ver@tracklang-region-codes.tex\endcsname{%
2025/01/22 v1.6.3 (NLCT) Track Languages Regions}%

```

```

\TrackLangRegionMap{<numeric code>}{<alpha-2
code>}{<alpha-3 code>}

```

\TrackLangRegionMap

Define mapping.

```

\def\TrackLangRegionMap#1#2#3{%
  \@tracklang@enamedef{@tracklang@region@numtoalphaii@#1}{#2}%
  \@tracklang@enamedef{@tracklang@region@numtoalphaiii@#1}{#3}%
  \@tracklang@enamedef{@tracklang@region@alphaiitonum@#2}{#1}%
  \@tracklang@enamedef{@tracklang@region@alphaiiitonum@#3}{#1}%
  \@tracklang@enamedef{@tracklang@region@alphaiitoalphaiii@#2}{#3}%
  \@tracklang@enamedef{@tracklang@region@alphaiiitoalphaii@#3}{#2}%
}%

```

```

\TrackLangAlphaIIToNumericRegion{<alpha-2 code>}

```

\TrackLangAlphaIIToNumericRegion

```

\def\TrackLangAlphaIIToNumericRegion#1{%
  \@tracklang@nameuse{@tracklang@region@alphaiitonum@#1}%
}%

```

```

\TrackLangNumericToAlphaIIRegion{<numeric code>}

```

\TrackLangNumericToAlphaIIRegion

```

\def\TrackLangNumericToAlphaIIRegion#1{%
  \@tracklang@nameuse{@tracklang@region@numtoalphaii@#1}%
}%

```

```

\TrackLangIfKnownAlphaIIRegion{<alpha-2
code>}{<true>}{<false>}

```

\TrackLangIfKnownAlphaIIRegion

```

\def\TrackLangIfKnownAlphaIIRegion#1#2#3{%
  \@tracklang@ifundef{@tracklang@region@alphaiitonum@#1}%

```



```
{#3}%
{#2}%
}%
```

```
\TrackLangIfKnownNumericRegion{<numeric
code>}{<true>}{<false>}
```

ackLangIfKnownNumericRegion

```
\def\TrackLangIfKnownNumericRegion#1#2#3{%
\@tracklang@ifundef{@tracklang@region@numtoalpaii@#1}%
{#3}%
{#2}%
}%
```

```
\TrackLangAlphaIIIToNumericRegion{<alpha-3 code>}
```

LangAlphaIIIToNumericRegion

```
\def\TrackLangAlphaIIIToNumericRegion#1{%
\@tracklang@nameuse{@tracklang@region@alpaiiitonum@#1}%
}%
```

```
\TrackLangNumericToAlphaIIIRegion{<numeric code>}
```

LangNumericToAlphaIIIRegion

```
\def\TrackLangNumericToAlphaIIIRegion#1{%
\@tracklang@nameuse{@tracklang@region@numtoalpaiii@#1}%
}%
```

```
\TrackLangIfKnownAlphaIIIRegion{<alpha-3
code>}{<true>}{<false>}
```

ackLangIfKnownAlphaIIIRegion

```
\def\TrackLangIfKnownAlphaIIIRegion#1#2#3{%
\@tracklang@ifundef{@tracklang@region@alpaiiitonum@#1}%
{#3}%
{#2}%
}%
```

Define mappings.

```
\TrackLangRegionMap{004}{AF}{AFG}%
\TrackLangRegionMap{248}{AX}{ALA}%
\TrackLangRegionMap{008}{AL}{ALB}%
\TrackLangRegionMap{012}{DZ}{DZA}%
```

\TrackLangRegionMap{016}{AS}{ASM}%  
\TrackLangRegionMap{020}{AD}{AND}%  
\TrackLangRegionMap{024}{AO}{AGO}%  
\TrackLangRegionMap{660}{AI}{AIA}%  
\TrackLangRegionMap{010}{AQ}{ATA}%  
\TrackLangRegionMap{028}{AG}{ATG}%  
\TrackLangRegionMap{032}{AR}{ARG}%  
\TrackLangRegionMap{051}{AM}{ARM}%  
\TrackLangRegionMap{533}{AW}{ABW}%  
\TrackLangRegionMap{036}{AU}{AUS}%  
\TrackLangRegionMap{040}{AT}{AUT}%  
\TrackLangRegionMap{031}{AZ}{AZE}%  
\TrackLangRegionMap{044}{BS}{BHS}%  
\TrackLangRegionMap{048}{BH}{BHR}%  
\TrackLangRegionMap{050}{BD}{BGD}%  
\TrackLangRegionMap{052}{BB}{BRB}%  
\TrackLangRegionMap{112}{BY}{BLR}%  
\TrackLangRegionMap{056}{BE}{BEL}%  
\TrackLangRegionMap{084}{BZ}{BLZ}%  
\TrackLangRegionMap{204}{BJ}{BEN}%  
\TrackLangRegionMap{060}{BM}{BMU}%  
\TrackLangRegionMap{064}{BT}{BTN}%  
\TrackLangRegionMap{068}{BO}{BOL}%  
\TrackLangRegionMap{535}{BQ}{BES}%  
\TrackLangRegionMap{070}{BA}{BIH}%  
\TrackLangRegionMap{072}{BW}{BWA}%  
\TrackLangRegionMap{074}{BV}{BVT}%  
\TrackLangRegionMap{076}{BR}{BRA}%  
\TrackLangRegionMap{086}{IO}{IOT}%  
\TrackLangRegionMap{096}{BN}{BRN}%  
\TrackLangRegionMap{100}{BG}{BGR}%  
\TrackLangRegionMap{854}{BF}{BFA}%  
\TrackLangRegionMap{108}{BI}{BDI}%  
\TrackLangRegionMap{132}{CV}{CPV}%  
\TrackLangRegionMap{116}{KH}{KHM}%  
\TrackLangRegionMap{120}{CM}{CMR}%  
\TrackLangRegionMap{124}{CA}{CAN}%  
\TrackLangRegionMap{136}{KY}{CYM}%  
\TrackLangRegionMap{140}{CF}{CAF}%  
\TrackLangRegionMap{148}{TD}{TCD}%  
\TrackLangRegionMap{152}{CL}{CHL}%  
\TrackLangRegionMap{156}{CN}{CHN}%  
\TrackLangRegionMap{162}{CX}{CXR}%  
\TrackLangRegionMap{166}{CC}{CCK}%  
\TrackLangRegionMap{170}{CO}{COL}%  
\TrackLangRegionMap{174}{KM}{COM}%  
\TrackLangRegionMap{180}{CD}{COD}%  
\TrackLangRegionMap{178}{CG}{COG}%  
\TrackLangRegionMap{184}{CK}{COK}%  
\TrackLangRegionMap{188}{CR}{CRI}%

\TrackLangRegionMap{384}{CI}{CIV}%  
\TrackLangRegionMap{191}{HR}{HRV}%  
\TrackLangRegionMap{192}{CU}{CUB}%  
\TrackLangRegionMap{531}{CW}{CUW}%  
\TrackLangRegionMap{196}{CY}{CYP}%  
\TrackLangRegionMap{203}{CZ}{CZE}%  
\TrackLangRegionMap{208}{DK}{DNK}%  
\TrackLangRegionMap{262}{DJ}{DJI}%  
\TrackLangRegionMap{212}{DM}{DMA}%  
\TrackLangRegionMap{214}{DO}{DOM}%  
\TrackLangRegionMap{218}{EC}{ECU}%  
\TrackLangRegionMap{818}{EG}{EGY}%  
\TrackLangRegionMap{222}{SV}{SLV}%  
\TrackLangRegionMap{226}{GQ}{GNQ}%  
\TrackLangRegionMap{232}{ER}{ERI}%  
\TrackLangRegionMap{233}{EE}{EST}%  
\TrackLangRegionMap{231}{ET}{ETH}%  
\TrackLangRegionMap{238}{FK}{FLK}%  
\TrackLangRegionMap{234}{FO}{FRO}%  
\TrackLangRegionMap{242}{FJ}{FJI}%  
\TrackLangRegionMap{246}{FI}{FIN}%  
\TrackLangRegionMap{250}{FR}{FRA}%  
\TrackLangRegionMap{254}{GF}{GUF}%  
\TrackLangRegionMap{258}{PF}{PYF}%  
\TrackLangRegionMap{260}{TF}{ATF}%  
\TrackLangRegionMap{266}{GA}{GAB}%  
\TrackLangRegionMap{270}{GM}{GMB}%  
\TrackLangRegionMap{268}{GE}{GEO}%  
\TrackLangRegionMap{276}{DE}{DEU}%  
\TrackLangRegionMap{288}{GH}{GHA}%  
\TrackLangRegionMap{292}{GI}{GIB}%  
\TrackLangRegionMap{300}{GR}{GRC}%  
\TrackLangRegionMap{304}{GL}{GRL}%  
\TrackLangRegionMap{308}{GD}{GRD}%  
\TrackLangRegionMap{312}{GP}{GLP}%  
\TrackLangRegionMap{316}{GU}{GUM}%  
\TrackLangRegionMap{320}{GT}{GTM}%  
\TrackLangRegionMap{831}{GG}{GGY}%  
\TrackLangRegionMap{324}{GN}{GIN}%  
\TrackLangRegionMap{624}{GW}{GNB}%  
\TrackLangRegionMap{328}{GY}{GUY}%  
\TrackLangRegionMap{332}{HT}{HTI}%  
\TrackLangRegionMap{334}{HM}{HMD}%  
\TrackLangRegionMap{336}{VA}{VAT}%  
\TrackLangRegionMap{340}{HN}{HND}%  
\TrackLangRegionMap{344}{HK}{HKG}%  
\TrackLangRegionMap{348}{HU}{HUN}%  
\TrackLangRegionMap{352}{IS}{ISL}%  
\TrackLangRegionMap{356}{IN}{IND}%  
\TrackLangRegionMap{360}{ID}{IDN}%

\TrackLangRegionMap{364}{IR}{IRN}%  
\TrackLangRegionMap{368}{IQ}{IRQ}%  
\TrackLangRegionMap{372}{IE}{IRL}%  
\TrackLangRegionMap{833}{IM}{IMN}%  
\TrackLangRegionMap{376}{IL}{ISR}%  
\TrackLangRegionMap{380}{IT}{ITA}%  
\TrackLangRegionMap{388}{JM}{JAM}%  
\TrackLangRegionMap{392}{JP}{JPN}%  
\TrackLangRegionMap{832}{JE}{JEY}%  
\TrackLangRegionMap{400}{JO}{JOR}%  
\TrackLangRegionMap{398}{KZ}{KAZ}%  
\TrackLangRegionMap{404}{KE}{KEN}%  
\TrackLangRegionMap{296}{KI}{KIR}%  
\TrackLangRegionMap{408}{KP}{PRK}%  
\TrackLangRegionMap{410}{KR}{KOR}%  
\TrackLangRegionMap{414}{KW}{KWT}%  
\TrackLangRegionMap{417}{KG}{KGZ}%  
\TrackLangRegionMap{418}{LA}{LAO}%  
\TrackLangRegionMap{428}{LV}{LVA}%  
\TrackLangRegionMap{422}{LB}{LBN}%  
\TrackLangRegionMap{426}{LS}{LSO}%  
\TrackLangRegionMap{430}{LR}{LBR}%  
\TrackLangRegionMap{434}{LY}{LBY}%  
\TrackLangRegionMap{438}{LI}{LIE}%  
\TrackLangRegionMap{440}{LT}{LTU}%  
\TrackLangRegionMap{442}{LU}{LUX}%  
\TrackLangRegionMap{446}{MO}{MAC}%  
\TrackLangRegionMap{807}{MK}{MKD}%  
\TrackLangRegionMap{450}{MG}{MDG}%  
\TrackLangRegionMap{454}{MW}{MWI}%  
\TrackLangRegionMap{458}{MY}{MYS}%  
\TrackLangRegionMap{462}{MV}{MDV}%  
\TrackLangRegionMap{466}{ML}{MLI}%  
\TrackLangRegionMap{470}{MT}{MLT}%  
\TrackLangRegionMap{584}{MH}{MHL}%  
\TrackLangRegionMap{474}{MQ}{MTQ}%  
\TrackLangRegionMap{478}{MR}{MRT}%  
\TrackLangRegionMap{480}{MU}{MUS}%  
\TrackLangRegionMap{175}{YT}{MYT}%  
\TrackLangRegionMap{484}{MX}{MEX}%  
\TrackLangRegionMap{583}{FM}{FSM}%  
\TrackLangRegionMap{498}{MD}{MDA}%  
\TrackLangRegionMap{492}{MC}{MCO}%  
\TrackLangRegionMap{496}{MN}{MNG}%  
\TrackLangRegionMap{499}{ME}{MNE}%  
\TrackLangRegionMap{500}{MS}{MSR}%  
\TrackLangRegionMap{504}{MA}{MAR}%  
\TrackLangRegionMap{508}{MZ}{MOZ}%  
\TrackLangRegionMap{104}{MM}{MMR}%  
\TrackLangRegionMap{516}{NA}{NAM}%

\TrackLangRegionMap{520}{NR}{NRU}%  
\TrackLangRegionMap{524}{NP}{NPL}%  
\TrackLangRegionMap{528}{NL}{NLD}%  
\TrackLangRegionMap{540}{NC}{NCL}%  
\TrackLangRegionMap{554}{NZ}{NZL}%  
\TrackLangRegionMap{558}{NI}{NIC}%  
\TrackLangRegionMap{562}{NE}{NER}%  
\TrackLangRegionMap{566}{NG}{NGA}%  
\TrackLangRegionMap{570}{NU}{NIU}%  
\TrackLangRegionMap{574}{NF}{NFK}%  
\TrackLangRegionMap{580}{MP}{MNP}%  
\TrackLangRegionMap{578}{NO}{NOR}%  
\TrackLangRegionMap{512}{OM}{OMN}%  
\TrackLangRegionMap{586}{PK}{PAK}%  
\TrackLangRegionMap{585}{PW}{PLW}%  
\TrackLangRegionMap{275}{PS}{PSE}%  
\TrackLangRegionMap{591}{PA}{PAN}%  
\TrackLangRegionMap{598}{PG}{PNG}%  
\TrackLangRegionMap{600}{PY}{PRY}%  
\TrackLangRegionMap{604}{PE}{PER}%  
\TrackLangRegionMap{608}{PH}{PHL}%  
\TrackLangRegionMap{612}{PN}{PCN}%  
\TrackLangRegionMap{616}{PL}{POL}%  
\TrackLangRegionMap{620}{PT}{PRT}%  
\TrackLangRegionMap{630}{PR}{PRI}%  
\TrackLangRegionMap{634}{QA}{QAT}%  
\TrackLangRegionMap{638}{RE}{REU}%  
\TrackLangRegionMap{642}{RO}{ROU}%  
\TrackLangRegionMap{643}{RU}{RUS}%  
\TrackLangRegionMap{646}{RW}{RWA}%  
\TrackLangRegionMap{652}{BL}{BLM}%  
\TrackLangRegionMap{654}{SH}{SHN}%  
\TrackLangRegionMap{659}{KN}{KNA}%  
\TrackLangRegionMap{662}{LC}{LCA}%  
\TrackLangRegionMap{663}{MF}{MAF}%  
\TrackLangRegionMap{666}{PM}{SPM}%  
\TrackLangRegionMap{670}{VC}{VCT}%  
\TrackLangRegionMap{882}{WS}{WSM}%  
\TrackLangRegionMap{674}{SM}{SMR}%  
\TrackLangRegionMap{678}{ST}{STP}%  
\TrackLangRegionMap{682}{SA}{SAU}%  
\TrackLangRegionMap{686}{SN}{SEN}%  
\TrackLangRegionMap{688}{RS}{SRB}%  
\TrackLangRegionMap{690}{SC}{SYC}%  
\TrackLangRegionMap{694}{SL}{SLE}%  
\TrackLangRegionMap{702}{SG}{SGP}%  
\TrackLangRegionMap{534}{SX}{SXM}%  
\TrackLangRegionMap{703}{SK}{SVK}%  
\TrackLangRegionMap{705}{SI}{SVN}%  
\TrackLangRegionMap{090}{SB}{SLB}%

```

\TrackLangRegionMap{706}{SO}{SOM}%
\TrackLangRegionMap{710}{ZA}{ZAF}%
\TrackLangRegionMap{239}{GS}{SGS}%
\TrackLangRegionMap{728}{SS}{SSD}%
\TrackLangRegionMap{724}{ES}{ESP}%
\TrackLangRegionMap{144}{LK}{LKA}%
\TrackLangRegionMap{729}{SD}{SDN}%
\TrackLangRegionMap{740}{SR}{SUR}%
\TrackLangRegionMap{744}{SJ}{SJM}%
\TrackLangRegionMap{748}{SZ}{SWZ}%
\TrackLangRegionMap{752}{SE}{SWE}%
\TrackLangRegionMap{756}{CH}{CHE}%
\TrackLangRegionMap{760}{SY}{SYR}%
\TrackLangRegionMap{158}{TW}{TWN}%
\TrackLangRegionMap{762}{TJ}{TJK}%
\TrackLangRegionMap{834}{TZ}{TZA}%
\TrackLangRegionMap{764}{TH}{THA}%
\TrackLangRegionMap{626}{TL}{TLS}%
\TrackLangRegionMap{768}{TG}{TGO}%
\TrackLangRegionMap{772}{TK}{TKL}%
\TrackLangRegionMap{776}{TO}{TON}%
\TrackLangRegionMap{780}{TT}{TTO}%
\TrackLangRegionMap{788}{TN}{TUN}%
\TrackLangRegionMap{792}{TR}{TUR}%
\TrackLangRegionMap{795}{TM}{TKM}%
\TrackLangRegionMap{796}{TC}{TCA}%
\TrackLangRegionMap{798}{TV}{TUV}%
\TrackLangRegionMap{800}{UG}{UGA}%
\TrackLangRegionMap{804}{UA}{UKR}%
\TrackLangRegionMap{784}{AE}{ARE}%
\TrackLangRegionMap{826}{GB}{GBR}%
\TrackLangRegionMap{581}{UM}{UMI}%
\TrackLangRegionMap{840}{US}{USA}%
\TrackLangRegionMap{858}{UY}{URY}%
\TrackLangRegionMap{860}{UZ}{UZB}%
\TrackLangRegionMap{548}{VU}{VUT}%
\TrackLangRegionMap{862}{VE}{VEN}%
\TrackLangRegionMap{704}{VN}{VNM}%
\TrackLangRegionMap{092}{VG}{VGB}%
\TrackLangRegionMap{850}{VI}{VIR}%
\TrackLangRegionMap{876}{WF}{WLF}%
\TrackLangRegionMap{732}{EH}{ESH}%
\TrackLangRegionMap{887}{YE}{YEM}%
\TrackLangRegionMap{894}{ZM}{ZMB}%
\TrackLangRegionMap{716}{ZW}{ZWE}%

\@tracklang@input@extra@region@files
  Restore category code of @.
\@tracklang@regions@restore@at

```

## 6 ISO 15924 Scripts L<sup>A</sup>T<sub>E</sub>X Package (tracklang-scripts.sty)

This is just a L<sup>A</sup>T<sub>E</sub>X package wrapper for the generic code in tracklang-scripts.tex.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{tracklang-scripts}[2025/01/22 v1.6.3 (NLCT) Track
Language Scripts (LaTeX)]
\RequirePackage{tracklang}
\input{tracklang-scripts}
```

## 7 ISO 15924 Scripts Generic Code (tracklang-scripts.tex)

Provides information about ISO 15924 scripts. Not automatically loaded.

```
\ifnum\catcode'\@=11\relax
  \def\@tracklang@scripts@restore@at{}%
\else
  \expandafter\edef\csname @tracklang@scripts@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@}\relax
  }%
  \catcode'\@=11\relax
\fi
```

Check if this file has already been loaded:

```
\ifx\TrackLangScriptMap\undefined
\else
  \@tracklang@scripts@restore@at
  \expandafter\endinput
\fi
```

Version info.

```
\expandafter\def\csname ver@tracklang-scripts.tex\endcsname{%
2025/01/22 v1.6.3 (NLCT) Track Languages Scripts (Generic)}%
```

```
\TrackLangScriptMap{<letter
code>}{<number>}{<name>}{<direction>}{<parent>}
```

\TrackLangScriptMap

Define mapping. To avoid problems with encodings, only use ASCII characters in the arguments. The first argument is the four-letter ISO 15924 code. The second argument is the numeric code. The third argument is just intended for informational purposes. The fourth argument indicates the direction. This may be LR (left-to-right), RL (right-to-left), TB (top-to-bottom), *varies* or *inherited*. The *<parent>* argument is for the parent writing system, which may be left blank. (Currently, this is blank for all the mappings provided here, but the syntax has five arguments in case of future development.)

```
\def\TrackLangScriptMap#1#2#3#4#5{%
```

This user command is provided to make it easier to test the script using `\ifx`.

```

\@tracklang@enamedef{TrackLangScript#1}{#1}%
\@tracklang@enamedef{@tracklang@script@numtoalpha@#2}{#1}%
\@tracklang@enamedef{@tracklang@script@alphatonum@#1}{#2}%
\@tracklang@enamedef{@tracklang@script@alphatname@#1}{#3}%
\@tracklang@enamedef{@tracklang@script@alphatodir@#1}{#4}%
\ifx\relax#5\relax
\else
\@tracklang@enamedef{@tracklang@script@parent@#1}{#5}%
\fi
}

```

`\TrackLangScriptAlphaToNumeric`

```
\TrackLangScriptAlphaToNumeric{<alpha code>}
```

```

\def\TrackLangScriptAlphaToNumeric#1{%
\@tracklang@nameuse{@tracklang@script@alphatonum@#1}%
}%

```

`\TrackLangScriptIfKnownAlpha`

```
\TrackLangScriptIfKnownAlpha{<alpha code>}{<true>}{<false>}
```

```

\def\TrackLangScriptIfKnownAlpha#1#2#3{%
\@tracklang@ifundef{@tracklang@script@alphatonum@#1}%
{#3}%
{#2}%
}%

```

`\TrackLangScriptNumericToAlpha`

```
\TrackLangScriptNumericToAlpha{<numeric code>}
```

```

\def\TrackLangScriptNumericToAlpha#1{%
\@tracklang@nameuse{@tracklang@script@numtoalpha@#1}%
}%

```

`\TrackLangScriptIfKnownNumeric`

```
\TrackLangScriptIfKnownNumeric{<numeric code>}{<true>}{<false>}
```

```

\def\TrackLangScriptIfKnownNumeric#1#2#3{%
\@tracklang@ifundef{@tracklang@script@numtoalpha@#1}%

```



```
{#3}%  
{#2}%  
}%
```

```
\TrackLangScriptAlphaToName{alpha code}
```

\TrackLangScriptAlphaToName

```
\def\TrackLangScriptAlphaToName#1{%  
  \@tracklang@nameuse{@tracklang@script@alphatname@#1}%  
}%
```

```
\TrackLangScriptAlphaToDir{alpha code}
```

\TrackLangScriptAlphaToDir

```
\def\TrackLangScriptAlphaToDir#1{%  
  \@tracklang@nameuse{@tracklang@script@alphatodir@#1}%  
}%
```

I wasn't sure whether or not to implement a parent, but it's here if required. Unlike the other elements above, there's also a command to set this field.

```
\TrackLangScriptSetParent{alpha code}{parent alpha code}
```

\TrackLangScriptSetParent

```
\def\TrackLangScriptSetParent#1#2{%  
  \@tracklang@namedef{@tracklang@script@parent@#1}{#2}%  
}%
```

```
\TrackLangScriptGetParent{alpha code}
```

\TrackLangScriptGetParent

```
\def\TrackLangScriptGetParent#1{%  
  \@tracklang@nameuse{@tracklang@script@parent@#1}%  
}%
```

```
\TrackLangScriptIfHasParent{alpha code}{true}{false}
```

\TrackLangScriptIfHasParent

```
\def\TrackLangScriptIfHasParent#1#2#3{%
```

```

\@tracklang@ifundef{@tracklang@script@parent@#1}%
{#3}%
{#2}%
}%

```

Define mappings. The parent information is currently missing.

```

\TrackLangScriptMap{Adlm}{166}{Adlam}{RL}{}%
\TrackLangScriptMap{Afak}{439}{Afaka}{varies}{}%
\TrackLangScriptMap{Aghb}{239}{Caucasian Albanian}{LR}{}%
\TrackLangScriptMap{Ahom}{338}{Ahom, Tai Ahom}{LR}{}%
\TrackLangScriptMap{Arab}{160}{Arabic}{RL}{}%
\TrackLangScriptMap{Aran}{161}{Arabic (Nastaliq variant)}{RL}{}%
\TrackLangScriptMap{Armi}{124}{Imperial Aramaic}{RL}{}%
\TrackLangScriptMap{Armn}{230}{Armenian}{LR}{}%
\TrackLangScriptMap{Avst}{134}{Avestan}{RL}{}%
\TrackLangScriptMap{Bali}{360}{Balinese}{LR}{}%
\TrackLangScriptMap{Bamu}{435}{Bamum}{LR}{}%
\TrackLangScriptMap{Bass}{259}{Bassa Vah}{LR}{}%
\TrackLangScriptMap{Batk}{365}{Batak}{LR}{}%
\TrackLangScriptMap{Beng}{334}{Bhaiksuki}{LR}{}%
\TrackLangScriptMap{Blis}{550}{Blissymbols}{varies}{}%
\TrackLangScriptMap{Bopo}{285}{Bopomofo}{LR}{}%
\TrackLangScriptMap{Brah}{300}{Brahmi}{LR}{}%
\TrackLangScriptMap{Brai}{570}{Braille}{LR}{}%
\TrackLangScriptMap{Bugi}{367}{Buginese}{LR}{}%
\TrackLangScriptMap{Buhd}{372}{Buhid}{LR}{}%
\TrackLangScriptMap{Cakm}{349}{Chakma}{LR}{}%
\TrackLangScriptMap{Cans}{440}{Unified Canadian Aboriginal Syllabics}{LR}{}%
\TrackLangScriptMap{Cari}{201}{Carian}{LR}{}%
\TrackLangScriptMap{Cham}{358}{Cham}{LR}{}%
\TrackLangScriptMap{Cher}{445}{Cherokee}{LR}{}%
\TrackLangScriptMap{Cirt}{291}{Cirth}{varies}{}%
\TrackLangScriptMap{Copt}{204}{Coptic}{LR}{}%
\TrackLangScriptMap{Cprt}{403}{Cypriot}{RL}{}%
\TrackLangScriptMap{Cyr1}{220}{Cyrillic}{LR}{}%
\TrackLangScriptMap{Cyr2}{221}{Cyrillic (Old Church Slavonic variant)}{varies}{}%
\TrackLangScriptMap{Deva}{315}{Devanagari (Nagari)}{LR}{}%
\TrackLangScriptMap{Dsrt}{250}{Deseret (Mormon)}{LR}{}%
\TrackLangScriptMap{Dup1}{755}{Duployan shorthand, Duployan stenography}{LR}{}%
\TrackLangScriptMap{Egyd}{070}{Egyptian demotic}{RL}{}%
\TrackLangScriptMap{Egyh}{060}{Egyptian hieratic}{RL}{}%
\TrackLangScriptMap{Egyp}{050}{Egyptian hieroglyphs}{LR}{}%
\TrackLangScriptMap{Elba}{226}{Elbasan}{LR}{}%
\TrackLangScriptMap{Ethi}{430}{Ethiopic (Ge'ez)}{LR}{}%
\TrackLangScriptMap{Geok}{241}{Khutsuri (Asomtavruli and Nuskhuri)}{LR}{}%
\TrackLangScriptMap{Geor}{240}{Georgian (Mkhedruli)}{LR}{}%
\TrackLangScriptMap{Glag}{225}{Glagolitic}{LR}{}%
\TrackLangScriptMap{Goth}{206}{Gothic}{LR}{}%
\TrackLangScriptMap{Gran}{343}{Grantha}{LR}{}%
\TrackLangScriptMap{Grek}{200}{Greek}{LR}{}%

```

```

\TrackLangScriptMap{Gujr}{320}{Gujarati}{LR}{}%
\TrackLangScriptMap{Guru}{310}{Gurmukhi}{LR}{}%
\TrackLangScriptMap{Hanb}{503}{Han with Bopomofo (alias for Han + Bopomofo)}{LR}{}%
\TrackLangScriptMap{Hang}{286}{Hangul}{LR}{}%
\TrackLangScriptMap{Hani}{500}{Han (Hanzi, Kanji, Hanja)}{LR}{}%
\TrackLangScriptMap{Hano}{371}{Hanunoo}{LR}{}%
\TrackLangScriptMap{Hans}{501}{Han (Simplified variant)}{varies}{}%
\TrackLangScriptMap{Hant}{502}{Han (Traditional variant)}{varies}{}%
\TrackLangScriptMap{Hatr}{127}{Hatran}{RL}{}%
\TrackLangScriptMap{Hebr}{125}{Hebrew}{RL}{}%
\TrackLangScriptMap{Hira}{410}{Hiragana}{LR}{}%
\TrackLangScriptMap{Hluw}{080}{Anatolian Hieroglyphs (Luwian Hieroglyphs, Hittite Hieroglyphs)}{LR}{}%
\TrackLangScriptMap{Hmng}{450}{Pahawh Hmong}{LR}{}%
\TrackLangScriptMap{Hrkt}{412}{Japanese syllabaries (alias for Hiragana + Katakana)}{varies}{}%
\TrackLangScriptMap{Hung}{176}{Old Hungarian (Hungarian Runic)}{RL}{}%
\TrackLangScriptMap{Inds}{610}{Indus (Harappan)}{RL}{}%
\TrackLangScriptMap{Ital}{210}{Old Italic (Etruscan, Oscan, etc.)}{LR}{}%
\TrackLangScriptMap{Jamo}{284}{Jamo (alias for Jamo subset of Hangul)}{LR}{}%
\TrackLangScriptMap{Java}{361}{Javanese}{LR}{}%
\TrackLangScriptMap{Jpan}{413}{Japanese (alias for Han + Hiragana + Katakana)}{varies}{}%
\TrackLangScriptMap{Jurc}{510}{Jurchen}{LR}{}%
\TrackLangScriptMap{Kali}{357}{Kayah Li}{LR}{}%
\TrackLangScriptMap{Kana}{411}{Katakana}{LR}{}%
\TrackLangScriptMap{Khar}{305}{Kharoshthi}{RL}{}%
\TrackLangScriptMap{Khmr}{355}{Khmer}{LR}{}%
\TrackLangScriptMap{Khoj}{322}{Khojki}{LR}{}%
\TrackLangScriptMap{Kitl}{505}{Khitan large script}{LR}{}%
\TrackLangScriptMap{Kits}{288}{Khitan small script}{TB}{}%
\TrackLangScriptMap{Knda}{345}{Kannada}{LR}{}%
\TrackLangScriptMap{Kore}{287}{Korean (alias for Hangul + Han)}{LR}{}%
\TrackLangScriptMap{Kpel}{436}{Kpelle}{LR}{}%
\TrackLangScriptMap{Kthi}{317}{Kaithi}{LR}{}%
\TrackLangScriptMap{Lana}{351}{Tai Tham (Lanna)}{LR}{}%
\TrackLangScriptMap{Lao}{356}{Lao}{LR}{}%
\TrackLangScriptMap{Latf}{217}{Latin (Fraktur variant)}{varies}{}%
\TrackLangScriptMap{Latg}{216}{Latin (Gaelic variant)}{LR}{}%
\TrackLangScriptMap{Latn}{215}{Latin}{LR}{}%
\TrackLangScriptMap{Leke}{364}{Leke}{LR}{}%
\TrackLangScriptMap{Lepc}{335}{Lepcha}{LR}{}%
\TrackLangScriptMap{Limb}{336}{Limbu}{LR}{}%
\TrackLangScriptMap{Lina}{400}{Linear A}{LR}{}%
\TrackLangScriptMap{Linb}{401}{Linear B}{LR}{}%
\TrackLangScriptMap{Lisu}{399}{Lisu (Fraser)}{LR}{}%
\TrackLangScriptMap{Loma}{437}{Loma}{LR}{}%
\TrackLangScriptMap{Lyci}{202}{Lycian}{LR}{}%
\TrackLangScriptMap{Lydi}{116}{Lydian}{RL}{}%
\TrackLangScriptMap{Mahj}{314}{Mahajani}{LR}{}%
\TrackLangScriptMap{Mand}{140}{Mandaic, Mandaean}{RL}{}%
\TrackLangScriptMap{Mani}{139}{Manichaean}{RL}{}%
\TrackLangScriptMap{Marc}{332}{Marchen}{LR}{}%

```

```

\TrackLangScriptMap{Maya}{090}{Mayan hieroglyphs}{varies}{}%
\TrackLangScriptMap{Mend}{438}{Mende Kikakui}{RL}{}%
\TrackLangScriptMap{Merc}{101}{Meroitic Cursive}{RL}{}%
\TrackLangScriptMap{Mero}{100}{Meroitic Hieroglyphs}{RL}{}%
\TrackLangScriptMap{Mlym}{347}{Malayalam}{LR}{}%
\TrackLangScriptMap{Modi}{324}{Modi}{LR}{}%
\TrackLangScriptMap{Mong}{145}{Mongolian}{TB}{}%
\TrackLangScriptMap{Moon}{218}{Moon (Moon code, Moon script, Moon type)}{varies}{}%
\TrackLangScriptMap{Mroo}{199}{Mro, Mru}{LR}{}%
\TrackLangScriptMap{Mtei}{337}{Meitei Mayek (Meithei, Meetei)}{LR}{}%
\TrackLangScriptMap{Mult}{323}{Multani}{LR}{}%
\TrackLangScriptMap{Mymr}{350}{Myanmar (Burmese)}{LR}{}%
\TrackLangScriptMap{Narb}{106}{Old North Arabian (Ancient North Arabian)}{RL}{}%
\TrackLangScriptMap{Nbat}{159}{Nabataean}{RL}{}%
\TrackLangScriptMap{Newa}{333}{Newa, Newar, Newari}{LR}{}%
\TrackLangScriptMap{Nkgb}{420}{Nakhi Geba}{LR}{}%
\TrackLangScriptMap{Nkoo}{165}{N'Ko}{RL}{}%
\TrackLangScriptMap{Nshu}{499}{Nushu}{LR}{}%
\TrackLangScriptMap{Ogam}{212}{Ogham}{varies}{}%
\TrackLangScriptMap{Olck}{261}{Ol Chiki}{LR}{}%
\TrackLangScriptMap{Orkh}{175}{Old Turkic, Orkhon Runic}{RL}{}%
\TrackLangScriptMap{Orya}{327}{Oriya}{LR}{}%
\TrackLangScriptMap{Osge}{219}{Osage}{LR}{}%
\TrackLangScriptMap{Osma}{260}{Osmanya}{LR}{}%
\TrackLangScriptMap{Palm}{126}{Palmyrene}{RL}{}%
\TrackLangScriptMap{Pauc}{263}{Pau Cin Hau}{LR}{}%
\TrackLangScriptMap{Perm}{227}{Old Permic}{LR}{}%
\TrackLangScriptMap{Phag}{331}{Phags-pa}{TB}{}%
\TrackLangScriptMap{Phli}{131}{Inscriptional Pahlavi}{RL}{}%
\TrackLangScriptMap{Phlp}{132}{Psalter Pahlavi}{RL}{}%
\TrackLangScriptMap{Phlv}{133}{Book Pahlavi}{RL}{}%
\TrackLangScriptMap{Phnx}{115}{Phoenician}{RL}{}%
\TrackLangScriptMap{Piqd}{293}{Klingon (KLI plqaD)}{LR}{}%
\TrackLangScriptMap{Plrd}{282}{Miao (Pollard)}{LR}{}%
\TrackLangScriptMap{Prti}{130}{Inscriptional Parthian}{RL}{}%
\TrackLangScriptMap{Qaaa}{900}{Reserved for private use (start)}{varies}{}%
\TrackLangScriptMap{Qaai}{908}{Private use}{varies}{}%
\TrackLangScriptMap{Qabx}{949}{Reserved for private use (end)}{varies}{}%
\TrackLangScriptMap{Rjng}{363}{Rejang (Redjang, Kaganga)}{LR}{}%
\TrackLangScriptMap{Roro}{620}{Rongorongo}{varies}{}%
\TrackLangScriptMap{Runr}{211}{Runic}{LR}{}%
\TrackLangScriptMap{Samr}{123}{Samaritan}{RL}{}%
\TrackLangScriptMap{Sara}{292}{Saratii}{varies}{}%
\TrackLangScriptMap{Sarb}{105}{Old South Arabian}{RL}{}%
\TrackLangScriptMap{Saur}{344}{Saurashtra}{LR}{}%
\TrackLangScriptMap{Sgnw}{095}{SignWriting}{TB}{}%
\TrackLangScriptMap{Shaw}{281}{Shavian (Shaw)}{LR}{}%
\TrackLangScriptMap{Shrd}{319}{Sharada}{LR}{}%
\TrackLangScriptMap{Sidd}{302}{Siddham}{LR}{}%
\TrackLangScriptMap{Sind}{318}{Khudawadi, Sindhi}{LR}{}%

```

```

\TrackLangScriptMap{Sinh}{348}{Sinhala}{LR}{}%
\TrackLangScriptMap{Sora}{398}{Sora Sompeng}{LR}{}%
\TrackLangScriptMap{Sund}{362}{Sundanese}{LR}{}%
\TrackLangScriptMap{Sylo}{316}{Syloti Nagri}{LR}{}%
\TrackLangScriptMap{Syrç}{135}{Syriac}{RL}{}%
\TrackLangScriptMap{Syre}{138}{Syriac (Estrangelo variant)}{RL}{}%
\TrackLangScriptMap{Syrj}{137}{Syriac (Western variant)}{RL}{}%
\TrackLangScriptMap{Syrn}{136}{Syriac (Eastern variant)}{RL}{}%
\TrackLangScriptMap{Tagb}{373}{Tagbanwa}{LR}{}%
\TrackLangScriptMap{Takr}{321}{Takri}{LR}{}%
\TrackLangScriptMap{Tale}{353}{Tai Le}{LR}{}%
\TrackLangScriptMap{Talu}{354}{New Tai Lue}{LR}{}%
\TrackLangScriptMap{Taml}{346}{Tamil}{LR}{}%
\TrackLangScriptMap{Tang}{520}{Tangut}{LR}{}%
\TrackLangScriptMap{Tavt}{359}{Tai Viet}{LR}{}%
\TrackLangScriptMap{Telu}{340}{Telugu}{LR}{}%
\TrackLangScriptMap{Teng}{290}{Tengwar}{LR}{}%
\TrackLangScriptMap{Tfng}{120}{Tifinagh (Berber)}{LR}{}%
\TrackLangScriptMap{Tglg}{370}{Tagalog (Baybayin, Alibata)}{LR}{}%
\TrackLangScriptMap{Thaa}{170}{Thaana}{RL}{}%
\TrackLangScriptMap{Thai}{352}{Thai}{LR}{}%
\TrackLangScriptMap{Tibt}{330}{Tibetan}{LR}{}%
\TrackLangScriptMap{Tirh}{326}{Tirhuta}{LR}{}%
\TrackLangScriptMap{Ugar}{040}{Ugaritic}{LR}{}%
\TrackLangScriptMap{Vaii}{470}{Vai}{LR}{}%
\TrackLangScriptMap{Visp}{280}{Visible Speech}{LR}{}%
\TrackLangScriptMap{Wara}{262}{Warang Citi (Varang Kshiti)}{LR}{}%
\TrackLangScriptMap{Wole}{480}{Woleai}{RL}{}%
\TrackLangScriptMap{Xpeo}{030}{Old Persian}{LR}{}%
\TrackLangScriptMap{Xsux}{020}{Cuneiform, Sumero-Akkadian}{LR}{}%
\TrackLangScriptMap{Yiii}{460}{Yi}{LR}{}%
\TrackLangScriptMap{Zinh}{994}{Inherited script}{inherited}{}%
\TrackLangScriptMap{Zmth}{995}{Mathematical notation}{LR}{}%
\TrackLangScriptMap{Zsym}{996}{Symbols}{varies}{}%
\TrackLangScriptMap{Zsye}{993}{Symbols (emoji variant)}{varies}{}%
\TrackLangScriptMap{Zxxx}{997}{Unwritten documents}{varies}{}%
\TrackLangScriptMap{Zyyy}{998}{Undetermined script}{varies}{}%
\TrackLangScriptMap{Zzzz}{999}{Uncoded script}{varies}{}%

```

Load additional script files.

```
\@tracklang@input@extra@script@files
```

Restore category code of @.

```
\@tracklang@scripts@restore@at
```

## Change History

1.0 – 2014-09-29			
General: Initial release . . . . .	2		
1.1 – 2014-11-21			
\@tracklang@add@argentinespanish:			
new . . . . .	77		
\@tracklang@add@bolivianspanish:			
new . . . . .	77		
\@tracklang@add@chilianspanish:			
new . . . . .	77		
\@tracklang@add@columbianspanish:			
new . . . . .	77		
\@tracklang@add@costaricanspanish:			
new . . . . .	77		
\@tracklang@add@cubanspanish:			
new . . . . .	77		
\@tracklang@add@de-BE: new . . . . .	80		
\@tracklang@add@de-CH: new . . . . .	82		
\@tracklang@add@de-DE: new . . . . .	80		
\@tracklang@add@dominicanspanish:			
new . . . . .	77		
\@tracklang@add@ecudorianspanish:			
new . . . . .	78		
\@tracklang@add@elsalvadorspanish:			
new . . . . .	78		
\@tracklang@add@en-AU: new . . . . .	80		
\@tracklang@add@en-CA: new . . . . .	80		
\@tracklang@add@en-GB: new . . . . .	80		
\@tracklang@add@en-GG: new . . . . .	80		
\@tracklang@add@en-IM: new . . . . .	81		
\@tracklang@add@en-JE: new . . . . .	81		
\@tracklang@add@en-MT: new . . . . .	81		
\@tracklang@add@en-NZ: new . . . . .	80		
\@tracklang@add@en-US: new . . . . .	80		
\@tracklang@add@es-AR: new . . . . .	81		
\@tracklang@add@es-BO: new . . . . .	81		
\@tracklang@add@es-CL: new . . . . .	81		
\@tracklang@add@es-CO: new . . . . .	81		
\@tracklang@add@es-CR: new . . . . .	81		
\@tracklang@add@es-CU: new . . . . .	82		
\@tracklang@add@es-DO: new . . . . .	82		
\@tracklang@add@es-EC: new . . . . .	82		
\@tracklang@add@es-ES: new . . . . .	81		
\@tracklang@add@es-GT: new . . . . .	82		
\@tracklang@add@es-HN: new . . . . .	82		
\@tracklang@add@es-MX: new . . . . .	82		
\@tracklang@add@es-NI: new . . . . .	82		
\@tracklang@add@es-PA: new . . . . .	82		
\@tracklang@add@es-PE: new . . . . .	82		
\@tracklang@add@es-PR: new . . . . .	82		
\@tracklang@add@es-PY: new . . . . .	82		
\@tracklang@add@es-SV: new . . . . .	82		
\@tracklang@add@es-UY: new . . . . .	82		
\@tracklang@add@es-VE: new . . . . .	82		
\@tracklang@add@fr-BE: new . . . . .	80		
\@tracklang@add@fr-CA: new . . . . .	80		
\@tracklang@add@fr-CH: new . . . . .	82		
\@tracklang@add@fr-FR: new . . . . .	80		
\@tracklang@add@fr-GG: new . . . . .	80		
\@tracklang@add@fr-JE: new . . . . .	81		
\@tracklang@add@france: new . . . . .	73		
\@tracklang@add@guatemalanspanish:			
new . . . . .	78		
\@tracklang@add@guernseyenglish:			
new . . . . .	75		
\@tracklang@add@guernseyfrench:			
new . . . . .	75		
\@tracklang@add@honduranspanish:			
new . . . . .	78		
\@tracklang@add@isleofmanenglish:			
new . . . . .	76		
\@tracklang@add@it-CH: new . . . . .	83		
\@tracklang@add@it-HR: new . . . . .	80		
\@tracklang@add@it-IT: new . . . . .	80		
\@tracklang@add@it-SI: new . . . . .	81		
\@tracklang@add@it-SM: new . . . . .	81		
\@tracklang@add@it-VA: new . . . . .	83		
\@tracklang@add@jerseyenglish:			
new . . . . .	75		
\@tracklang@add@jerseyfrench:			
new . . . . .	75		
\@tracklang@add@maltaenglish:			
new . . . . .	76		
\@tracklang@add@maltamaltese:			
new . . . . .	76		
\@tracklang@add@maltese: new . . . . .	64		
\@tracklang@add@manx: new . . . . .	64		
\@tracklang@add@mexicanspanish:			
new . . . . .	78		
\@tracklang@add@mt-MT: new . . . . .	81		
\@tracklang@add@netherlands:			
new . . . . .	73		
\@tracklang@add@ngermanDE:			
new . . . . .	74		

\@tracklang@add@nicaraguanspanish:	removed hard-coded
new	polyglossia language list . . . . 3
\@tracklang@add@nl-BE: new	. 80
\@tracklang@add@nl-NL: new	. 81
\@tracklang@add@panamaspanish:	
new	. 78
\@tracklang@add@paraguayspanish:	
new	. 78
\@tracklang@add@peruvianspanish:	
new	. 78
\@tracklang@add@portugal: new	76
\@tracklang@add@pt-BR: new	. 80
\@tracklang@add@pt-PT: new	. 81
\@tracklang@add@puertoricospanish:	
new	. 78
\@tracklang@add@rm-CH: new	. 83
\@tracklang@add@sl-SI: new	. 81
\@tracklang@add@spainspanish:	
new	. 77
\@tracklang@add@swissfrench:	
new	. 78
\@tracklang@add@swissgerman:	
new	. 78
\@tracklang@add@swissitalian:	
new	. 78
\@tracklang@add@swissromansh:	
new	. 79
\@tracklang@add@uruguayspanish:	
new	. 78
\@tracklang@add@venezuelanspanish:	
new	. 78
\@tracklang@declareoption:	
new	. 56
\LetTrackLangOption: new	. . . 79
1.2 – 2015-03-23	
\@tracklang@add@GBirish: new	75
\@tracklang@add@IEenglish:	
new	. 75
\@tracklang@add@IEirish: new	75
\@tracklang@add@en-IE: new	. 83
\@tracklang@add@ga-GB: new	. 83
\@tracklang@add@ga-IE: new	. 83
1.3 – 2016-10-07	
General: added check for @	
category code	. . . . . 7
added test for german.sty	. . . . 3
added	
tracklang-region-codes.tex	. 135
added tracklang-scripts.sty	. . 143
added tracklang-scripts.tex	. . 143
\@TrackLangRequestResource:	
new	. . . . . 131
\@TrackLangRequireDialect:	
new	. . . . . 132
\@TrackLangRequireResource:	
new	. . . . . 130
\@TrackLangRequireResourceOrDo:	
new	. . . . . 130
\@tracklang@add@GBscottish:	
new	. . . . . 77
\@tracklang@add@GBwelsh: new	79
\@tracklang@add@abkhaz: new	. 57
\@tracklang@add@afar: new	. . 57
\@tracklang@add@akan: new	. . 57
\@tracklang@add@aragonese:	
new	. . . . . 57
\@tracklang@add@assamese: new	57
\@tracklang@add@avaric: new	. 57
\@tracklang@add@avestan: new	57
\@tracklang@add@aymara: new	. 57
\@tracklang@add@azerbaijani:	
new	. . . . . 58
\@tracklang@add@bambara: new	58
\@tracklang@add@bashkir: new	58
\@tracklang@add@belarusian:	
new	. . . . . 58
\@tracklang@add@berber: new	. 58
\@tracklang@add@bihari: new	. 58
\@tracklang@add@bislama: new	58
\@tracklang@add@bokmal: new	. 58
\@tracklang@add@bosnian: new	58
\@tracklang@add@burmese: new	59
\@tracklang@add@chamorro: new	59
\@tracklang@add@chechen: new	59
\@tracklang@add@chichewa: new	59
\@tracklang@add@chinese: new	59
\@tracklang@add@churchslavonic:	
new	. . . . . 59
\@tracklang@add@chuvash: new	59
\@tracklang@add@cornish: new	59
\@tracklang@add@corsican: new	59
\@tracklang@add@cree: new	. . 59
\@tracklang@add@cy-GB: new	. 83
\@tracklang@add@de-AT: new	. 83
\@tracklang@add@de-AT-1996:	
new	. . . . . 83

\@tracklang@add@de-CH-1996:		\@tracklang@add@limburgish:	
new .....	83	new .....	63
\@tracklang@add@de-DE-1996:		\@tracklang@add@lingala: new	63
new .....	83	\@tracklang@add@lubakatanga:	
\@tracklang@add@dzongkha: new	60	new .....	63
\@tracklang@add@easternpunjabi:		\@tracklang@add@luxembourgish:	
new .....	60	new .....	63
\@tracklang@add@ewe: new	60	\@tracklang@add@macedonian:	
\@tracklang@add@faroeese: new	60	new .....	63
\@tracklang@add@fijian: new	60	\@tracklang@add@malagasy: new	64
\@tracklang@add@fula: new	60	\@tracklang@add@maori: new	64
\@tracklang@add@ganda: new	60	\@tracklang@add@marshallese:	
\@tracklang@add@gd-GB: new	83	new .....	64
\@tracklang@add@georgian: new	61	\@tracklang@add@mongolian:	
\@tracklang@add@germanDE: new	74	new .....	64
\@tracklang@add@germanb: new	74	\@tracklang@add@ms-MY: new	83
\@tracklang@add@guarani: new	61	\@tracklang@add@nauruan: new	64
\@tracklang@add@gujarati: new	61	\@tracklang@add@naustrian:	
\@tracklang@add@haitian: new	61	added modifier .....	73
\@tracklang@add@hausa: new	61	\@tracklang@add@navajo: new	64
\@tracklang@add@herero: new	61	\@tracklang@add@nbelgiangerman:	
\@tracklang@add@hirimotu: new	61	new .....	74
\@tracklang@add@hr-HR: new	83	\@tracklang@add@ndonga: new	64
\@tracklang@add@hu-HU: new	83	\@tracklang@add@nepali: new	64
\@tracklang@add@id-IN: new	83	\@tracklang@add@ngerman:	
\@tracklang@add@ido: new	61	added modifier .....	74
\@tracklang@add@igbo: new	61	\@tracklang@add@ngermanDE:	
\@tracklang@add@interlingue:		added modifier .....	74
new .....	61	\@tracklang@add@ngermanb: new	74
\@tracklang@add@inuktitut:		\@tracklang@add@northernndebele:	
new .....	62	new .....	64
\@tracklang@add@inupiaq: new	62	\@tracklang@add@northernsotho:	
\@tracklang@add@japanese: new	62	new .....	65
\@tracklang@add@javanese: new	62	\@tracklang@add@nswissgerman:	
\@tracklang@add@kalaallisut:		new .....	78
new .....	62	\@tracklang@add@nuosu: new	65
\@tracklang@add@kanuri: new	62	\@tracklang@add@ojibwe: new	65
\@tracklang@add@kashmiri: new	62	\@tracklang@add@oriya: new	65
\@tracklang@add@kazakh: new	62	\@tracklang@add@oromo: new	65
\@tracklang@add@khmer: new	62	\@tracklang@add@ossetian: new	65
\@tracklang@add@kikuyu: new	62	\@tracklang@add@pali: new	65
\@tracklang@add@kinyarwanda:		\@tracklang@add@pashto: new	65
new .....	62	\@tracklang@add@polutoniko:	
\@tracklang@add@kirundi: new	62	added modifier .....	76
\@tracklang@add@komi: new	62	\@tracklang@add@polutonikogreek:	
\@tracklang@add@kongo: new	63	added modifier .....	76
\@tracklang@add@korean: new	63	\@tracklang@add@quechua: new	65
\@tracklang@add@kurdish: new	63	\@tracklang@add@samoan: new	66
\@tracklang@add@kwanyama: new	63	\@tracklang@add@sango: new	66
\@tracklang@add@kyrgyz: new	63		



\@tracklang@add@sardinian:	\@tracklang@hasthirdchar: new	37
new	\@tracklang@ifalldigits: new	39
\@tracklang@add@serbianc: new	\@tracklang@ifalpha: new	38
\@tracklang@add@serbianl: new	\@tracklang@ifalphanumeric:	
\@tracklang@add@shona: new	new	39
\@tracklang@add@sindhi: new	\@tracklang@ifdigit: new	38
\@tracklang@add@sinhalese:	\@tracklang@iflanguage@ii@tag:	
new	new	40
\@tracklang@add@sloveneistriasslovenian	\@tracklang@iflanguage@iii@tag:	
fixed root language name	new	41
\@tracklang@add@somali: new	\@tracklang@ifregion@ii@tag:	
\@tracklang@add@southernndebele:	new	42
new	\@tracklang@ifregion@iii@tag:	
\@tracklang@add@southernsotho:	new	42
new	\@tracklang@ifscripttag: new	43
\@tracklang@add@sudanese: new	\@tracklang@ifundef: added	
\@tracklang@add@swahili: new	check for \ifc\$name	8
\@tracklang@add@swati: new	\@tracklang@ifvariant@iv@tag:	
\@tracklang@add@tagalog: new	new	44
\@tracklang@add@tahitian: new	\@tracklang@info: new	11
\@tracklang@add@tajik: new	\@tracklang@known@langs: new	24
\@tracklang@add@tatar: new	\@tracklang@locale@c: new	13
\@tracklang@add@tigrinya: new	\@tracklang@locale@posix: new	13
\@tracklang@add@tonga: new	\@tracklang@nameuse: added	
\@tracklang@add@tsonga: new	check for undef	9
\@tracklang@add@tswana: new	\@tracklang@parse@langtag:	
\@tracklang@add@twi: new	new	46
\@tracklang@add@usorbian:	\@tracklang@parse@locale: new	18
corrected ISO 639-1 code	\@tracklang@parse@track@locale:	
\@tracklang@add@uyghur: new	new	53
\@tracklang@add@uzbek: new	\@tracklang@parseenv: new	21
\@tracklang@add@venda: new	\@tracklang@sanitize: new	10
\@tracklang@add@volapuk: new	\@tracklang@secondoftwo: new	10
\@tracklang@add@westernfrisian:	\@tracklang@split@hyphen: new	20
new	\@tracklang@split@otherunderscore:	
\@tracklang@add@wolof: new	new	20
\@tracklang@add@xhosa: new	\@tracklang@split@underscore:	
\@tracklang@add@yiddish: new	new	19
\@tracklang@add@yoruba: new	\@tracklang@split@underscoreorhyp:	
\@tracklang@add@zhuang: new	new	19
\@tracklang@add@zulu: new	\@tracklang@track@locale: new	53
\@tracklang@addtohook: new	\@tracklang@warn: new	11
\@tracklang@enamedef: new	\AddTrackedCountryIsoCode:	
\@tracklang@firstoftwo: new	new	36
\@tracklang@hasfifthchar: new	\AddTrackedLanguageIsoCodes:	
\@tracklang@hasfourthchar:	new	36
new	\GetTrackedDialectAdditional:	
\@tracklang@hasninthchar: new	new	32
\@tracklang@hassecondchar:	\GetTrackedDialectFromLanguageTag:	
new	new	49

\GetTrackedDialectFromMapping:		\ThreeLetterExtIsoLanguageCode:	
new .....	129	new .....	29
\GetTrackedDialectModifier:		\TrackLangAddToCaptions: new	127
new .....	29	\TrackLangAddToHook: new ...	125
\GetTrackedDialectScript: new	29	\TrackLangAlphaIIIToNumericRegion:	
\GetTrackedDialectSubLang:		new .....	137
new .....	31	\TrackLangAlphaIIToNumericRegion:	
\GetTrackedDialectToMapping:		new .....	136
new .....	129	\TrackLangDeclareDialectOption:	
\GetTrackedDialectVariant:		new .....	72
new .....	31	\TrackLangDeclareLanguageOption:	
\GetTrackedLanguageTag: new	32	new .....	56
\IfHasTrackedDialectAdditional:		\TrackLangFromEnv: new ....	52
new .....	32	\TrackLangGetDefaultScript:	
\IfHasTrackedDialectModifier:		new .....	27
new .....	29	\TrackLangGetKnownCountry:	
\IfHasTrackedDialectScript:		new .....	27
new .....	30	\TrackLangGetKnownIsoThreeLetterLang:	
\IfHasTrackedDialectSubLang:		new .....	26
new .....	31	\TrackLangGetKnownIsoThreeLetterLangB:	
\IfHasTrackedDialectVariant:		new .....	26
new .....	31	\TrackLangGetKnownIsoTwoLetterLang:	
\IfTrackedDialectHasMapping:		new .....	25
new .....	128	\TrackLangGetKnownLangFromIso:	
\IfTrackedDialectIsScriptCs:		new .....	26
new .....	30	\TrackLangIfAlphaNumericChar:	
\ifTrackLangShowInfo: new ..	11	new .....	39
\ifTrackLangShowWarnings: new	10	\TrackLangIfHasDefaultScript:	
\LetTrackLangSynonym: new ..	79	new .....	27
\noop@TrackLangRequestResource:		\TrackLangIfHasKnownCountry:	
new .....	131	new .....	27
\noop@TrackLangRequireDialect:		\TrackLangIfKnownAlphaIIRegion:	
new .....	131	new .....	137
\noop@TrackLangRequireResource:		\TrackLangIfKnownAlphaIRegion:	
new .....	129	new .....	136
\noop@TrackLangRequireResourceOrDo:		\TrackLangIfKnownIsoThreeLetterLang:	
new .....	130	new .....	25
\SetCurrentTrackedDialect:		\TrackLangIfKnownIsoThreeLetterLangB:	
new .....	33	new .....	26
\SetTrackedDialectAdditional:		\TrackLangIfKnownIsoTwoLetterLang:	
new .....	31	new .....	25
\SetTrackedDialectLabelMap:		\TrackLangIfKnownLang: new ..	25
new .....	128	\TrackLangIfKnownLangFromIso:	
\SetTrackedDialectModifier:		new .....	26
new .....	29	\TrackLangIfKnownNumericRegion:	
\SetTrackedDialectScript: new	29	new .....	137
\SetTrackedDialectSubLang:		\TrackLangIfLanguageTag: new	40
new .....	31	\TrackLangIfRegionTag: new ..	41
\SetTrackedDialectVariant:		\TrackLangIfScriptTag: new ..	42
new .....	30	\TrackLangIfVariantTag: new ..	43

\TrackLangNewLanguage: new .	24	\TrackLangProvidePredefinedDialect:	
\TrackLangNumericToAlphaIIRegion:		fixed mapping order . . . . .	72
new . . . . .	137	1.3.4 – 2017-03-25	
\TrackLangNumericToAlphaIIRegion:		\@tracklang@add@furlan: new .	74
new . . . . .	136	\@tracklang@add@kurmanji: new	74
\TrackLangParseFromEnv: new .	18	\@tracklang@err: fixed typo in	
\TrackLangProvidesResource:		\errhelp command name . .	10
new . . . . .	124	\@tracklang@pkgwarn: new . . .	10
\TrackLangQueryEnv: new . .	15, 16	1.3.5 – 2018-02-21	
\TrackLangQueryOtherEnv:		General: check for \xpg@loaded .	3
new . . . . .	15, 17	1.3.6 – 2018-05-13	
\TrackLangRegionMap: new . . .	136	\@tracklang@fullmatch: new .	52
\TrackLangRequestResource:		\GetTrackedDialectFromLanguageTag:	
new . . . . .	131	added	
\TrackLangRequireDialect:		\TrackedDialectClosestSubMatch	
new . . . . .	131	. . . . .	49
\TrackLangRequireResource:		1.3.7 – 2019-08-31	
new . . . . .	129	General: corrected misspelt	
\TrackLangRequireResourceOrDo:		command . . . . .	4, 6
new . . . . .	130	1.3.8 – 2019-10-06	
\TrackLangScriptAlphaToDir:		\@tracklang@add@nil: new . . .	79
new . . . . .	145	\@tracklang@add@undetermined:	
\TrackLangScriptAlphaToName:		new . . . . .	68
new . . . . .	145	\@tracklang@prelangpkgcheck@hook:	
\TrackLangScriptAlphaToNumeric:		new . . . . .	2
new . . . . .	144	1.3.9 – 2019-11-11	
\TrackLangScriptGetParent:		\@TrackIfKnownLanguage: new .	46
new . . . . .	145	\TrackIfKnownLanguage: new .	46
\TrackLangScriptIfHasParent:		1.4 – 2019-11-30	
new . . . . .	145	General: input extra regions if	
\TrackLangScriptIfKnownAlpha:		provided . . . . .	142
new . . . . .	144	new . . . . .	149
\TrackLangScriptIfKnownNumeric:		removed some spurious empty	
new . . . . .	144	braces and commented out	
\TrackLangScriptMap: new . . .	143	EOL . . . . .	146
\TrackLangScriptNumericToAlpha:		\@tracklang@firstoftwo: made	
new . . . . .	144	long . . . . .	10
\TrackLangScriptSetParent:		\@tracklang@ifcseqcsname: new	10
new . . . . .	145	\@tracklang@input@extra@region@filelist:	
\TrackLanguageTag: new . . . . .	45	new . . . . .	48
\TrackLocale: new . . . . .	52	\@tracklang@input@extra@region@files:	
1.3.2 – 2016-10-11		new . . . . .	49
\@tracklang@tryshellescape:		\@tracklang@input@extra@script@filelist:	
added check if \shellescape		new . . . . .	49
has been set to \relax . . . .	13	\@tracklang@input@extra@script@files:	
1.3.3 – 2016-11-03		new . . . . .	49
\IfHookHasMappingFromTrackedDialect:		\@tracklang@redefhook: new .	128
new . . . . .	129	\@tracklang@secondoftwo: made	
\SetCurrentTrackedDialect:		long . . . . .	10
fixed mapping . . . . .	33		

\@tracklang@test@if@file@exists@for@dialect@tracklang@test@if@file@exists@for@langIskipscriptregion:	new	89	new	107
\@tracklang@test@if@file@exists@for@langIskipscriptskipregion:	new	115	new	108
\@tracklang@test@if@file@exists@for@langIvariant:	new	116	new	118
\@tracklang@test@if@file@exists@for@langIvariant:	new	106	new	117
\@tracklang@test@if@file@exists@for@langIvariant@notregiononly:	new	100	new	117
\@tracklang@test@if@file@exists@for@langIvariant@region:	new	95	new	117
\@tracklang@test@if@file@exists@for@langIvariant@rootlang:	new	114	new	119
\@tracklang@test@if@file@exists@for@langIvariant@tag:	new	105	new	89
\@tracklang@test@if@file@exists@for@langIvariant@noop:	new	101	new	89
\@tracklang@test@if@file@exists@for@langIvariant@new	new	113	new	11
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	114	\IfTrackedLanguageFileExists:	86
\@tracklang@test@if@file@exists@for@langIvariant@orig:	new	119	\IfTrackedLanguageFileExists@orig:	120
\@tracklang@test@if@file@exists@for@langIvariant@omitDialectLabel:	new	103, 104	\IfTrackedLanguageFileExistsOmitDialectLabel:	89
\@tracklang@test@if@file@exists@for@langIvariant@omitOnlyRegion:	new	98	\IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion:	88
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	93	\IfTrackedLanguageFileExistsOmitOnlyRegion:	87
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	111	\ifTrackLangShowVerbose: new	11
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	103	\IfTrackedLanguageFileExists@orig: regionFile:	48
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	103	\IfTrackedLanguageFileExists@orig: ExtraScriptFile:	49
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	99	\IfTrackedLanguageFileExists@orig: ProvidePredefinedDialect:	69
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	110	\IfTrackedLanguageFileExists@orig: ProvidePredefinedLanguage:	56
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	111	\IfTrackedLanguageFileExists@orig: ProvidePredefinedRegion:	127
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	118	\IfTrackedLanguageFileExists@orig: AddToHook: removed	redundant code and added
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	91	\IfTrackedLanguageFileExists@orig: IsScriptRegion:	126
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	108	\IfTrackedLanguageFileExists@orig: TrackLangRedefHook: removed	added
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	101	\IfTrackedLanguageFileExists@orig: IsScriptRegion:	127
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	97	\IfTrackedLanguageFileExists@orig: verbose message	127
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	101	\IfTrackedLanguageFileExists@orig: removed spurious code block	116
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	97	\IfTrackedLanguageFileExists@orig: added verbose messages	120

1.6 – 2022-10-29		\@tracklang@input: added	
General: added check for		\@tracklang@inputfile . . . . .	8
\xpg@bcp@loaded . . . . .	3	\@tracklang@regions: new . . . . .	22
\TrackLangQueryEnv: changed \x		\@tracklang@test@if@file@exists@for@langIIregion:	
to \@tracklang@x . . . . .	15	bug fix: check region not	
1.6.1 – 2022-12-13		script . . . . .	106
\TrackLangEncodingName: new . . . . .	12	\@tracklang@test@if@file@exists@for@langIIregion:	
1.6.2 – 2025-01-14		bug fix: check region not	
\@tracklang@add@scots: new . . . . .	66	script . . . . .	103, 104
1.6.3 – 2025-01-22		\@tracklang@test@if@file@exists@for@notdialectlabel:	
General: added [no]verbose		new . . . . .	90
package options . . . . .	2	\AnyTrackedRegions: new . . . . .	85
\@@TrackLang@RequireDialect:		\ForEachTrackedRegion: new . . . . .	85
new . . . . .	132	\IfTrackedLanguageFileExistsOmitDialectLabel:	
\@@tracklang@test@if@file@exists@for@dialect:		new . . . . .	88
new . . . . .	89	\IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion:	
\@@tracklang@test@if@file@exists@for@region:		new . . . . .	87
new . . . . .	117	\IfTrackedLanguageFileExistsOmitOnlyRegion:	
\@TrackLangRequireDialectOmitDialectLabel:		new . . . . .	87
new . . . . .	133	\TrackLangRequireDialectOmitDialectLabel:	
\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion:		new . . . . .	133
new . . . . .	134	\TrackLangRequireDialectOmitLabelOmitOnlyRegion:	
\@TrackLangRequireDialectOmitOnlyRegion:		new . . . . .	134
new . . . . .	135	\TrackLangRequireDialectOmitOnlyRegion:	
		new . . . . .	134

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols	
\-	20
\@	7, 21, 135, 143
\@@	9
\@@TrackLang@RequireDialect	132, 132, 133–135
\@@TrackLang@RequireDialect	132
\@@TrackLang@RequireDialectOmitDialectLabel	133, 133
\@@TrackLang@RequireDialectOmitDialectLabelOmitOnlyRegion	133, 134, 134
\@@TrackLang@RequireDialectOmitOnlyRegion	133, 134, 135
\@input	8
\@tracklang@checklocale	13, 13
\@tracklang@ifalldigits	39, 39
\@tracklang@split@hyphen	20
\@tracklang@split@otherunderscore	20
\@tracklang@split@underscore	20
\@tracklang@test@if@file@exists@for@direct	86–89, 89
\@tracklang@test@if@file@exists@for@region	37, 40, 41, 43, 44
\@TrackIfKnownLanguage	46, 46
\@TrackLangAddToHook	125, 132
\@TrackLangEnvAdditional	19, 47, 48, 55
\@TrackLangEnvCodeSet	18, 19, 21, 47, 52
\@TrackLangEnvFirstSubLang	19, 44, 47, 54
\@TrackLangEnvLang	18, 19, 46, 47, 50, 52–55
\@TrackLangEnvModifier	18, 19, 47, 50, 52–55
\@TrackLangEnvScript	19, 47, 50, 53–55
\@TrackLangEnvSubLang	19, 44, 47, 50, 51, 53–55
\@TrackLangEnvTerritory	18, 19, 47, 48, 50–55
\@TrackLangEnvVariant	19, 45, 47, 50, 51, 53–55
\@TrackLangRedefHook	127
\@TrackLangRequestResource	131, 132
\@TrackLangRequireDialect	131, 132, 133
\@TrackLangRequireDialectOmitDialectLabel	133, 133
\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion	133, 134, 134
\@TrackLangRequireDialectOmitOnlyRegion	133, 134, 135
\@TrackLangRequireResourceOrDo	130, 132
\@TrackLanguageTag	45, 45
\@after	22
\@before	22
\@declaredoptions	2
\@empty	3
\@end@tracklang@hasfifthchar	38, 43
\@end@tracklang@hasfourthchar	.
\@end@tracklang@hasninthchar	38, 44
\@end@tracklang@hassecondchar	37, 40, 42
\@end@tracklang@hasthirdchar	37, 40, 41, 47, 54
\@filef@und	12
\@for	3–6, 8, 9
\@fortmp	8, 9
\@gobble	2
\@ifpackageloaded	3, 5
\@ifundefined	3–6
\@namedef	5, 6, 9
\@nameuse	4–7
\@nil	8, 9, 22
\@nnil	8
\@noop@TrackLangRequireDialect	131
\@onelevel@sanitize	10
\@org@tracklang@add@latex	4
\@tracklang@if@file@exists	12, 89–123, 130, 131

\@tracklang@add 22, 23, 24, 28, 48, 49	\@tracklang@add@Spanish	6
\@tracklang@add@Acadian	\@tracklang@add@Swedish	6
\@tracklang@add@Afrikaans	\@tracklang@add@Turkish	6
\@tracklang@add@AmericanEnglish	\@tracklang@add@UKenglish	79
\@tracklang@add@Austrian	\@tracklang@add@USenglish	79
\@tracklang@add@Bahasa	\@tracklang@add@Ukrainian	6
\@tracklang@add@Basque	\@tracklang@add@UpperSorbian	6
\@tracklang@add@Brazilian	\@tracklang@add@Welsh	6
\@tracklang@add@Breton	\@tracklang@add@abkhaz	57
\@tracklang@add@BritishEnglish	\@tracklang@add@acadian	5, 72
\@tracklang@add@Bulgarian	\@tracklang@add@afar	57
\@tracklang@add@Canadian	\@tracklang@add@afrikaans	5, 57
\@tracklang@add@Canadien	\@tracklang@add@akan	57
\@tracklang@add@Catalan	\@tracklang@add@albanian	57
\@tracklang@add@Croatian	\@tracklang@add@american	5, 72
\@tracklang@add@Czech	\@tracklang@add@amharic	57
\@tracklang@add@Danish	\@tracklang@add@anglosaxon	57
\@tracklang@add@Dutch	\@tracklang@add@apache	57
\@tracklang@add@English	\@tracklang@add@arabic	57
\@tracklang@add@Esperanto	\@tracklang@add@aragonese	57
\@tracklang@add@Estonian	\@tracklang@add@argentinespanish	77
\@tracklang@add@Finnish	.....	77
\@tracklang@add@French	\@tracklang@add@armenian	57
\@tracklang@add@GBirish	\@tracklang@add@assamese	57
\@tracklang@add@GBscottish	\@tracklang@add@asturian	57
\@tracklang@add@GBwelsh	\@tracklang@add@australian	72
\@tracklang@add@Galician	\@tracklang@add@austrian	5, 72
\@tracklang@add@German	\@tracklang@add@avaric	57
\@tracklang@add@Greek	\@tracklang@add@avestan	57
\@tracklang@add@Hebrew	\@tracklang@add@aymara	57
\@tracklang@add@Hungarian	\@tracklang@add@azerbaijani	58
\@tracklang@add@IEenglish	\@tracklang@add@bahasa	5, 73
\@tracklang@add@IEirish	\@tracklang@add@bahasai	58
\@tracklang@add@Icelandic	\@tracklang@add@bahasam	58
\@tracklang@add@Irish	\@tracklang@add@bambara	58
\@tracklang@add@Italian	\@tracklang@add@bashkir	58
\@tracklang@add@Latin	\@tracklang@add@basque	5, 58
\@tracklang@add@LowerSorbian	\@tracklang@add@belarusian	58
\@tracklang@add@Magyar	\@tracklang@add@belgiangerman	74
\@tracklang@add@Norsk	\@tracklang@add@belgique	74
\@tracklang@add@Nynorsk	\@tracklang@add@bengali	58
\@tracklang@add@Polish	\@tracklang@add@berber	58
\@tracklang@add@Polutoniko	\@tracklang@add@bihari	58
\@tracklang@add@Portuguese	\@tracklang@add@bislama	58
\@tracklang@add@Romanian	\@tracklang@add@bokmal	58
\@tracklang@add@Russian	\@tracklang@add@bolivianspanish	77
\@tracklang@add@Scottish	\@tracklang@add@bosnian	58
\@tracklang@add@Serbian	\@tracklang@add@brazil	5, 73
\@tracklang@add@Slovak	\@tracklang@add@brazilian	73
\@tracklang@add@Slovene	\@tracklang@add@breton	5, 58

\@tracklang@add@british	5, 73	\@tracklang@add@en-IE	83
\@tracklang@add@bulgarian	5, 58	\@tracklang@add@en-IM	81
\@tracklang@add@burmese	59	\@tracklang@add@en-JE	81
\@tracklang@add@canadian	5, 73	\@tracklang@add@en-MT	81
\@tracklang@add@canadien	5, 73	\@tracklang@add@en-NZ	80
\@tracklang@add@catalan	5, 59	\@tracklang@add@en-US	80
\@tracklang@add@chamorro	59	\@tracklang@add@english	5, 60
\@tracklang@add@chechen	59	\@tracklang@add@es-AR	81
\@tracklang@add@chichewa	59	\@tracklang@add@es-BO	81
\@tracklang@add@chilianspanish	77	\@tracklang@add@es-CL	81
\@tracklang@add@chinese	59	\@tracklang@add@es-CO	81
\@tracklang@add@churchslavonic	59	\@tracklang@add@es-CR	81
\@tracklang@add@chuvash	59	\@tracklang@add@es-CU	82
\@tracklang@add@columbianspanish		\@tracklang@add@es-DO	82
.....	77	\@tracklang@add@es-EC	82
\@tracklang@add@coptic	59	\@tracklang@add@es-ES	81
\@tracklang@add@cornish	59	\@tracklang@add@es-GT	82
\@tracklang@add@corsican	59	\@tracklang@add@es-HN	82
\@tracklang@add@costaricanspanish		\@tracklang@add@es-MX	82
.....	77	\@tracklang@add@es-NI	82
\@tracklang@add@cree	59	\@tracklang@add@es-PA	82
\@tracklang@add@croatia	73	\@tracklang@add@es-PE	82
\@tracklang@add@croatian	5, 59	\@tracklang@add@es-PR	82
\@tracklang@add@cubanspanish	77	\@tracklang@add@es-PY	82
\@tracklang@add@cy-GB	83	\@tracklang@add@es-SV	82
\@tracklang@add@cymraeg	79	\@tracklang@add@es-UY	82
\@tracklang@add@czech	5, 59	\@tracklang@add@es-VE	82
\@tracklang@add@danish	5, 59	\@tracklang@add@esperanto	6, 60
\@tracklang@add@de-AT	83	\@tracklang@add@estonian	6, 60
\@tracklang@add@de-AT-1996	83	\@tracklang@add@ewe	60
\@tracklang@add@de-BE	80	\@tracklang@add@faroese	60
\@tracklang@add@de-CH	82	\@tracklang@add@farsi	60
\@tracklang@add@de-CH-1996	83	\@tracklang@add@fijian	60
\@tracklang@add@de-DE	80	\@tracklang@add@finnish	6, 60
\@tracklang@add@de-DE-1996	83	\@tracklang@add@flemish	73
\@tracklang@add@deutsch	74	\@tracklang@add@fr-BE	80
\@tracklang@add@divehi	59	\@tracklang@add@fr-CA	80
\@tracklang@add@dominicanspanish		\@tracklang@add@fr-CH	82
.....	77	\@tracklang@add@fr-FR	80
\@tracklang@add@dutch	5, 60	\@tracklang@add@fr-GG	80
\@tracklang@add@dzongkha	60	\@tracklang@add@fr-JE	81
\@tracklang@add@easternpunjabi	60	\@tracklang@add@francais	73
\@tracklang@add@ecudorianspanish		\@tracklang@add@france	73
.....	78	\@tracklang@add@french	5, 6, 60
\@tracklang@add@elsalvadorspanish		\@tracklang@add@frenchb	73
.....	78	\@tracklang@add@friulan	60
\@tracklang@add@en-AU	80	\@tracklang@add@friulano	74
\@tracklang@add@en-CA	80	\@tracklang@add@friulian	74
\@tracklang@add@en-GB	80	\@tracklang@add@fula	60
\@tracklang@add@en-GG	80	\@tracklang@add@furlan	74



<code>\@tracklang@add@ga-GB</code>	<a href="#">83</a>	<code>\@tracklang@add@it-SM</code>	<a href="#">81</a>
<code>\@tracklang@add@ga-IE</code>	<a href="#">83</a>	<code>\@tracklang@add@it-VA</code>	<a href="#">83</a>
<code>\@tracklang@add@gaeilge</code>	<a href="#">75</a>	<code>\@tracklang@add@italian</code>	<a href="#">6, 62</a>
<code>\@tracklang@add@gaelic</code>	<a href="#">77</a>	<code>\@tracklang@add@italy</code>	<a href="#">75</a>
<code>\@tracklang@add@galician</code>	<a href="#">6, 60</a>	<code>\@tracklang@add@japanese</code>	<a href="#">62</a>
<code>\@tracklang@add@galicien</code>	<a href="#">74</a>	<code>\@tracklang@add@javanese</code>	<a href="#">62</a>
<code>\@tracklang@add@ganda</code>	<a href="#">60</a>	<code>\@tracklang@add@jerseyenglish</code>	<a href="#">75</a>
<code>\@tracklang@add@gd-GB</code>	<a href="#">83</a>	<code>\@tracklang@add@jerseyfrench</code>	<a href="#">75</a>
<code>\@tracklang@add@georgian</code>	<a href="#">61</a>	<code>\@tracklang@add@kalaallisut</code>	<a href="#">62</a>
<code>\@tracklang@add@german</code>	<a href="#">3, 6, 61</a>	<code>\@tracklang@add@kanada</code>	<a href="#">62</a>
<code>\@tracklang@add@germanDE</code>	<a href="#">74</a>	<code>\@tracklang@add@kanuri</code>	<a href="#">62</a>
<code>\@tracklang@add@germanb</code>	<a href="#">74</a>	<code>\@tracklang@add@kashmiri</code>	<a href="#">62</a>
<code>\@tracklang@add@greek</code>	<a href="#">6, 61</a>	<code>\@tracklang@add@kazakh</code>	<a href="#">62</a>
<code>\@tracklang@add@guarani</code>	<a href="#">61</a>	<code>\@tracklang@add@khmer</code>	<a href="#">62</a>
<code>\@tracklang@add@guatemalanspanish</code>		<code>\@tracklang@add@kikuyu</code>	<a href="#">62</a>
	<a href="#">78</a>	<code>\@tracklang@add@kinyarwanda</code>	<a href="#">62</a>
<code>\@tracklang@add@guernseyenglish</code>	<a href="#">75</a>	<code>\@tracklang@add@kirundi</code>	<a href="#">62</a>
<code>\@tracklang@add@guernseyfrench</code>	<a href="#">75</a>	<code>\@tracklang@add@komi</code>	<a href="#">62</a>
<code>\@tracklang@add@gujarati</code>	<a href="#">61</a>	<code>\@tracklang@add@kongo</code>	<a href="#">63</a>
<code>\@tracklang@add@haitian</code>	<a href="#">61</a>	<code>\@tracklang@add@korean</code>	<a href="#">63</a>
<code>\@tracklang@add@hausa</code>	<a href="#">61</a>	<code>\@tracklang@add@kurdish</code>	<a href="#">63</a>
<code>\@tracklang@add@hebrew</code>	<a href="#">6, 61</a>	<code>\@tracklang@add@kurmanji</code>	<a href="#">74</a>
<code>\@tracklang@add@herero</code>	<a href="#">61</a>	<code>\@tracklang@add@kwanyama</code>	<a href="#">63</a>
<code>\@tracklang@add@hindi</code>	<a href="#">61</a>	<code>\@tracklang@add@kyrgyz</code>	<a href="#">63</a>
<code>\@tracklang@add@hirimotu</code>	<a href="#">61</a>	<code>\@tracklang@add@lao</code>	<a href="#">63</a>
<code>\@tracklang@add@honduranspanish</code>	<a href="#">78</a>	<code>\@tracklang@add@latein</code>	<a href="#">75</a>
<code>\@tracklang@add@hr-HR</code>	<a href="#">83</a>	<code>\@tracklang@add@latex</code>	<a href="#">4</a>
<code>\@tracklang@add@hu-HU</code>	<a href="#">83</a>	<code>\@tracklang@add@latin</code>	<a href="#">6, 63</a>
<code>\@tracklang@add@hungarian</code>	<a href="#">6, 74</a>	<code>\@tracklang@add@latvian</code>	<a href="#">63</a>
<code>\@tracklang@add@icelandic</code>	<a href="#">6, 61</a>	<code>\@tracklang@add@limburgish</code>	<a href="#">63</a>
<code>\@tracklang@add@id-IN</code>	<a href="#">83</a>	<code>\@tracklang@add@lingala</code>	<a href="#">63</a>
<code>\@tracklang@add@ido</code>	<a href="#">61</a>	<code>\@tracklang@add@lithuanian</code>	<a href="#">63</a>
<code>\@tracklang@add@igbo</code>	<a href="#">61</a>	<code>\@tracklang@add@lowersorbian</code>	<a href="#">6, 75</a>
<code>\@tracklang@add@indon</code>	<a href="#">74</a>	<code>\@tracklang@add@lsorbian</code>	<a href="#">63</a>
<code>\@tracklang@add@indonesian</code>	<a href="#">75</a>	<code>\@tracklang@add@lubakatanga</code>	<a href="#">63</a>
<code>\@tracklang@add@interlingua</code>	<a href="#">61</a>	<code>\@tracklang@add@luxembourgish</code>	<a href="#">63</a>
<code>\@tracklang@add@interlingue</code>	<a href="#">61</a>	<code>\@tracklang@add@macedonian</code>	<a href="#">63</a>
<code>\@tracklang@add@inuktitut</code>	<a href="#">62</a>	<code>\@tracklang@add@magyar</code>	<a href="#">6, 63</a>
<code>\@tracklang@add@inupiaq</code>	<a href="#">62</a>	<code>\@tracklang@add@malagasy</code>	<a href="#">64</a>
<code>\@tracklang@add@irish</code>	<a href="#">6, 62</a>	<code>\@tracklang@add@malay</code>	<a href="#">76</a>
<code>\@tracklang@add@isleofmanenglish</code>		<code>\@tracklang@add@malayalam</code>	<a href="#">64</a>
	<a href="#">76</a>	<code>\@tracklang@add@maltenglish</code>	<a href="#">76</a>
<code>\@tracklang@add@istriacountycroatian</code>		<code>\@tracklang@add@maltamaltese</code>	<a href="#">76</a>
	<a href="#">73</a>	<code>\@tracklang@add@maltese</code>	<a href="#">64</a>
<code>\@tracklang@add@istriacountyitalian</code>		<code>\@tracklang@add@manx</code>	<a href="#">64</a>
	<a href="#">73</a>	<code>\@tracklang@add@maori</code>	<a href="#">64</a>
<code>\@tracklang@add@it-CH</code>	<a href="#">83</a>	<code>\@tracklang@add@marathi</code>	<a href="#">64</a>
<code>\@tracklang@add@it-HR</code>	<a href="#">80</a>	<code>\@tracklang@add@marshallese</code>	<a href="#">64</a>
<code>\@tracklang@add@it-IT</code>	<a href="#">80</a>	<code>\@tracklang@add@mexicanspanish</code>	<a href="#">78</a>
<code>\@tracklang@add@it-SI</code>	<a href="#">81</a>	<code>\@tracklang@add@meyalu</code>	<a href="#">76</a>

\@tracklang@add@mongolian	64	\@tracklang@add@quechua	65
\@tracklang@add@ms-MY	83	\@tracklang@add@rm-CH	83
\@tracklang@add@mt-MT	81	\@tracklang@add@romanche	76
\@tracklang@add@nauruan	64	\@tracklang@add@romanian	6, 65
\@tracklang@add@naustrian	5, 73	\@tracklang@add@romansch	76
\@tracklang@add@navajo	64	\@tracklang@add@romansh	65
\@tracklang@add@nbelgiangerman	74	\@tracklang@add@rumantsch	76
\@tracklang@add@ndonga	64	\@tracklang@add@russian	6, 65
\@tracklang@add@nepali	64	\@tracklang@add@russianb	77
\@tracklang@add@netherlands	73	\@tracklang@add@samin	66
\@tracklang@add@newzealand	76	\@tracklang@add@samoan	66
\@tracklang@add@ngerman	3, 6, 74	\@tracklang@add@sango	66
\@tracklang@add@ngermanDE	74	\@tracklang@add@sanmarino	75
\@tracklang@add@ngermanb	74	\@tracklang@add@sanskrit	66
\@tracklang@add@nicaraguanspanish		\@tracklang@add@sardinian	66
	78	\@tracklang@add@scots	66
\@tracklang@add@nil	79	\@tracklang@add@scottish	6, 66
\@tracklang@add@nko	64	\@tracklang@add@serbian	6, 66
\@tracklang@add@nl-BE	80	\@tracklang@add@serbianc	77
\@tracklang@add@nl-NL	81	\@tracklang@add@serbianl	77
\@tracklang@add@norsk	6, 64	\@tracklang@add@shona	66
\@tracklang@add@northernndebele	64	\@tracklang@add@sindhi	66
\@tracklang@add@northernsotho	65	\@tracklang@add@sinhalese	66
\@tracklang@add@norwegian	76	\@tracklang@add@sl-SI	81
\@tracklang@add@nswissgerman	78	\@tracklang@add@slovak	6, 66
\@tracklang@add@nuosu	65	\@tracklang@add@slovene	6, 66
\@tracklang@add@nynorsk	6, 64	\@tracklang@add@sloveneistriaitalian	
\@tracklang@add@occitan	65		75
\@tracklang@add@ojibwe	65	\@tracklang@add@sloveneistriaslovenian	
\@tracklang@add@oriya	65		77
\@tracklang@add@oromo	65	\@tracklang@add@slovenia	77
\@tracklang@add@ossetian	65	\@tracklang@add@slovenian	77
\@tracklang@add@pali	65	\@tracklang@add@somali	66
\@tracklang@add@panamaspanish	78	\@tracklang@add@southernndebele	66
\@tracklang@add@paraguayspanish	78	\@tracklang@add@southernsotho	66
\@tracklang@add@pashto	65	\@tracklang@add@spainspanish	77
\@tracklang@add@persian	73	\@tracklang@add@spanish	6, 67
\@tracklang@add@peruvianspanish	78	\@tracklang@add@sudanese	67
\@tracklang@add@piedmontese	65	\@tracklang@add@swahili	67
\@tracklang@add@piemonteis	76	\@tracklang@add@swati	67
\@tracklang@add@polish	6, 65	\@tracklang@add@swedish	6, 67
\@tracklang@add@polutoniko	6, 76	\@tracklang@add@swissfrench	78
\@tracklang@add@polutonikogreek	76	\@tracklang@add@swissgerman	78
\@tracklang@add@portugal	76	\@tracklang@add@swissitalian	78
\@tracklang@add@portuges	65	\@tracklang@add@swissromansh	79
\@tracklang@add@portuguese	5, 6, 76	\@tracklang@add@syriac	67
\@tracklang@add@pt-BR	80	\@tracklang@add@tagalog	67
\@tracklang@add@pt-PT	81	\@tracklang@add@tahitian	67
\@tracklang@add@puertoricospanish		\@tracklang@add@tai	67
	78	\@tracklang@add@tajik	67

<code>\@tracklang@add@tamil</code> . . . . .	<a href="#">67</a>	<code>\@tracklang@dialects</code> . . . . .	
<code>\@tracklang@add@tatar</code> . . . . .	<a href="#">67</a>		<a href="#">21, 23, 33, 34, 50, 85</a>
<code>\@tracklang@add@telugu</code> . . . . .	<a href="#">67</a>	<code>\@tracklang@doifinlist</code> . . . . .	<a href="#">22</a>
<code>\@tracklang@add@thai</code> . . . . .	<a href="#">67</a>	<code>\@tracklang@element</code> . . . . .	<a href="#">22, 23, 84</a>
<code>\@tracklang@add@tibetan</code> . . . . .	<a href="#">67</a>	<code>\@tracklang@enamedef</code> . . . . .	<a href="#">9,</a>
<code>\@tracklang@add@tigrinya</code> . . . . .	<a href="#">67</a>		<a href="#">23–25, 27–32, 128, 136, 144, 145</a>
<code>\@tracklang@add@tonga</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@end@parseenv</code> . . . . .	<a href="#">19, 21</a>
<code>\@tracklang@add@tsonga</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@end@split@hyphen</code> . . . . .	<a href="#">20</a>
<code>\@tracklang@add@tswana</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@end@split@underscore</code>	
<code>\@tracklang@add@turkish</code> . . . . .	<a href="#">6, 68</a>		<a href="#">20</a>
<code>\@tracklang@add@turkmen</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@err</code> . . . . .	<a href="#">10,</a>
<code>\@tracklang@add@twi</code> . . . . .	<a href="#">68</a>		<a href="#">37, 56, 72, 124, 125, 127, 129–131</a>
<code>\@tracklang@add@ukraine</code> . . . . .	<a href="#">79</a>	<code>\@tracklang@extra@region@filelist</code>	
<code>\@tracklang@add@ukraineb</code> . . . . .	<a href="#">79</a>		<a href="#">48, 49</a>
<code>\@tracklang@add@ukrainian</code> . . . . .	<a href="#">6, 68</a>	<code>\@tracklang@extra@script@filelist</code>	
<code>\@tracklang@add@undetermined</code> . . . . .	<a href="#">68</a>		<a href="#">49</a>
<code>\@tracklang@add@uppersorbian</code> . . . . .	<a href="#">6, 79</a>	<code>\@tracklang@firstoftwo</code> . . . . .	
<code>\@tracklang@add@urdu</code> . . . . .	<a href="#">68</a>		<a href="#">10, 38, 39, 89–120</a>
<code>\@tracklang@add@uruguayspanish</code> . . . . .	<a href="#">78</a>	<code>\@tracklang@for</code> . . . . .	<a href="#">8, 33, 34, 49, 50, 85</a>
<code>\@tracklang@add@usorbian</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@forloop</code> . . . . .	<a href="#">9</a>
<code>\@tracklang@add@uyghur</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@fornoop</code> . . . . .	<a href="#">9</a>
<code>\@tracklang@add@uzbek</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@fullmatch</code> . . . . .	<a href="#">51, 52</a>
<code>\@tracklang@add@valencian</code> . . . . .	<a href="#">79</a>	<code>\@tracklang@hasfifthchar</code> . . . . .	<a href="#">38, 43</a>
<code>\@tracklang@add@valencien</code> . . . . .	<a href="#">79</a>	<code>\@tracklang@hasfourthchar</code> . . . . .	
<code>\@tracklang@add@vatican</code> . . . . .	<a href="#">75</a>		<a href="#">37, 40, 41, 43, 44</a>
<code>\@tracklang@add@venda</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@hasninthchar</code> . . . . .	<a href="#">38, 44</a>
<code>\@tracklang@add@venezuelanspanish</code>		<code>\@tracklang@hassecondchar</code> . . . . .	<a href="#">37, 40, 42</a>
	<a href="#">78</a>	<code>\@tracklang@hasthirdchar</code> . . . . .	
<code>\@tracklang@add@vietnamese</code> . . . . .	<a href="#">68</a>		<a href="#">37, 40, 41, 47, 54</a>
<code>\@tracklang@add@volapuk</code> . . . . .	<a href="#">68</a>	<code>\@tracklang@hook</code> . . . . .	<a href="#">126</a>
<code>\@tracklang@add@walloon</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@if@file@exists</code> . . . . .	<a href="#">86–120</a>
<code>\@tracklang@add@welsh</code> . . . . .	<a href="#">6, 69</a>	<code>\@tracklang@ifalldigits</code> . . . . .	<a href="#">39, 41</a>
<code>\@tracklang@add@westernfrisian</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@ifalpha</code> . . . . .	<a href="#">38, 39</a>
<code>\@tracklang@add@wolof</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@ifalphanumeric</code> . . . . .	<a href="#">39, 40</a>
<code>\@tracklang@add@xhosa</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@ifcseqcsname</code> . . . . .	
<code>\@tracklang@add@yiddish</code> . . . . .	<a href="#">69</a>		<a href="#">10, 107, 110, 113</a>
<code>\@tracklang@add@yoruba</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@ifdigit</code> . . . . .	<a href="#">38, 39, 44</a>
<code>\@tracklang@add@zhuang</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@ifinlist</code> . . . . .	<a href="#">22, 22, 25, 84</a>
<code>\@tracklang@add@zulu</code> . . . . .	<a href="#">69</a>	<code>\@tracklang@iflanguage@ii@tag</code> . . . . .	
<code>\@tracklang@addtohook</code> . . . . .	<a href="#">126, 126</a>		<a href="#">40, 40</a>
<code>\@tracklang@bestmatch</code> . . . . .	<a href="#">50, 51</a>	<code>\@tracklang@iflanguage@iii@tag</code>	
<code>\@tracklang@checklocale</code> . . . . .	<a href="#">12, 15, 16</a>		<a href="#">40, 41</a>
<code>\@tracklang@currentmatch</code> . . . . .	<a href="#">50, 51</a>	<code>\@tracklang@iforloop</code> . . . . .	<a href="#">9</a>
<code>\@tracklang@currfile</code> . . . . .	<a href="#">49</a>	<code>\@tracklang@ifregion@ii@tag</code> . . . . .	<a href="#">42, 42</a>
<code>\@tracklang@declareoptions</code> . . . . .	<a href="#">2, 3, 5</a>	<code>\@tracklang@ifregion@iii@tag</code> . . . . .	<a href="#">42</a>
<code>\@tracklang@declareoption</code> . . . . .		<code>\@tracklang@ifscripttag</code> . . . . .	<a href="#">43, 43</a>
	<a href="#">2, 2, 56, 56, 72, 79</a>	<code>\@tracklang@ifundef</code> . . . . .	
<code>\@tracklang@defscript</code> . . . . .	<a href="#">50</a>		<a href="#">7, 9, 10, 23, 25–27, 29–</a>
<code>\@tracklang@dialect</code> . . . . .			<a href="#">33, 36, 37, 45, 46, 53, 56, 72,</a>
	<a href="#">33, 34, 49–51, 53–55, 70, 71</a>		<a href="#">84, 85, 125–131, 136, 137, 144, 146</a>

\@tracklang@ifvariant@iv@tag	44, <a href="#">44</a>	\@tracklang@split@otherunderscore	
\@tracklang@info	11, 12, 15, 16		19, <a href="#">20</a>
\@tracklang@input	8, 15, 16	\@tracklang@split@otherunderscore@remainder	
\@tracklang@input@extra@region@filelist			20
	<a href="#">48</a>	\@tracklang@split@post	
\@tracklang@input@extra@region@files			19–21, 44, 45, 47, 48
	<a href="#">49</a> , <a href="#">142</a>	\@tracklang@split@pre	
\@tracklang@input@extra@script@filelist			19, 20, 44, 45, 47, 48
	<a href="#">49</a>	\@tracklang@split@underscore	19, <a href="#">19</a>
\@tracklang@input@extra@script@files		\@tracklang@split@underscore@remainder	
	<a href="#">49</a> , <a href="#">149</a>		20
\@tracklang@inputfile		\@tracklang@split@underscorerhypo	
	8, 48, 49, 130, 131		19, <a href="#">19</a> , 44, 45, 47, 48
\@tracklang@known@langs	24, <a href="#">24</a> , 25	\@tracklang@strip@prefix	10
\@tracklang@lang	23, 28, 50, 53, 54	\@tracklang@tag	45, 46
\@tracklang@languages		\@tracklang@test@if@file@exists@for@dialect	
	3, 7, <a href="#">21</a> , 23, 84, 85		86, 87, 89, <a href="#">89</a>
\@tracklang@locale@c	13, <a href="#">13</a>	\@tracklang@test@if@file@exists@for@langII	
\@tracklang@locale@posix	12, <a href="#">13</a>		91, <a href="#">115</a>
\@tracklang@namedef	9, 56, 70, 71	\@tracklang@test@if@file@exists@for@langIII	
\@tracklang@nameuse	9, 25–29, 31,		93, 94, 115, 116, <a href="#">116</a>
	32, 37, 46, 53, 136, 137, 144, 145	\@tracklang@test@if@file@exists@for@langIIIregion	
\@tracklang@next	39, 124, 131–135		102, 104, <a href="#">106</a>
\@tracklang@nnil	8, 9, 22, 39	\@tracklang@test@if@file@exists@for@langIIIscript	
\@tracklang@parse@extlang	44, 47		98–100, <a href="#">100</a>
\@tracklang@parse@langtag	46	\@tracklang@test@if@file@exists@for@langIIIscriptregion	
\@tracklang@parse@locale	18, <a href="#">18</a> , 53		90, <a href="#">95</a> , 109, 112
\@tracklang@parse@track@locale		\@tracklang@test@if@file@exists@for@langIIIscriptskipregion	
	52, 53, <a href="#">53</a>		113, 114, <a href="#">114</a>
\@tracklang@parse@variant	45, 48	\@tracklang@test@if@file@exists@for@langIIIskipregion	
\@tracklang@parse@env	19, <a href="#">21</a>		96, <a href="#">105</a> , 106
\@tracklang@parselangtag	46, 49	\@tracklang@test@if@file@exists@for@langIIIskipscript	
\@tracklang@pkgwarn	10, 11		96, 100, 101, <a href="#">101</a>
\@tracklang@prelangpkgcheck@hook		\@tracklang@test@if@file@exists@for@langIIIskipscriptregion	
	<a href="#">2</a>		97, <a href="#">113</a>
\@tracklang@providesresource	124	\@tracklang@test@if@file@exists@for@langIIIskipscriptskipregion	
\@tracklang@redefhook	127, 128, <a href="#">128</a>		114, <a href="#">114</a>
\@tracklang@regions	22, 23, 85	\@tracklang@test@if@file@exists@for@langIIIvariant	
\@tracklang@regions@restore@at			118, 119, <a href="#">119</a>
	135, 136, 142	\@tracklang@test@if@file@exists@for@langIIregion	
\@tracklang@restore@at	7, <a href="#">7</a> , 135		102, <a href="#">103</a> , 104
\@tracklang@result	19	\@tracklang@test@if@file@exists@for@langIIscript	
\@tracklang@sanitize	10		97, 98, <a href="#">98</a>
\@tracklang@scripts@restore@at		\@tracklang@test@if@file@exists@for@langIIscriptregion	
	143, 149		90, <a href="#">93</a> , 109
\@tracklang@secondoftwo		\@tracklang@test@if@file@exists@for@langIIscriptskipregion	
	10, 38, 39, 89		110, 111, <a href="#">111</a>
\@tracklang@split@hyphen	19, <a href="#">20</a>	\@tracklang@test@if@file@exists@for@langIIskipregion	
\@tracklang@split@hyphen@remainder			94, 103, <a href="#">103</a> , 105, 106
	20, 21		

<code>\@tracklang@test@if@file@exists@for@langI@skips@script</code> . . . . .	11, 124
. . . . .	94, 99, 99
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region</code>	
. . . . .	94, 95, 110
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	36, 56
. . . . .	111, 111
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	23, 23, 54, 70, 71
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	118, 118
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	23, 27, 36, 54, 55
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	4, 6, 23, 56
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	90, 91
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	36, 54, 56, 70, 71
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	107, 108
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	23, 37, 55, 71
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	85
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	92, 101
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	85
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	92, 97
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	5, 6
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	92, 93, 107
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	15, 16
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	108, 108
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	7
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	7, 20, 21, 135, 143
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	12
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	95,
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	96, 98–102, 104–106, 116, 117, 117
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	21, 23, 28, 30, 32, 33, 36, 37,
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	54, 72, 79, 124–129, 135, 136, 143
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	90
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	33–35, 125–128
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	87, 88, 117
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	86, 88, 117, 117
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	117–119, 119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	88, 90
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	103, 105, 106
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	86–89, 89
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35, 91–
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	100, 107, 108, 110, 111, 113, 114
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	89–119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35, 91–116, 118, 119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	89, 89, 90–119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	34, 35, 117–119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	12, 24, 50, 51, 72, 125–127
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	35, 90–116, 118–123
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	46, 53, 53
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	13, 15
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	86–89, 91, 118
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	11, 33–35, 86–123, 126–128
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	86–89, 93, 98, 103, 104, 115, 119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	11, 13–
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	18, 35, 45, 48, 52, 54, 130, 132–135
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	86–
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	89, 95, 100, 106, 109, 112, 116, 119
<code>\@tracklang@test@if@file@exists@for@langI@skips@script@region@code</code> . . . . .	15, 16

<code>\CurrentTrackedLanguage</code> . . . . .	
. . . . .	34, 35, 86–90, 97–100, 102, 104, 107, 109, 110, 112, 113, 115–123, 126–128
<code>\CurrentTrackedLanguageTag</code> . . . . .	
. . . . .	34–36, 89
<code>\CurrentTrackedRegion</code> . . . . .	34, 35, 91–97, 107, 110, 113, 117, 120–123
<code>\CurrentTrackedTag</code> . . . . .	86–123, 132–135
<b>D</b>	
<code>\DeclareOption</code> . . . . .	2
<code>\def</code> . . . . .	4, 7–33, 35–50, 52, 53, 56, 69–72, 79, 84–91, 93, 95, 97–101, 103–108, 110, 111, 113–120, 124–137, 143–145
<code>\directlua</code> . . . . .	13, 16, 17
<code>\do</code> . . . . .	3–6, 8, 33, 34, 49, 50, 85
<b>E</b>	
<code>\edef</code> . . . . .	7, 9, 10, 12, 15–17, 22–24, 33–35, 44–46, 48–51, 53, 54, 84, 86–101, 103–108, 110–116, 118–123, 125, 127, 135, 143
<code>\else</code> . . . . .	7–24, 30, 37–55, 70–72, 84, 85, 91–119, 121–125, 131–136, 143, 144
<code>\empty</code> . . . . .	9, 12, 13, 15–19, 21–24, 44–47, 50, 52–55, 84, 85, 90–120, 122, 123
<code>\end@tracklang@doifinlist</code> . . . . .	22
<code>\endcsname</code> . . . . .	2, 7–10, 21, 23, 28, 30, 32, 33, 36, 37, 54, 72, 79, 124–129, 135, 136, 143
<code>\endgroup</code> . . . . .	15, 16
<code>\endinput</code> . . . . .	7, 136, 143
<code>\endlinechar</code> . . . . .	15, 16
<code>\errhelp</code> . . . . .	10
<code>\errmessage</code> . . . . .	10
<code>\everyeof</code> . . . . .	15, 16
<code>\expandafter</code> . . . . .	4, 7–10, 13, 19, 21–23, 25, 28, 30, 37–48, 54, 55, 72, 79, 84, 124–126, 128, 135, 136, 143
<b>F</b>	
<code>\fi</code> . . . . .	7–25, 30, 37–56, 70–72, 84, 85, 91–108, 110–119, 122–125, 131–136, 143, 144
<code>\ForEachTrackedDialect</code> . . . . .	85
<code>\ForEachTrackedLanguage</code> . . . . .	85
<code>\ForEachTrackedRegion</code> . . . . .	85
<b>G</b>	
<code>\gdef</code> . . . . .	20, 21, 126, 128
<code>\GetTrackedDialectAdditional</code> . . . . .	32, 34
<code>\GetTrackedDialectFromLanguageTag</code> . . . . .	49
<code>\GetTrackedDialectFromMapping</code> . . . . .	33, 129
<code>\GetTrackedDialectModifier</code> . . . . .	29, 34
<code>\GetTrackedDialectScript</code> . . . . .	29, 34, 50
<code>\GetTrackedDialectSubLang</code> . . . . .	31, 34, 51
<code>\GetTrackedDialectToMapping</code> . . . . .	129
<code>\GetTrackedDialectVariant</code> . . . . .	31, 34, 51
<code>\GetTrackedLanguageTag</code> . . . . .	32, 34
<b>I</b>	
<code>\ifcsname</code> . . . . .	7, 8
<code>\ifeof</code> . . . . .	12
<code>\IfFileExists</code> . . . . .	12
<code>\IfHasTrackedDialectAdditional</code> . . . . .	32
<code>\IfHasTrackedDialectModifier</code> . . . . .	29
<code>\IfHasTrackedDialectScript</code> . . . . .	30, 30, 34
<code>\IfHasTrackedDialectSubLang</code> . . . . .	31
<code>\IfHasTrackedDialectVariant</code> . . . . .	31
<code>\IfHookHasMappingFromTrackedDialect</code> . . . . .	33, 129
<code>\ifnum</code> . . . . .	7, 14, 38, 39, 41–43, 51, 133, 143
<code>\IfTrackedDialect</code> . . . . .	33, 34, 50, 84, 86–89, 120
<code>\IfTrackedDialectHasMapping</code> . . . . .	125, 127, 128
<code>\IfTrackedDialectIsScriptCs</code> . . . . .	30
<code>\IfTrackedIsoCode</code> . . . . .	84
<code>\IfTrackedLanguage</code> . . . . .	33, 34, 84
<code>\IfTrackedLanguageFileExists</code> . . . . .	86, 132
<code>\IfTrackedLanguageFileExists@orig</code> . . . . .	120
<code>\IfTrackedLanguageFileExistsOmitDialectLabel</code> . . . . .	88, 133
<code>\IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion</code> . . . . .	87, 134
<code>\IfTrackedLanguageFileExistsOmitOnlyRegion</code> . . . . .	87, 135
<code>\IfTrackedLanguageHasIsoCode</code> . . . . .	32, 34, 35, 84, 90, 97–100, 102, 104, 109, 112, 115–122
<code>\ifTrackLangShowInfo</code> . . . . .	11, 11
<code>\ifTrackLangShowVerbose</code> . . . . .	11, 12
<code>\ifTrackLangShowWarnings</code> . . . . .	10, 11, 132–135

<code>\ifx</code> .....	3, 7–24, 30, 37–40, 44–56, 69–72, 84, 85, 91–120, 122–125, 131–136, 143, 144	<code>\ProcessOptions</code> .....	2
<code>\input</code> .....	2, 8, 143	<code>\providecommand</code> .....	2
<code>\inputencodingname</code> .....	12	<code>\ProvidesFile</code> .....	124, 125
<code>\inputlineno</code> .....	11	<code>\ProvidesPackage</code> .....	2, 143
<b>L</b>			
<code>\language</code> .....	35	<b>R</b>	
<code>\lccode</code> .....	38, 41, 43	<code>\relax</code> .....	7–9, 12–16, 19–21, 23, 37–44, 47, 51, 54, 69–72, 124, 131–135, 143, 144
<code>\let</code> 2, 4–6, 8–10, 12, 18, 19, 21, 23, 33, 34, 39, 44, 45, 47, 48, 50–53, 72, 79, 89–123, 126, 132, 133		<code>\RequirePackage</code> .....	143
<code>\LetTrackLangOption</code> .....	79, 80–83	<b>S</b>	
<code>\LetTrackLangSynonym</code> .....	79, 79	<code>\SetCurrentTrackedDialect</code> .....	33, 86–89, 120
<code>\long</code> .....	7–10, 12, 84–88, 120, 124	<code>\SetTrackedDialectAdditional</code> .....	31, 55
<b>M</b>			
<code>\mainbabelname</code> .....	4	<code>\SetTrackedDialectLabelMap</code> .....	72, 128
<code>\meaning</code> .....	10	<code>\SetTrackedDialectModifier</code> .....	29, 55, 70, 71
<code>\message</code> .....	11, 124, 125	<code>\SetTrackedDialectScript</code> .....	7, 29, 55, 72
<code>\MessageBreak</code> ..	11, 35, 124, 125, 130	<code>\SetTrackedDialectSubLang</code> ..	31, 55
<b>N</b>			
<code>\NeedsTeXFormat</code> .....	2, 143	<code>\SetTrackedDialectVariant</code> .....	30, 55, 70, 71
<code>\newif</code> .....	10, 11	<code>\shellescape</code> .....	13, 14
<code>\newlinechar</code> .....	11, 124	<code>\space</code> .....	3, 5, 13, 14, 18, 52, 124, 125, 127, 129–131
<code>\noexpand</code> .....	7, 15, 16, 135, 143	<code>\string</code> .....	3, 5, 13–18, 35, 45, 52, 124, 125, 127, 129–131
<code>\noop@TrackLangAddToHook</code> .....	125, 125, 133	<b>T</b>	
<code>\noop@TrackLangRedefHook</code> ..	127, 127	<code>\TeXOSQueryLocale</code> .....	15–17
<code>\noop@TrackLangRequestResource</code> .....	131, 131, 133	<code>\the</code> .....	11
<code>\noop@TrackLangRequireDialect</code> ..	131, 132	<code>\this@language</code> .....	3–7
<code>\noop@TrackLangRequireResource</code> ..	129, 129, 133	<code>\ThreeLetterExtIsoLanguageCode</code> ..	29, 36, 54
<code>\noop@TrackLangRequireResourceOrDo</code> ..	130, 130, 133	<code>\ThreeLetterIsoLanguageCode</code> ..	29, 36
<code>\number</code> .....	7, 135, 143	<code>\TrackedDialectClosestSubMatch</code> ..	49, 51
<b>O</b>			
<code>\openin</code> .....	12	<code>\TrackedDialectsFromLanguage</code> ..	28, 33, 34, 50
<code>\org@currenttrackedisocode</code> .....	121	<code>\TrackedIsoCodeFromLanguage</code> ..	28, 32, 35, 51, 86–89, 120–122
<b>P</b>			
<code>\PackageError</code> .....	10	<code>\TrackedLanguageFromDialect</code> ..	28, 30, 32, 34
<code>\PackageInfo</code> .....	3, 5, 11	<code>\TrackedLanguageFromIsoCode</code> ..	28
<code>\PackageWarning</code> .....	4, 6, 10, 11	<code>\TrackIfKnownLanguage</code> .....	46
<code>\pdfshellescape</code> .....	13, 14	<code>\TrackLangAddExtraRegionFile</code> ..	48
		<code>\TrackLangAddExtraScriptFile</code> ..	49
		<code>\TrackLangAddToCaptions</code> .....	127

<code>\TrackLangAddToHook</code> .....	<code>\TrackLangNewLanguage</code> .....	24, 56
..... 125, <a href="#">125</a> , <a href="#">127</a> , <a href="#">132</a> , <a href="#">133</a>	<code>\TrackLangNumericToAlphaIIRegion</code>	<a href="#">137</a>
<code>\TrackLangAlphaIIIToNumericRegion</code>	.....	<a href="#">137</a>
..... <a href="#">137</a>	<code>\TrackLangNumericToAlphaIRegion</code>	..... <a href="#">48</a> , <a href="#">136</a>
<code>\TrackLangAlphaIIToNumericRegion</code>	.....	<a href="#">21</a>
..... <a href="#">136</a>	<code>\TrackLangParseFromEnv</code> .....	<a href="#">18</a>
<code>\TrackLangDeclareDialectOption</code>	<code>\tracklangparsemod</code> .....	<a href="#">21</a> , <a href="#">21</a>
..... <a href="#">72</a> , <a href="#">72</a> , <a href="#">73–79</a>	<code>\TrackLangProvidePredefinedDialect</code>	..... <a href="#">69</a> , <a href="#">72</a>
<code>\TrackLangDeclareLanguageOption</code>	.....	<a href="#">56</a> , <a href="#">57–69</a>
..... <a href="#">56</a> , <a href="#">57–69</a>	<code>\TrackLangProvidePredefinedLanguage</code>	..... <a href="#">56</a> , <a href="#">56</a>
<code>\TrackLangEncodingName</code> .....	.....	<a href="#">124</a>
..... <a href="#">12</a>	<code>\TrackLangProvidesResource</code> ...	<a href="#">13</a> , <a href="#">15</a> , <a href="#">16</a> , <a href="#">52</a>
<code>\tracklangendparseenvatmod</code> ....	<code>\TrackLangQueryEnv</code> .....	<a href="#">13</a> , <a href="#">14</a> , <a href="#">15</a> , <a href="#">17</a>
..... <a href="#">21</a>	.....	<a href="#">127</a> , <a href="#">127</a>
<code>\TrackLangEnv</code> .....	<code>\TrackLangRedefHook</code> .....	<a href="#">127</a> , <a href="#">127</a>
..... <a href="#">12–18</a> , <a href="#">52</a>	<code>\TrackLangRegionMap</code> .....	..... <a href="#">48</a> , <a href="#">136</a> , <a href="#">136</a> , <a href="#">137–142</a>
<code>\TrackLangEnvCodeSet</code> .....	.....	<a href="#">131</a> , <a href="#">131</a> , <a href="#">132</a> , <a href="#">133</a>
..... <a href="#">18</a> , <a href="#">52</a>	<code>\TrackLangRequestResource</code> .....	..... <a href="#">124</a> , <a href="#">125</a> , <a href="#">131</a> , <a href="#">131</a> , <a href="#">132</a> , <a href="#">133</a>
<code>\TrackLangEnvLang</code> .....	.....	<a href="#">132</a> , <a href="#">133</a> , <a href="#">133</a>
..... <a href="#">18</a> , <a href="#">52</a>	<code>\TrackLangRequireDialect</code> .....	..... <a href="#">132–134</a>
<code>\TrackLangEnvModifier</code> .....	.....	<a href="#">134</a>
..... <a href="#">18</a> , <a href="#">52</a>	<code>\TrackLangRequireDialectOmitDialectLabel</code>	..... <a href="#">132</a> , <a href="#">133</a> , <a href="#">133</a>
<code>\TrackLangEnvTerritory</code> .....	.....	<a href="#">132–134</a>
..... <a href="#">18</a> , <a href="#">52</a>	<code>\TrackLangRequireDialectOmitLabelOmitOnlyRegion</code>	..... <a href="#">132–134</a>
<code>\TrackLangFromEnv</code> .....	.....	<a href="#">134</a>
..... <a href="#">52</a>	<code>\TrackLangRequireDialectOmitOnlyRegion</code>	..... <a href="#">132</a> , <a href="#">133</a> , <a href="#">134</a>
<code>\TrackLangGetDefaultScript</code> ....	.....	<a href="#">129</a> , <a href="#">129</a> , <a href="#">132–135</a>
..... <a href="#">27</a> , <a href="#">34</a> , <a href="#">50</a>	<code>\TrackLangRequireResource</code> .....	..... <a href="#">129</a> , <a href="#">129</a> , <a href="#">132–135</a>
<code>\TrackLangGetKnownCountry</code> .....	.....	<a href="#">130</a> , <a href="#">130</a> , <a href="#">132</a> , <a href="#">133</a>
..... <a href="#">27</a>	<code>\TrackLangScriptAlphaToDir</code> ...	<a href="#">145</a>
<code>\TrackLangGetKnownIsoThreeLetterLang</code>	<code>\TrackLangScriptAlphaToName</code> ...	<a href="#">145</a>
.....	.....	<a href="#">144</a>
..... <a href="#">26</a>	<code>\TrackLangScriptAlphaToNumeric</code>	<a href="#">144</a>
<code>\TrackLangGetKnownIsoThreeLetterLangB</code>	.....	<a href="#">145</a>
.....	<code>\TrackLangScriptGetParent</code> .....	<a href="#">145</a>
..... <a href="#">26</a>	.....	<a href="#">145</a>
<code>\TrackLangGetKnownIsoTwoLetterLang</code>	<code>\TrackLangScriptIfHasParent</code> ...	<a href="#">144</a>
.....	.....	<a href="#">144</a>
..... <a href="#">25</a>	<code>\TrackLangScriptIfKnownAlpha</code> ..	<a href="#">144</a>
<code>\TrackLangGetKnownLangFromIso</code> .	<code>\TrackLangScriptIfKnownNumeric</code>	<a href="#">144</a>
.....	.....	<a href="#">49</a> , <a href="#">143</a> , <a href="#">143</a> , <a href="#">146–149</a>
..... <a href="#">26</a> , <a href="#">50</a> , <a href="#">53</a>	<code>\TrackLangScriptMap</code> .....	..... <a href="#">49</a> , <a href="#">143</a> , <a href="#">143</a> , <a href="#">146–149</a>
<code>\TrackLangIfAlphaNumericChar</code> ..	.....	<a href="#">144</a>
..... <a href="#">39</a>	<code>\TrackLangScriptNumericToAlpha</code>	<a href="#">144</a>
<code>\TrackLangIfHasDefaultScript</code> <a href="#">27</a> , <a href="#">30</a>	.....	<a href="#">145</a>
<code>\TrackLangIfHasKnownCountry</code> ...	<code>\TrackLangScriptSetParent</code> .....	<a href="#">145</a>
..... <a href="#">27</a>	.....	<a href="#">11</a>
<code>\TrackLangIfKnownAlphaIIRegion</code> <a href="#">137</a>	<code>\TrackLangShowInfotru</code> .....	<a href="#">2</a> , <a href="#">11</a>
<code>\TrackLangIfKnownAlphaIRegion</code> <a href="#">136</a>	.....	
<code>\TrackLangIfKnownIsoThreeLetterLang</code>		
.....		
..... <a href="#">25</a>		
<code>\TrackLangIfKnownIsoThreeLetterLangB</code>		
.....		
..... <a href="#">26</a>		
<code>\TrackLangIfKnownIsoTwoLetterLang</code>		
.....		
..... <a href="#">25</a>		
<code>\TrackLangIfKnownLang</code> .....		
..... <a href="#">25</a>		
<code>\TrackLangIfKnownLangFromIso</code> ..		
.....		
..... <a href="#">26</a> , <a href="#">46</a> , <a href="#">53</a>		
<code>\TrackLangIfKnownNumericRegion</code>		
.....		
..... <a href="#">48</a> , <a href="#">137</a>		
<code>\TrackLangIfLanguageTag</code> ....		
..... <a href="#">40</a> , <a href="#">44</a>		
<code>\TrackLangIfRegionTag</code> .....		
..... <a href="#">41</a> , <a href="#">47</a>		
<code>\TrackLangIfScriptTag</code> .....		
..... <a href="#">42</a> , <a href="#">47</a>		
<code>\TrackLangIfVariantTag</code> .....		
..... <a href="#">43</a> , <a href="#">45</a>		
<code>\TrackLangLastTrackedDialect</code> ..		
..... <a href="#">23</a>		



<code>\TrackLangShowVerbosetrue</code> . . . . .	2		
<code>\TrackLangShowWarningstrue</code> . . . . .	10		
<code>\tracklangtmp</code> . . . . .	21		
<code>\TrackLanguageTag</code> . . . . .	4, <a href="#">45</a>		
<code>\TrackLocale</code> . . . . .	<a href="#">52</a>		
<code>\TrackPredefinedDialect</code> . . . . .	2, <a href="#">37</a>		
<code>\trans@languages</code> . . . . .	6		
<code>\TwoLetterIsoCountryCode</code> . . . . .	<a href="#">28</a>		
<code>\TwoLetterIsoLanguageCode</code> . . . . .	<a href="#">28</a> , <a href="#">36</a>		
			<b>U</b>
		<code>\uccode</code> . . . . .	<a href="#">42</a> , <a href="#">43</a>
		<code>\undefined</code> . . . . .	<a href="#">7–18</a> , <a href="#">48</a> , <a href="#">49</a> , <a href="#">52</a> , <a href="#">56</a> , <a href="#">124</a> , <a href="#">125</a> , <a href="#">136</a> , <a href="#">143</a>
			<b>X</b>
		<code>\xdef</code> . . . . .	<a href="#">124</a>
		<code>\xpg@bcp@loaded</code> . . . . .	<a href="#">4</a>
		<code>\xpg@loaded</code> . . . . .	<a href="#">3</a> , <a href="#">4</a>